Revision date: 09.12.2022 v. 1 Date of issue: 13.02.2015

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Developer D-100

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Developer
- 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Supplier:

BabbCo SA

SherwinBabbCo

15, rue des Frères Lumière Z.I. des EBISOIRES 78370 PLAISIR (France)

Tel: +33 (0)1.30.80.81.82

Tel: +33 (0)1.30.80.81.98

Fax: +33 (0)1.30.80.81.99

e-mail: babb-co@orange.fr e-mail: SherwinBabbco@orange.fr

http://www.babbco.fr Manufacturer:

NDT Europa BV damsluisweg 77 1332 EB almere / the netherlands phone +31 (0) 36 5495000 fax +31 (0) 36 5495011 e-mail: info@ndt-europa.nl http://www.ndt-europa.nl

· Further information obtainable from: Product safety department

1.4 Emergency telephone number:

Tel: +33 (0)1.40.05.48.48 (Centre anti-poison de Paris)

Tel: +33 (0)1.30.80.81.98

Additional information:

Attention Medical Authorities,

In accordance with law, to the best of its knowledge, and in good faith, SherwinBabb Co herewith indicates known, or possible,

arising from the use of the product described below.

There may be similar products on the market for which the suppliers have not indicated certain risks.

Suppliers are responsible for completing SDS forms in a manner that:

- does not give a product's user a false sense of security concerning the product's risks, or which,
- misrepresents the product in a manner that could be construed as unfair competition, or which,
- could lead to legal proceedings against the supplier.

Please contact us to answer any questions, or for additional information, concerning this document, or the product(s) described.

## **SECTION 2: Hazards identification**

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms





GHS02

GHS07

Signal word Danger

Revision date: 09.12.2022 v. 1 Date of issue: 13.02.2015

**Trade name: Developer D-100** 

(Contd. of page 1)

Hazard statements

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

**Precautionary statements** 

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P210

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P261 Avoid breathing mist/vapours

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P405 Store locked up.

- · 2.3 Other hazards See Chapters 3 and 15 for details.
- · Results of PBT and vPvB assessment
- · PBT: Not applicable. · vPvB: Not applicable.

## **SECTION 3: Composition/information on ingredients**

- 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

٠	Dano	erous	com	ponents:
	Dane	CI UUS	CUIII	Duncines.

CAS: 67-63-0 EINECS: 200-661-7

Reg.nr.: 01-2119457558-25

propan-2-ol 🏵 Flam. Lig. 2, H225; 🕩 Eye Irrit. 2, H319; STOT SE 3, H336 50-100%

Additional information: For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: First aid measures**

- 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Remove contaminated clothing.

- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

### **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

Water haze

Foam

ABC powder

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

Carbon monoxide and carbon dioxide

No further relevant information available.

- 5.3 Advice for firefighters
- **Special protective equipment for fire-fighters:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

Revision date: 09.12.2022 v. 1 Date of issue: 13.02.2015

**Trade name: Developer D-100** 

(Contd. of page 2)

### **SECTION 6: Accidental release measures**

#### · 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Store in cool, dry place in tightly closed receptacles.

Work only in fume cupboard.

Prevent formation of aerosols.

## Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Avoid contact of spilled material and runoff with soil and surface waterways. Wash thoroughly after handling. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material.

- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Store receptacle in fume cupboard.

Store in cool, dry conditions in well sealed receptacles.

· 7.3 Specific end use(s) No further relevant information available.

#### **SECTION 8: Exposure controls/personal protection**

#### · 8.1 Control parameters

### Ingredients with limit values that require monitoring at the workplace:

CAS: 67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm

- · Regulatory information WEL: EH40/2020
- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

**Respiratory protection:** 

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Respiratory protection:

When using a liquid based on organic compound:

- Recommended for organic vapour (type A)

(Contd. on page 4)

Revision date: 09.12.2022 v. 1 Date of issue: 13.02.2015

**Trade name: Developer D-100** 

(Contd. of page 3)

When using a dry powder:

- Recommended for particulate filters (type P)
- · Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Material of gloves Natural rubber, NR
- · Penetration time of glove material
- The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- Eye/face protection



Safety glasses

Tightly sealed goggles

**Body protection:** 

Protective work clothing Use protective suit.

## **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties

General Information

Physical state
Colour:
Odour:
Odour threshold:
Melting point/freezing point:
Fluid
White
Characteristic
Not determined.
Undetermined.

· Boiling point or initial boiling point and boiling range 82 °C

Flammability Highly flammable.

Lower and upper explosion limit

· Lower: 2 Vol %

· **Upper:** 12 Vol %

Flash point: 13 °C (ASTM D-93)

Auto-ignition temperature: 425 °C

Decomposition temperature: Not determined.

pH Not determined.

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

Solubility

water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

· Vapour pressure at 20 °C: 43 hPa

Density and/or relative density

Density at 20 °C: 0.859 g/cm³ (ASTM D-1298)

Relative density

Vapour density

Not determined.

Not determined.

9.2 Other information

Appearance:

· Form: Fluid

(Contd. on page 5)

Revision date: 09.12.2022 v. 1 Date of issue: 13.02.2015

**Trade name: Developer D-100** 

(Contd. of page 4)

· Important information on protection of health and

environment, and on safety.

**Auto-ignition temperature:** Product is not selfigniting.

• Explosive properties: Not determined.

Solvent content:

Organic solvents: 87.4 % **VOC (1999/13/EG)** 87.40 % **Solids content:** 12.5 %

Change in condition

**Evaporation rate** Not determined.

· Information with regard to physical hazard classes

**Explosives** not applicable Flammable gases not applicable Aerosols not applicable Oxidising gases not applicable Gases under pressure not applicable

Flammable liquids Highly flammable liquid and vapour.

Flammable solids not applicable · Self-reactive substances and mixtures not applicable **Pyrophoric liquids** not applicable **Pyrophoric solids** not applicable · Self-heating substances and mixtures not applicable

· Substances and mixtures, which emit flammable gases in

contact with water not applicable **Oxidising liquids** not applicable **Oxidising solids** not applicable Organic peroxides not applicable · Corrosive to metals not applicable **Desensitised explosives** not applicable

### **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

Stable at environment temperature.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## **SECTION 11: Toxicological information**

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Information on hazardous ingredients

#### · LD/LC50 values relevant for classification:

#### CAS: 67-63-0 propan-2-ol Oral LD50 5,045 mg/kg (rat) LD50 12,800 mg/kg (rabbit) Dermal Inhalative LC50/4h >20 mg/kg (rat)

- Serious eye damage/irritation Causes serious eye irritation.
- · STOT-single exposure May cause drowsiness or dizziness.

(Contd. on page 6)

Revision date: 09.12.2022 v. 1 Date of issue: 13.02.2015

**Trade name: Developer D-100** 

(Contd. of page 5)

· 11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

### **SECTION 12: Ecological information**

- 12.1 Toxicity
- **Aquatic toxicity:**

Information on hazardous ingredients

#### CAS: 67-63-0 propan-2-ol

LC50/ 96 h >100 mg/l (Fish)

EC50/ 48 h >100 mg/l (daphnia)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties.
- 12.7 Other adverse effects
- Additional ecological information:
- General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

### **SECTION 13: Disposal considerations**

- 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Waste/ unused products

Collect all waste in suitable and labelled containers and dispose according to local legislation.

- · Uncleaned packaging:
- · Recommendation:

Waste / used products

Waste products and empty packages dispose of in accordance with local regulations.

### SECTION 14: Transport information

- 14.1 UN number or ID number
- · ADR, IMDG, IATA UN1219
- · 14.2 UN proper shipping name
- · ADR, IMDG, IATA ISOPROPANOL (ISOPROPYL ALCOHOL) mixture
- 14.3 Transport hazard class(es)
- ADR, IMDG, IATA



· Class 3 Flammable liquids.

Label

(Contd. on page 7)

Revision date: 09.12.2022 v. 1 Date of issue: 13.02.2015

**Trade name: Developer D-100** 

	(Contd. of page 6)
· 14.4 Packing group · ADR, IMDG, IATA	II
14.5 Environmental hazards: Marine pollutant:	No
<ul> <li>14.6 Special precautions for user</li> <li>Hazard identification number (Kemler code):</li> <li>EMS Number:</li> <li>Stowage Category</li> </ul>	Warning: Flammable liquids. 33 F-E,S-D B
· 14.7 Maritime transport in bulk according to IM instruments	O Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
Transport category Tunnel restriction code	2 D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· IATA · Remarks:	Max. net quantity per package - Passenger Aircraft 5 L Max. net quantity per package - Cargo Aircraft 60 L Max. net quantity per package - Limited quantities 1 L Packaging Instruction: Passenger Aircraft - PI 353 Cargo aircraft - PI 364 Limited quantities - PI Y341
· UN "Model Regulation":	UN 1219 ISOPROPANOL (ISOPROPYL ALCOHOL) MIXTURE, 3, II

### **SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

(Contd. on page 8)

Revision date: 09.12.2022 v. 1 Date of issue: 13.02.2015

**Trade name: Developer D-100** 

(Contd. of page 7)

European regulation (UK REACH) requires that in paragraph 16 all H sentences dealing with raw materials appearing in paragraph 2 and 3 be written. This regulation states which sentences will finally be written on labels (paragraph 3) depending on the respective concentration of every raw material in the preparation. That's why some or all of the sentences or signs shows in paragraph 16 may not be written on the label. BabbCo complies with the law. Any MSDS with the H sentences of the raw material not shown in the paragraph 16 does not comply with regulation.

#### Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Prepared by NDT Europa BV

### Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

\* Data compared to the previous version altered.