

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH)) , as retained and amended in UK law

BOLICONE M4 ALU PA

Regulation (EU) n. 2020/878

Safety Data Sheet date: 4/11/2024, version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name: BOLICONE M4 ALU PA
SDS code: 100399EU
UFI: NXVG-HAR8-DA9N-R53A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Industrial uses
Paint/Coating

1.3. Details of the supplier of the safety data sheet

Manufacturers:

Socomore SASU - Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - France
-Tel. +33 (0)2 97 43 76 90

Manufacturing - Parc Gohelis - 56250 ELVEN France - Tel +33 (0)2 97 43 76 83 - Fax +33 (0)2 97 54 50 26

Socomore Ireland Ltd. - Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922 / Fax +353 21 4889923 / ireland@socomore.com

Distributors:

Socomore SASU - Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - France
-Tel. +33 (0)2 97 43 76 90

Manufacturing - Parc Gohelis - 56250 ELVEN France - Tel +33 (0)2 97 43 76 83 - Fax +33 (0)2 97 54 50 26

Socomore Ireland Ltd. - Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922 / Fax +353 21 4889923 / ireland@socomore.com

Competent person responsible for the safety data sheet:

msdsinformation-eu@socomore.com

1.4. Emergency telephone number

UK NPIS 0344 892 0111
France : ORFILA (INRS) +33 (0)1 45 42 59 59
International : CHEMTEL +1-813-248-0585.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

Amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567

- ⚠ Danger, Flam. Liq. 2, Highly flammable liquid and vapour.
- ⚠ Warning, Skin Irrit. 2, Causes skin irritation.
- ⚠ Warning, Eye Irrit. 2, Causes serious eye irritation.
- ⚠ Warning, STOT SE 3, May cause respiratory irritation.

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH)) , as retained and amended in UK law**BOLICONE M4 ALU PA**

⚠ Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:



Danger

Hazard statements:

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P370+P378 In case of fire: Use dry sand, chemical powder or alcohol-resistant foam for extinction.

P403+P235 Store in a well-ventilated place. Keep cool.

Special Provisions:

EUH208 Contains N-(3-TRIMETHOXYSILYL)PROPYL)ETHYLENEDIAMINE. May produce an allergic reaction.

Contains

Xylene, mixture of isomers

reaction mass of ethylbenzene and xylene

2-methylpropan-1-ol; iso-butanol

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration $\geq 0.1\%$

SECTION 3: Composition/information on ingredients**3.1. Substances**

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH)) , as retained and amended in UK law

BOLICONE M4 ALU PA

Qty	Name	Ident. Number	Classification
>= 20% - < 25%	Xylene	CAS: 1330-20-7 EC: 215-535-7 REACH No.: 01-2119488216-32	<p> ⚠ 2.6/3 Flam. Liq. 3 H226 ⚠ 3.10/1 Asp. Tox. 1 H304 ⚠ 3.1/4/Dermal Acute Tox. 4 H312 ⚠ 3.1/4/Inhal Acute Tox. 4 H332 ⚠ 3.2/2 Skin Irrit. 2 H315 ⚠ 3.3/2 Eye Irrit. 2 H319 ⚠ 3.8/3 STOT SE 3 H335 ⚠ 3.9/2 STOT RE 2 H373 4.1/C3 Aquatic Chronic 3 H412 Acute Toxicity Estimate: ATE - Dermal 1100 mg/kg bw ATE - Inhalation (Vapours) 11 mg/l ATE - Inhalation (Dust/mist) 1,5 mg/l ATE - Inhalation (Gas) 5000 ppmV </p>
>= 10% - < 12.5%	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	EC: 918-481-9 REACH No.: 01-2119457273-39	<p> ⚠ 3.10/1 Asp. Tox. 1 H304 EUH066 DECLP (CLP)* </p>
>= 5% - < 7%	n-butyl acetate	Index number: 607-025-00-1 CAS: 123-86-4 EC: 204-658-1 REACH No.: 01-2119485493-29	<p> ⚠ 2.6/3 Flam. Liq. 3 H226 ⚠ 3.8/3 STOT SE 3 H336 EUH066 </p>
>= 1% - < 3%	reaction mass of ethylbenzene and xylene	CAS: 1330-20-7 EC: 905-588-0 REACH No.: 01-2119488216-32	<p> ⚠ 2.6/3 Flam. Liq. 3 H226 ⚠ 3.10/1 Asp. Tox. 1 H304 ⚠ 3.1/4/Dermal Acute Tox. 4 H312 ⚠ 3.1/4/Inhal Acute Tox. 4 H332 ⚠ 3.2/2 Skin Irrit. 2 H315 ⚠ 3.3/2 Eye Irrit. 2 H319 ⚠ 3.8/3 STOT SE 3 H335 ⚠ 3.9/2 STOT RE 2 H373 4.1/C3 Aquatic Chronic 3 H412 Acute Toxicity Estimate: ATE - Dermal 1100 mg/kg bw ATE - Inhalation (Vapours) 11 mg/l </p>
>= 1% - < 3%	butan-1-ol; n-butanol	Index number: 603-004-00-6	<p> ⚠ 2.6/3 Flam. Liq. 3 H226 ⚠ 3.8/3 STOT SE 3 H335 </p>

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH)) , as retained and amended in UK law

BOLICONE M4 ALU PA

		<p>CAS: 71-36-3 EC: 200-751-6 REACH No.: 01-2119484630-38</p>	<p>⚠ 3.2/2 Skin Irrit. 2 H315 ⚠ 3.3/1 Eye Dam. 1 H318 ⚠ 3.8/3 STOT SE 3 H336 ⚠ 3.1/4/Oral Acute Tox. 4 H302 Acute Toxicity Estimate: ATE - Oral 500 mg/kg bw ATE - Dermal 3430 mg/kg bw ATE - Inhalation (Dust/mist) 17,76 mg/l</p>
>= 1% - < 3%	2-methylpropan-1-ol; iso-butanol	<p>CAS: 78-83-1 EC: 201-148-0 REACH No.: 01-2119484609-23</p>	<p>⚠ 2.6/3 Flam. Liq. 3 H226 ⚠ 3.1/4/Inhal Acute Tox. 4 H332 ⚠ 3.2/2 Skin Irrit. 2 H315 ⚠ 3.3/1 Eye Dam. 1 H318 ⚠ 3.8/3 STOT SE 3 H335 ⚠ 3.8/3 STOT SE 3 H336</p>
>= 0.5% - < 1%	N-(3-TRIMETHOXYSILYL) PROPYL) ETHYLENEDIAMINE	<p>CAS: 1760-24-3 EC: 217-164-6 REACH No.: 01-2119970215-39</p>	<p>⚠ 3.1/4/Inhal Acute Tox. 4 H332 ⚠ 3.3/1 Eye Dam. 1 H318 ⚠ 3.4.2/1B Skin Sens. 1B H317 ⚠ 3.9/2 STOT RE 2 H373 Acute Toxicity Estimate: ATE - Oral 2295 mg/kg bw ATE - Dermal 2001 mg/kg bw ATE - Inhalation (Dust/mist) 1,49 mg/l</p>
>= 0.5% - < 1%	acide 2-éthylhexanoïque - Manganese Salt	<p>CAS: 15956-58-8 EC: 240-085-3 REACH No.: 01-2119979087-23</p>	<p>⚠ 3.3/2 Eye Irrit. 2 H319 ⚠ 3.7/1B Repr. 1B H360 (Inhalation, Skin) ⚠ 3.9/2 STOT RE 2 H373 4.1/C3 Aquatic Chronic 3 H412</p>
>= 0.5% - < 1%	AD-1500 (* l'identité chimique spécifique a été refusée conformément à l'article	<p>EC: 484-050-2 REACH No.: 01-0000020228-74</p>	<p>⚠ 4.1/A1 Aquatic Acute 1 H400</p>
>= 0.3% - < 0.5%	ethylbenzene	<p>Index number: 601-023-00-4 CAS: 100-41-4 EC: 202-849-4 REACH No.: 01-2119489370-35</p>	<p>⚠ 2.6/2 Flam. Liq. 2 H225 ⚠ 3.2/2 Skin Irrit. 2 H315 ⚠ 3.3/2 Eye Irrit. 2 H319 4.1/C3 Aquatic Chronic 3 H412 ⚠ 3.1/4/Inhal Acute Tox. 4 H332 ⚠ 3.9/2 STOT RE 2 H373 (hearing organs) ⚠ 3.10/1 Asp. Tox. 1 H304</p>

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH)) , as retained and amended in UK law

BOLICONE M4 ALU PA

			Acute Toxicity Estimate: ATE - Inhalation (Vapours) 11 mg/l
>= 0.1% - < 0.25%	methanol	Index number: CAS: EC: REACH No.: 603-001-00-X 67-56-1 200-659-6 01- 2119433307 -44	<p> ◆ 2.6/2 Flam. Liq. 2 H225 ◆ 3.8/1 STOT SE 1 H370 (eyes, central nervous system) ◆ 3.1/3/Oral Acute Tox. 3 H301 ◆ 3.1/3/Dermal Acute Tox. 3 H311 ◆ 3.1/3/Inhal Acute Tox. 3 H331 Specific Concentration Limits: C >= 10%: STOT SE 1 H370 3% <= C < 10%: STOT SE 2 H371 Acute Toxicity Estimate: ATE - Oral 5000 mg/kg bw ATE - Dermal 300 mg/kg bw ATE - Inhalation (Vapours) 3 mg/l </p>
>= 0.001% - < 0.1%	toluene	Index number: CAS: EC: REACH No.: 601-021-00-3 108-88-3 203-625-9 01- 2119471310 -51	<p> ◆ 2.6/2 Flam. Liq. 2 H225 ◆ 3.7/2 Repr. 2 H361d ◆ 3.10/1 Asp. Tox. 1 H304 ◆ 3.9/2 STOT RE 2 H373 ◆ 3.2/2 Skin Irrit. 2 H315 ◆ 3.8/3 STOT SE 3 H336 4.1/C3 Aquatic Chronic 3 H412 </p>
>= 0.001% - < 0.1%	Cumene	Index number: CAS: EC: 601-024-00-X 98-82-8 202-704-5	<p> ◆ 2.6/3 Flam. Liq. 3 H226 ◆ 3.6/1B Carc. 1B H350 ◆ 3.10/1 Asp. Tox. 1 H304 ◆ 3.8/3 STOT SE 3 H335 ◆ 4.1/C2 Aquatic Chronic 2 H411 </p>

*DECLP (CLP): Substance classified in accordance with Note P, Annex VI of EC Regulation (EC) 1272/2008. The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 shall apply.

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH)) , as retained and amended in UK law**BOLICONE M4 ALU PA**

product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting. Obtain a medical examination.

In case of Inhalation:

In case of inhalation, consult a doctor immediately and show the packing or label.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

No particular treatment.

SECTION 5: Firefighting measures**5.1. Extinguishing media**

Suitable extinguishing media:

Foam.

Carbon dioxide (CO₂)

Dry powder

Extinguishing media which must not be used for safety reasons:

High power water jet

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH)) , as retained and amended in UK law**BOLICONE M4 ALU PA**

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Avoid contact with skin and eyes, inhalation of vapours and mists.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, ensure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

7.2. Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Store at ambient temperatures. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

7.3. Specific end use(s)

None in particular

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

Occupational exposure limit values

Xylene - CAS: 1330-20-7

- OEL Type: National - TWA(8h): 221 mg/m³, 50 ppm - STEL(15min (Miw)): 442 mg/m³, 100 ppm - Behaviour: Binding - Notes: France VLEC - TMP N° 4Bis, 84

- OEL Type: National - TWA(8h): 440 mg/m³, 100 ppm - Notes: Germany - DFG, H

- OEL Type: National - TWA(8h): 220 mg/m³, 50 ppm - STEL: 441 mg/m³, 100 ppm - Notes: UK (WELs)

- OEL Type: EU - TWA(8h): 221 mg/m³, 50 ppm - STEL: 442 mg/m³, 100 ppm - Notes: Skin

- OEL Type: ACGIH - TWA(8h): 20 ppm - Notes: A4, BEI - URT and eye irr; hematologic eff; CNS impair

- OEL Type: National - TWA: 435 mg/m³, 100 ppm - STEL: 870 mg/m³, 200 ppm - Notes: Swiss - SUVA

- OEL Type: National - TWA: 221 mg/m³, 50 ppm - STEL(15min (Miw)): 442 mg/m³, 100

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH)) , as retained and amended in UK law

BOLICONE M4 ALU PA

ppm - Notes: Österreich

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

- OEL Type: National - TWA: 1000 mg/m³ - STEL: 1500 mg/m³ - Behaviour: Indicative -

Notes: France

- OEL Type: National - TWA: 1200 mg/m³, 184 ppm - Notes: ExxonMobil

- OEL Type: EU - TWA: 1050 mg/m³ - Notes: EU HSPA

- OEL Type: National - TWA: 25 ppm - Notes: Denmark

- OEL Type: National - TWA: 300 mg/m³, 50 ppm - Notes: Germany

- OEL Type: National - TWA: 300 mg/m³ - STEL: 900 mg/m³ - Notes: Poland

- OEL Type: National - TWA: 150 mg/m³, 25 ppm - STEL: 300 mg/m³, 50 ppm - Notes:

Sweden

- OEL Type: National - TWA: 300 mg/m³, 50 ppm - STEL: 600 mg/m³, 100 ppm - Notes:

Switzerland

- OEL Type: National - TWA: 300 mg/m³ - STEL: 900 mg/m³ - Notes: Poland (NDS, NDSch)

n-butyl acetate - CAS: 123-86-4

- OEL Type: National - TWA: 241 mg/m³, 50 ppm - STEL: 723 mg/m³, 150 ppm -

Behaviour: Binding - Notes: France, VLEPC

- OEL Type: National - TWA: 150 ppm - STEL: 200 ppm - Notes: United Kingdom

- OEL Type: National - TWA(8h): 300 mg/m³, 62 ppm - Notes: Germany

- OEL Type: ACGIH - TWA(8h): 50 ppm - STEL: 150 ppm - Notes: Eye and URT irr

- OEL Type: National - TWA(8h): 238 mg/m³, 50 ppm - STEL: 712 mg/m³, 150 ppm -

Notes: BELGIQUE

- OEL Type: National - TWA(8h): 480 mg/m³, 99 ppm - Notes: PAYS-BAS

- OEL Type: National - TWA: 480 mg/m³, 100 ppm - STEL(Mow): 480 mg/m³, 100 ppm -

Notes: Österreich

- OEL Type: EU - TWA(8h): 241 mg/m³, 50 ppm - STEL: 723 mg/m³, 150 ppm

reaction mass of ethylbenzene and xylene - CAS: 1330-20-7

- OEL Type: National - TWA(8h): 221 mg/m³, 50 ppm - STEL: 442 mg/m³, 100 ppm -

Notes: France VLEC - TMP N° 4Bis, 84

- OEL Type: National - TWA(8h): 440 mg/m³, 100 ppm - Notes: Germany - DFG, H

- OEL Type: National - TWA(8h): 220 mg/m³, 50 ppm - STEL: 441 mg/m³, 100 ppm -

Notes: UK (WELs)

- OEL Type: EU - TWA(8h): 221 mg/m³, 50 ppm - STEL: 442 mg/m³, 100 ppm - Notes:

Skin

- OEL Type: ACGIH - TWA(8h): 20 ppm - Notes: A4, BEI - URT and eye irr; hematologic eff; CNS impair

- OEL Type: National - TWA: 435 mg/m³, 100 ppm - STEL: 870 mg/m³, 200 ppm - Notes:

Swiss - SUVA

- OEL Type: National - TWA: 221 mg/m³, 50 ppm - STEL(15min (Miw)): 442 mg/m³, 100

ppm - Notes: Österreich

- OEL Type: National - TWA: 221 mg/m³, 50 ppm - Notes: TWA:Poland

butan-1-ol; n-butanol - CAS: 71-36-3

- OEL Type: ACGIH - TWA(8h): 20 ppm - Notes: Eye and URT irr

- OEL Type: National - STEL: 150 mg/m³, 50 ppm - Notes: France

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH)) , as retained and amended in UK law**BOLICONE M4 ALU PA**

2-methylpropan-1-ol; iso-butanol - CAS: 78-83-1

- OEL Type: ACGIH - TWA(8h): 50 ppm - Notes: Skin and eye irr
- OEL Type: National - TWA: 310 mg/m³, 100 ppm - Notes: Germany TRGS 900

acide 2-éthylhexanoïque - Manganese Salt - CAS: 15956-58-8

- OEL Type: National - TWA: 0.2 mg/m³ - Behaviour: Indicative - Notes: France (INRS) ; fraction inhalable (manganèse)
- OEL Type: National - TWA: 0.05 mg/m³ - Behaviour: Indicative - Notes: France (INRS) ; fraction alvéolaire manganèse)

ethylbenzene - CAS: 100-41-4

- OEL Type: National - TWA(8h): 88.4 mg/m³, 20 ppm - Notes: Germany - EU, H
- OEL Type: National - TWA(8h): 88.4 mg/m³, 20 ppm - STEL: 442 mg/m³, 100 ppm - Notes: France VLEC - TMP N° 84
- OEL Type: National - TWA(8h): 441 mg/m³, 100 ppm - STEL: 552 mg/m³, 125 ppm - Notes: UK (WELs)
- OEL Type: EU - TWA(8h): 442 mg/m³, 100 ppm - STEL: 884 mg/m³, 200 ppm - Notes: Skin
- OEL Type: ACGIH - TWA(8h): 20 ppm - Notes: OTO; A3, BEI - URT & eye irr; ototoxicity; kidney eff; CNS impair
- OEL Type: National - STEL: 220 mg/m³ - Notes: Swiss
- OEL Type: MAK - TWA: 440 mg/m³, 100 ppm - STEL(5 min (Mow)): 880 mg/m³, 200 ppm - Notes: Osterreich

methanol - CAS: 67-56-1

- OEL Type: National - TWA(8h): 260 mg/m³, 200 ppm - STEL: 1300 mg/m³, 1000 ppm - Notes: France VLEC
- OEL Type: EU - TWA(8h): 260 mg/m³, 200 ppm - Notes: Skin
- OEL Type: ACGIH - TWA(8h): 200 ppm - STEL: 250 ppm - Notes: Skin, BEI - Headache, eye dam, dizziness, nausea
- OEL Type: TWA - TWA: 200 ppm

toluene - CAS: 108-88-3

- OEL Type: National - TWA(8h): 190 mg/m³ - Notes: Germany - DFG, H, Y
- OEL Type: National - TWA(8h): 76.8 mg/m³, 20 ppm - STEL(15min (Miw)): 384 mg/m³, 100 ppm - Behaviour: Binding - Notes: France VLEC - TMP N° 4bis, 84 ; peau
- OEL Type: EU - TWA(8h): 192 mg/m³, 50 ppm - STEL: 384 mg/m³, 100 ppm - Notes: Skin
- OEL Type: National - TWA: 191 mg/m³, 50 ppm - STEL: 384 mg/m³, 100 ppm - Notes: UK (WELs)
- OEL Type: ACGIH - TWA(8h): 20 ppm - Notes: OTO; A4; BEI - CNS, visual & hearing impair; female repro system eff; pregnancy loss
- OEL Type: MAK - TWA: 190 mg/m³, 50 ppm - STEL(15min (Miw)): 380 mg/m³, 100 ppm - Notes: Osterreich

Cumene - CAS: 98-82-8

- OEL Type: EU - TWA(8h): 50 mg/m³, 10 ppm - STEL: 250 mg/m³, 50 ppm - Notes: Skin
- OEL Type: ACGIH - TWA(8h): 5 ppm - Notes: A3 - URT adenoma, neurological eff
- OEL Type: National - TWA(8h): 50 mg/m³, 10 ppm - STEL(15min (Miw)): 250 mg/m³, 50 ppm - Behaviour: Binding - Notes: France, VLEPC / peau

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH)) , as retained and amended in UK law**BOLICONE M4 ALU PA**

- OEL Type: National - TWA: 50 mg/m³ - STEL: 250 mg/m³ - Notes: Poland (Skin / skóra)

DNEL Exposure Limit Values

Xylene - CAS: 1330-20-7

Worker Professional: 289 mg/m³ - Consumer: 174 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Professional: 289 mg/m³ - Consumer: 174 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Professional: 180 mg/kg b.w./day - Consumer: 108 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Professional: 77 mg/m³ - Consumer: 14.8 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 1.6 mg/kg b.w./day - Exposure: Human Oral - Frequency: Long Term, systemic effects

n-butyl acetate - CAS: 123-86-4

Worker Industry: 11 mg/kg - Consumer: 6 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 300 mg/m³ - Consumer: 35.7 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 2 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

Worker Industry: 600 mg/m³ - Consumer: 300 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 11 mg/kg - Consumer: 2 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects

Worker Industry: 600 mg/m³ - Consumer: 300 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Industry: 300 mg/m³ - Consumer: 35.7 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects

Worker Industry: 11 mg/kg - Consumer: 6 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects

reaction mass of ethylbenzene and xylene - CAS: 1330-20-7

Worker Industry: 77 mg/m³ - Consumer: 14.8 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Industry: 289 mg/m³ - Consumer: 174 mg/kg b.w./day - Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Industry: 289 mg/m³ - Consumer: 174 mg/kg b.w./day - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 180 mg/kg b.w./day - Consumer: 108 mg/kg b.w./day - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Consumer: 1.6 mg/kg b.w./day - Exposure: Human Oral - Frequency: Long Term, systemic effects

butan-1-ol; n-butanol - CAS: 71-36-3

Worker Industry: 310 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term (repeated) - Notes: 100 ppm

Consumer: 3125 mg/kg - Exposure: Human Oral - Frequency: Long Term (repeated) - Notes: 1 day

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH)) , as retained and amended in UK law

BOLICONE M4 ALU PA

- Consumer: 55 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term (repeated)
 N-(3-TRIMETHOXYSILYL)PROPYL)ETHYLENEDIAMINE - CAS: 1760-24-3
 Worker Industry: 35.3 mg/m³ - Consumer: 8.7 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Worker Industry: 5 mg/kg b.w./day - Consumer: 2.5 mg/kg b.w./day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Worker Industry: 5 mg/kg b.w./day - Consumer: 17 mg/kg b.w./day - Exposure: Human Dermal - Frequency: Short Term, systemic effects
 Consumer: 2.5 mg/kg b.w./day - Exposure: Human Oral
- ethylbenzene - CAS: 100-41-4
 Worker Industry: 77 mg/m³ - Consumer: 15 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
 Worker Industry: 180 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Worker Industry: 293 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects
- methanol - CAS: 67-56-1
 Worker Industry: 40 mg/kg b.w./day - Consumer: 8 mg/kg b.w./day - Exposure: Human Dermal - Frequency: Short Term, systemic effects
 Worker Industry: 40 mg/kg b.w./day - Consumer: 8 mg/kg b.w./day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Worker Industry: 260 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects
 Worker Industry: 260 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects
 Worker Industry: 260 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
- toluene - CAS: 108-88-3
 Worker Professional: 384 mg/m³ - Consumer: 226 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects
 Worker Professional: 192 mg/m³ - Consumer: 56.5 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Worker Professional: 180 mg/kg - Consumer: 226 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Consumer: 8.13 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
 Worker Professional: 384 mg/m³ - Consumer: 226 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects

PNEC Exposure Limit Values

- Xylene - CAS: 1330-20-7
 Target: Marine water - Value: 0.327 mg/l - Notes:: evaluation factor : 1
 Target: Marine water sediments - Value: 12.46 mg/kg
 Target: Soil (agricultural) - Value: 2.31 mg/kg
 Target: Microorganisms in sewage treatments - Value: 6.58 mg/l
 Target: Soil - Value: 2.31 mg/kg - Notes:: Assessment factor/ 1 / ECHA

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH)) , as retained and amended in UK law**BOLICONE M4 ALU PA**

n-butyl acetate - CAS: 123-86-4

Target: Fresh Water - Value: 0.18 mg/l

Target: Marine water - Value: 0.018 mg/l

Target: Freshwater sediments - Value: 0.981 mg/kg

Target: Water (intermittent discharge) - Value: 0.36 mg/l

Target: Marine water sediments - Value: 0.0981 mg/kg

Target: Soil - Value: 0.0903 mg/kg

Target: Microorganisms in sewage treatments - Value: 35.6 mg/l

reaction mass of ethylbenzene and xylene - CAS: 1330-20-7

Target: Fresh Water - Value: 0.327 mg/l

Target: Water (intermittent discharge) - Value: 0.327 mg/l

Target: Marine water - Value: 0.327 mg/l

Target: Sewage treatment plant - Value: 6.58 mg/l

Target: Freshwater sediments - Value: 12.46 mg/kg

Target: Marine water sediments - Value: 12.46 mg/kg

Target: Soil - Value: 2.31 mg/kg

butan-1-ol; n-butanol - CAS: 71-36-3

Target: Fresh Water - Value: 0.082 mg/l

Target: Marine water - Value: 0.0082 mg/l

Target: Freshwater sediments - Value: 0.178 mg/kg

Target: Marine water sediments - Value: 0.0178 mg/kg

Target: Soil (agricultural) - Value: 0.015 mg/kg

N-(3-TRIMETHOXYSILYL)PROPYL)ETHYLENEDIAMINE - CAS: 1760-24-3

Target: Fresh Water - Value: 0.062 mg/l

Target: Marine water - Value: 0.0062 mg/l

Target: Freshwater sediments - Value: 0.048 mg/kg

Target: Marine water sediments - Value: 0.0048 mg/kg

Target: Soil - Value: 0.0075 mg/kg

Target: Sewage treatment plant - Value: 25 mg/l

ethylbenzene - CAS: 100-41-4

Target: Marine water - Value: 0.01 mg/l - Notes:: factor assessment : 10

Target: Marine water - Value: 0.1 mg/l - Notes:: factor assessment : 18

Target: PNEC predator - Value: 2.68 mg/kg - Notes:: ECHA

methanol - CAS: 67-56-1

Target: Fresh Water - Value: 20.8 mg/l

Target: Marine water - Value: 2.08 mg/l

Target: Freshwater sediments - Value: 77 mg/kg

Target: Marine water sediments - Value: 7.7 mg/kg

Target: Soil (agricultural) - Value: 3.18 mg/kg

Target: Microorganisms in sewage treatments - Value: 100 mg/l

toluene - CAS: 108-88-3

Target: Fresh Water - Value: 0.68 mg/l

Target: Freshwater sediments - Value: 16.39 mg/kg

Target: Soil (agricultural) - Value: 2.89 mg/kg

Target: Microorganisms in sewage treatments - Value: 13.61 mg/l

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH)) , as retained and amended in UK law
BOLICONE M4 ALU PA

Biological Exposure Index

Xylene - CAS: 1330-20-7

Value: 1.5 g/g - medium: Urinary creatinine - Biological Indicator: Methyl hippuric acid in urine - Sampling Period: End of turn - Remark: ACGIH BEL (2009)

Value: 1.500 mg/g - medium: Urinary creatinine - Biological Indicator: Methyl hippuric acid in urine - Sampling Period: End of turn - Remark: FR IBE (1997)

reaction mass of ethylbenzene and xylene - CAS: 1330-20-7

Remark: ACGIH BEL (2009)

Remark: FR IBE (1997)

methanol - CAS: 67-56-1

Value: 15 mg/L - medium: Urine - Sampling Period: End of turn - Remark: Admissible concentration: 15 mg/l ; Base ACGIH BEI

8.2. Exposure controls

See below, example of PPE to use.

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use respiratory protection where ventilation is insufficient or exposure is prolonged.

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

Other conditions affecting workers exposure:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes
Physical state:	Liquid	--	--
Colour:	Metallic	--	--
Odour:	de solvant/ solvent-like	--	--
Melting point/freezing point:	Not Relevant	--	--
Boiling point or initial boiling point and boiling range:	>26°C	--	--
Flammability:	Flam. Liq. 2,	--	--

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH)) , as retained and amended in UK law

BOLICONE M4 ALU PA

	H225		
Lower and upper explosion limit:	N.A.	--	--
Flash point (°C):	~21°C	--	--
Auto-ignition temperature:	N.A.	--	--
Decomposition temperature:	Not Relevant	--	--
pH:	Not Relevant	--	--
Kinematic viscosity:	> 20,5 mm ² /sec (40 °C)	--	--
Solubility in water:	immiscible	--	--
Solubility in oil:	N.A.	--	--
Partition coefficient n-octanol/water (log value):	N.A.	--	--
Vapour pressure:	<1.000 hPa (50°C)	--	--
Density and/or relative density:	~1.12 g/cm ³ (23°C)	--	--
Relative vapour density:	N.A.	--	--
Particle characteristics:			
Particle size:	N.A.	--	--

9.2. Other information

Properties	Value	Method:	Notes
Viscosity:	>20.6 mm ² /s (40°C)	--	--

Volatile Organic compounds - VOCs = 49.43 %

N.A. = not available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH)) , as retained and amended in UK law**BOLICONE M4 ALU PA****10.2. Chemical stability**

Stable under normal conditions

10.3. Possibility of hazardous reactions

None

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

Strong oxidizers.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Toxicological information of the product:

BOLICONE M4 ALU PA

Acute toxicity

Not classified

Based on available data, the classification criteria are not met

ATEmix - Oral 24402,1 mg/kg bw

ATEmix - Dermal 4322,24 mg/kg bw

ATEmix - Inhalation (Vapours) 42,5743 mg/l

Skin corrosion/irritation

The product is classified: Skin Irrit. 2 H315

Serious eye damage/irritation

The product is classified: Eye Irrit. 2 H319

Respiratory or skin sensitisation

Not classified

Based on available data, the classification criteria are not met

Germ cell mutagenicity

Not classified

Based on available data, the classification criteria are not met

Carcinogenicity

Not classified

Based on available data, the classification criteria are not met

Reproductive toxicity

Not classified

Based on available data, the classification criteria are not met

STOT-single exposure

The product is classified: STOT SE 3 H335

STOT-repeated exposure

The product is classified: STOT RE 2 H373

Aspiration hazard

Not classified

Based on available data, the classification criteria are not met

Toxicological information of the main substances found in the product:

Xylene - CAS: 1330-20-7

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH)) , as retained and amended in UK law**BOLICONE M4 ALU PA**

Acute toxicity

ATE - Dermal 1100 mg/kg bw

ATE - Inhalation (Vapours) 11 mg/l

ATE - Inhalation (Dust/mist) 1,5 mg/l

ATE - Inhalation (Gas) 5000 ppmV

Test: LC50 - Route: Inhalation - Species: Rat = 5000 ppm - Duration: 4h

Test: LD50 - Route: Oral - Species: Rat = 3523 mg/kg bw

Test: LD50 - Route: Skin - Species: Rabbit = 12126 mg/kg

Test: LC50 - Route: Inhalation Vapour - Species: Rat = 27124 mg/m³ - Duration: 4h

Test: ATE - Route: Skin = 1100 mg/kg bw

Test: ATE - Route: Inhalation Vapour = 11 mg/l

Test: ATE - Route: Inhalation (dust, mist) = 1.5 mg/l

Test: ATE - Route: Inhalation Gas = 5000 ppmV

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg - Source: OECD Test Guideline 401

Test: LD50 - Route: Skin - Species: Rat > 2000 mg/kg - Source: OECD Test Guideline 402

Test: LC50 - Route: Inhalation Vapour - Species: Rat > 5000 mg/m³ - Duration: 4h

n-butyl acetate - CAS: 123-86-4

Acute toxicity:

Test: LD50 - Route: Skin - Species: Rabbit > 14000 mg/kg

Test: LD50 - Route: Oral - Species: Rat = 10736 mg/kg

Test: LC50 - Route: Inhalation Dust - Species: Rat = 23.4 mg/l - Duration: 4h

Test: LC50 - Route: Inhalation Mist - Species: Rat = 23.4 mg/l - Duration: 4h

Test: LC50 - Route: Inhalation (aerosol) - Species: Rabbit (male, female) = 0.74 mg/l - Duration: 4h - Source: OECD 403

Test: LC50 - Route: Inhalation Vapour - Species: Rat > 21.1 mg/l - Duration: 4h - Source: OECD 403

Test: LC0 - Route: Inhalation Vapour - Species: Rat > 38.32 mg/l - Duration: 6 hours

Reproductive toxicity:

Test: LOAEC - Route: Inhalation Vapour - Species: Rat = 1500 ppm - Source: OECD 414

Test: NOAEC - Route: Inhalation Vapour - Species: mouse (Male, female) = 2000 ppm - Duration: 90 Jours - Source: OECD 416

STOT-repeated exposure:

Test: NOAEC - Route: Inhalation - Species: Rat (Male, female) = 500 ppm - Duration: 13 weeks - Source: EPA OTS 798.2450

Test: NOAEL - Route: Oral - Species: Rat (Male, female) = 125 mg/kg bw/day - Duration: 13 weeks

Test: LOAEL

- Route: Oral - Species: mouse (Male, female) = 500 mg/kg bw/day - Duration: 13 days

reaction mass of ethylbenzene and xylene - CAS: 1330-20-7

Acute toxicity

ATE - Dermal 1100 mg/kg bw

ATE - Inhalation (Vapours) 11 mg/l

Test: LD50 - Route: Skin = 1100 mg/kg

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH)) , as retained and amended in UK law**BOLICONE M4 ALU PA**

Test: LC50 - Route: Inhalation Vapour = 11 mg/l

Carcinogenicity:

Test: NOAEL - Route: Oral - Species: Rat > 500 mg/kg bw/day

Reproductive toxicity:

Test: NOAEC - Route: Inhalation - Species: Rat = 500 ppm - Notes: fertilité/fertility

Test: NOAEC - Route: Inhalation - Species: Rat = 100 ppm - Notes: développement/development

Aspiration hazard:

= 0.812 cP - Notes: @20°C

butan-1-ol; n-butanol - CAS: 71-36-3

Acute toxicity

ATE - Oral 500 mg/kg bw

ATE - Dermal 3430 mg/kg bw

ATE - Inhalation (Dust/mist) 17,76 mg/l

Test: LD50 - Route: Oral - Species: Rat (Male, female) = 2292 mg/kg - Source: OECD, 401

Test: ATE - Route: Oral = 500 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit = 3430 mg/kg

Test: ATE - Route: Skin = 3430 mg/kg

Test: LC50 - Route: Inhalation Vapour - Species: Rat = 17.76 mg/l - Duration: 4h - Source: OECD, 403

Test: ATE - Route: Inhalation (dust, mist) = 17.76 mg/l

2-methylpropan-1-ol; iso-butanol - CAS: 78-83-1

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg

Test: ATE - Route: Inhalation (dust, mist) = 1.5 mg/l - Duration: 4h

N-(3-TRIMETHOXYSILYL)PROPYL)ETHYLENEDIAMINE - CAS: 1760-24-3

Acute toxicity

ATE - Oral 2295 mg/kg bw

ATE - Dermal 2001 mg/kg bw

ATE - Inhalation (Dust/mist) 1,49 mg/l

Test: LD50 - Route: Oral - Species: Rat = 2295 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg

Test: LC50 - Route: Inhalation (dust, mist) - Species: Rat > 1.49 mg/l - Duration: 4h

Test: LC50 - Route: Inhalation (dust, mist) - Species: Rat < 2.44 mg/l - Duration: 4h

Test: ATE - Route: Oral = 2295 mg/kg

Test: ATE - Route: Inhalation (dust, mist) >= 1.49 mg/l - Duration: 4h

Test: ATE - Route: Inhalation (dust, mist) <= 2.44 mg/l - Duration: 4h

Test: ATE - Route: Skin > 2000 mg/kg

AD-1500 (* l'identité chimique spécifique a été refusée conformément à l'article

Acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat > 6.3 mg/l

Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg

Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH)) , as retained and amended in UK law**BOLICONE M4 ALU PA**

ethylbenzene - CAS: 100-41-4

Acute toxicity

ATE - Inhalation (Vapours) 11 mg/l

Test: LD50 - Route: Skin - Species: Rabbit = 4100 mg/kg

Test: LD50 - Route: Oral - Species: Rat = 3500 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 20 mg/l - Duration: 4h

Test: LCL0 - Route: Inhalation - Species: Rat = 4000 ppm - Duration: 4h

methanol - CAS: 67-56-1

Acute toxicity

ATE - Oral 5000 mg/kg bw

ATE - Dermal 300 mg/kg bw

ATE - Inhalation (Vapours) 3 mg/l

Test: ATE - Route: Oral = 100 mg/kg

Test: ATE - Route: Skin = 300 mg/kg

Test: ATE - Route: Inhalation Vapour = 3 mg/l

Test: LC50 - Route: Inhalation Vapour - Species: Rat = 3 mg/l - Duration: 4h

Test: LD50 - Route: Oral - Species: Rat = 100 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit = 15800 mg/kg

Test: DLA - Approximate lethal dose - Species: Human = 340 mg/kg - Notes: Estimate

Test: DLA - Approximate lethal dose - Species: Human >= 29 mg/l - Notes: Estimate

Test: DLA - Approximate lethal dose - Species: Human <= 237 mg/l - Notes: Estimate

toluene - CAS: 108-88-3

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 5580 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

Test: LC50 - Route: Inhalation Vapour - Species: Rat = 28.1 mg/l - Duration: 4h

11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration >= 0.1%

Other toxicological information:

Xylene

Skin contact:

Irritating effect

Ingestion:

Ingestion may cause irritation of the digestive tract, nausea, vomiting and diarrhea, abdominal pain.

Harmful by inhalation.

-

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Eye contact:

May cause mild and transient eye discomfort.

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH)) , as retained and amended in UK law**BOLICONE M4 ALU PA**

-

reaction mass of ethylbenzene and xylene

Skin contact:

Irritating effect

Ingestion:

Ingestion may cause irritation of the digestive tract, nausea, vomiting and diarrhea, abdominal pain.

Harmful by inhalation.

-

butan-1-ol; n-butanol

Skin corrosion/skin irritation:

Irritating to skin.

Rabbit, Result: Irritant, OECD Guideline 404

Rabbit, Result: Risk of serious eye damage, OECD Guideline 405.

-

methanol

Acute oral toxicity :

Methanol is highly toxic to humans and can cause central nervous system effects, visual disturbances up to and including blindness, metabolic acidosis and degenerative damage to other organs including the liver, kidneys and heart. Effects may be delayed

Acute dermal toxicity:

The effects of methanol are the same as those seen with oral or inhalation exposure and include central nervous system depression, visual disturbances up to and including blindness, metabolic acidosis, as well as effects on organ systems such as the liver, kidneys and heart, and even death.

Inhalation toxicity :

Vapour concentrations that are easy to reach can cause serious harmful effects and even death. At lower concentrations: Possible respiratory irritation and central nervous system depression. Symptoms may include headache, dizziness and drowsiness leading to loss of co-ordination and consciousness. Inhalation of methanol can cause effects ranging from headaches, narcosis and impaired vision to metabolic acidosis, blindness and even death. Effects may be delayed.

Skin corrosion/irritation:

Prolonged contact may cause slight skin irritation with local redness.

-

toluene

Skin contact:

Irritating effect

Eye contact:

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH)) , as retained and amended in UK law

BOLICONE M4 ALU PA

Irritating effect

Inhalation of high concentration of vapours may cause irritation of the respiratory system.

Inhalation of high concentration vapours causes a narcotic reaction on the central nervous system, and severe lung damage.

Ingestion may cause irritation of the digestive tract, nausea, vomiting and diarrhea, abdominal pain.

Risk of central nervous system depression.

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

BOLICONE M4 ALU PA

Not classified for environmental hazards

Based on available data, the classification criteria are not met

Xylene - CAS: 1330-20-7

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Daphnia > 100 mg/l - Duration h: 24

Endpoint: LC50 - Species: Daphnia < 1000 mg/l - Duration h: 24

Endpoint: LC50 - Species: Fish = 2.6 mg/l - Duration h: 96 - Notes: Oncorhynchus mykiss

Endpoint: EC50 - Species: Daphnia = 1.0 mg/l - Duration h: 48

Endpoint: TLM - Species: Fish = 22 ppm - Duration h: 96 - Notes: Crapet Arlequin

Endpoint: IC50 - Species: Algae = 2.2 mg/l - Duration h: 72

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Algae = 0.44 mg/l - Duration h: 72

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

a) Aquatic acute toxicity:

Endpoint: NOEC - Species: Pseudokirchneriella subcapitata (green algae) > 1000 mg/l - Duration h: 72 - Notes: OECD Test Guideline 201

Endpoint: EC50 - Species: Daphnia > 1000 mg/l - Duration h: 48 - Notes: OECD Test Guideline 202

Endpoint: LC50 - Species: Rainbow Trout (Oncorhynchus mykiss) > 1000 mg/l - Duration h: 96 - Notes: OECD Test Guideline 203

b) Aquatic chronic toxicity:

Endpoint: NOAEL - Species: Daphnia = 0.18 mg/l - Duration h: 504 - Notes: Daphnia magna

Endpoint: NOAEL - Species: Fish = 0.10 mg/l - Duration h: 672 - Notes: Oncorhynchus mykiss

n-butyl acetate - CAS: 123-86-4

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae = 647.7 mg/l - Duration h: 72 - Notes: Desmodesmus subspicatus

Endpoint: NOEC - Species: Algae = 200 mg/l - Notes: Desmodesmus subspicatus

Endpoint: EC50 - Species: Aquatic plants = 397 mg/l - Duration h: 72 - Notes: DIN 38412 Part. 9, Pseudokirchneriella subcapitata

Endpoint: LC50 - Species: Fish = 18 mg/l - Duration h: 96 - Notes: OECD 203, Pimephales promelas

Endpoint: EC50 - Species: bacteria = 356 mg/l - Duration h: 40 - Notes: Tetrahymena pyriformis

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH)) , as retained and amended in UK law

BOLICONE M4 ALU PA

Endpoint: EC50 - Species: Daphnia = 44 mg/l - Duration h: 48 - Notes: OECD 202

Endpoint: ErC50 - Species: Aquatic plants = 397 mg/l - Duration h: 72 - Notes: OECD 201, Pseudokirchneriella subcapitata

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 23 mg/l - Duration h: 504 - Notes: OCDE 211

Endpoint: NOEC - Species: Aquatic plants = 196 mg/l - Duration h: 72 - Notes: OECD 201, Pseudokirchneriella subcapitata

Endpoint: IC50 - Species: bacteria = 356 mg/l - Duration h: 40 - Notes: TETRATOX assay, Tetrahymena pyriformis

d) Terrestrial toxicity:

Endpoint: EC50 > 1000 mg/kg - Duration h: 336 - Notes: Lactuca sativa

reaction mass of ethylbenzene and xylene - CAS: 1330-20-7

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 2.6 mg/l - Duration h: 96 - Notes: Oncorhynchus mykiss

Endpoint: IC50 - Species: Aquatic invertebrates = 1 mg/kg/d - Duration h: 24 - Notes: Daphnia magna

Endpoint: EC50 - Species: Aquatic plants = 2.2 mg/l - Duration h: 73 - Notes: Pseudokirchneriella subcapitata

Endpoint: NOEC - Species: activated sludge = 157 mg/l - Duration h: 3

Endpoint: NOEC - Species: Fish > 1.3 mg/l - Duration h: 1344 - Notes: Oncorhynchus mykiss

Endpoint: NOAEL - Species: Aquatic invertebrates = 1.17 mg/l - Duration h: 168 - Notes: Ceriodaphnia dubia

butan-1-ol; n-butanol - CAS: 71-36-3

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 1730 mg/l - Duration h: 96 - Notes: Pimephales promelas

Endpoint: EC50 - Species: Daphnia = 1983 mg/l - Duration h: 48

2-methylpropan-1-ol; iso-butanol - CAS: 78-83-1

a) Aquatic acute toxicity:

Endpoint: LD50 - Species: Fish > 100 mg/l - Duration h: 96 - Notes: Pimephales promelas

Endpoint: EC50 - Species: Aquatic invertebrates > 100 mg/l - Duration h: 48 - Notes: Daphnia magna

Endpoint: EC50 - Species: Algae > 100 mg/l - Duration h: 192

N-(3-TRIMETHOXYMETHYLPYRIDIUM)ETHYLENEDIAMINE - CAS: 1760-24-3

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Daphnia Magna = 81 mg/l - Duration h: 48

Endpoint: EC50 - Species: Pseudokirchneriella subcapitata (green algae) = 8.8 mg/l - Duration h: 72 - Activated sludge

Endpoint: NOEC - Species: Pseudokirchneriella subcapitata (green algae) = 3.1 mg/l - Duration h: 72

Endpoint: EC50 - Species: Pseudomonas putida = 67 mg/l - Duration h: 16

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia Magna > 1 mg/l - Duration h: 504 - Semi-static system

Endpoint: NOEC - Species: Eisenia fetida >= 1000 mg/kg - Duration h: 336

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH)) , as retained and amended in UK law

BOLICONE M4 ALU PA

ethylbenzene - CAS: 100-41-4

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia > 1.37 mg/l - Duration h: 48

Endpoint: EC50 - Species: Daphnia < 4.4 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish = 4.2 mg/l - Duration h: 96 - Notes: Oncorhynchus mykiss

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Fish > 1 mg/l

methanol - CAS: 67-56-1

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Daphnia Magna > 10000 mg/l - Duration h: 48

Endpoint: EC50r - Species: Pseudokirchneriella subcapitata = 22000 mg/l - Duration h: 96 -

Notes: OECD 201

Endpoint: IC50 - Species: bacteria > 1000 mg/l - Duration h: 3 - Notes: OECD 209

Endpoint: NOEC - Species: Oryzias latipes = 15800 mg/l - Duration h: 200

toluene - CAS: 108-88-3

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae = 134 mg/l - Duration h: 3 - Notes: Chlorella vulgaris

Endpoint: EC50 - Species: Daphnia = 3.78 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish = 5.5 mg/l - Duration h: 96 - Notes: Oncorhynchus kisutch

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 0.74 mg/l - Duration h: 168 - Notes: Ceriodaphnia dubia

Endpoint: NOEC - Species: Algae = 10 mg/l - Duration h: 72 - Notes: Skeletonema costatum

Endpoint: EC50 - Species: Daphnia = 3.23 mg/l - Duration h: 168 - Notes: Ceriodaphnia dubia

Endpoint: LOEC

- Species: Daphnia = 2.76 mg/kg/d - Duration h: 168 - Notes: Ceriodaphnia dubia

Endpoint: NOEC - Species: Fish = 1.39 mg/l - Duration h: 960 - Notes: Oncorhynchus kisutch

Endpoint: LOEC

- Species: Fish = 2.77 mg/l - Duration h: 960 - Notes: Oncorhynchus kisutch

c) Bacteria toxicity:

Endpoint: NOEC - Species: bacteria = 29 mg/l - Duration h: 16 - Notes: pseudomonas putida

12.2. Persistence and degradability

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Biodegradability: Biodegradability rate - Test: OECD 301F - Duration: 28 days - %: 80

n-butyl acetate - CAS: 123-86-4

Biodegradability: Biodegradability rate - Test: OECD 301D - Duration: 5 days - %: 83% - Notes:

CEE 92/69, C.4-E

butan-1-ol; n-butanol - CAS: 71-36-3

Biodegradability: Readily biodegradable - Duration: 19 days - %: > 70% - Notes: Aerobic

2-methylpropan-1-ol; iso-butanol - CAS: 78-83-1

Biodegradability: Readily biodegradable

methanol - CAS: 67-56-1

Biodegradability: Readily biodegradable

toluene - CAS: 108-88-3

Biodegradability: Readily biodegradable - Duration: 14 days - %: 100

12.3. Bioaccumulative potential

Xylene - CAS: 1330-20-7

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH)) , as retained and amended in UK law**BOLICONE M4 ALU PA**

Low bioconcentration potential

Log Pow 3.12

BCF 8.1 - 25.9

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Potentially bioaccumulative.

n-butyl acetate - CAS: 123-86-4

BCF 15.3

Log Kow 2.3 - Notes: 25 °C

N-(3-TRIMETHOXYSILYL)PROPYL)ETHYLENEDIAMINE - CAS: 1760-24-3

BCF < 100

Log Pow < 3

ethylbenzene - CAS: 100-41-4

Log Kow 3.15

methanol - CAS: 67-56-1

BCF < 100

Log Kow < 3

Partition coefficient: n-octanol/water (log Pow) -1,6 (20 °C) - Notes: measured

toluene - CAS: 108-88-3

BCF 90

Log Pow 2.65

12.4. Mobility in soil

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Floats on the water. Adsorption in soil, low mobility.

n-butyl acetate - CAS: 123-86-4

Log Koc 1.268

Volatility (H: Henry's Law Constant) 28.5 Pa.m³/mol - Notes: 25 °C

reaction mass of ethylbenzene and xylene - CAS: 1330-20-7

Log Koc 2.73 - Notes: @20-25°C

Volatility (H: Henry's Law Constant) 623-665 Pa m³/mol - Notes: @25°C

Surface tension 29.76 mN/m - Notes: @25°C

N-(3-TRIMETHOXYSILYL)PROPYL)ETHYLENEDIAMINE - CAS: 1760-24-3

Log Koc > 5000

methanol - CAS: 67-56-1

Koc 0.44 - Notes: Estimate

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration \geq 0.1%

12.7. Other adverse effects

No harmful effects expected.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

Codes of wastes (Décision 2001/573/EC, Directive 2006/12/EEC, Directive 94/31/EEC on hazardous

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH)) , as retained and amended in UK law

BOLICONE M4 ALU PA

waste):

08 01 11* wastes of paint and varnish containing organic solvents or other dangerous substances

SECTION 14: Transport information



14.1. UN number or ID number

ADR-UN Number: 1263
 IATA-UN Number: 1263
 IMDG-UN Number: 1263

14.2. UN proper shipping name

ADR-Shipping Name: PAINT
 IATA-Shipping Name: PAINT
 IMDG-Shipping Name: PAINT

14.3. Transport hazard class(es)

ADR-Class: 3
 ADR - Hazard identification number: 33
 IATA-Class: 3
 IATA-Label: 3
 IMDG-Class: 3

14.4. Packing group

ADR-Packing Group: II
 IATA-Packing group: II
 IMDG-Packing group: II

14.5. Environmental hazards

ADR-Environmental Pollutant: No
 IMDG-Marine pollutant: No
 IMDG-EmS: F-E , S-E

14.6. Special precautions for user

ADR-Subsidiary hazards: -
 ADR-S.P.: 163 367 640D 650
 ADR-Transport category (Tunnel restriction code): 2 (D/E)
 IATA-Passenger Aircraft: 353
 IATA-Subsidiary hazards: -
 IATA-Cargo Aircraft: 364
 IATA-S.P.: A3 A72 A192
 IATA-ERG: 3L
 IMDG-Subsidiary hazards: -
 IMDG-Stowage and handling: Category B
 IMDG-Segregation: -
 Q.L.: 5L
 Q.E.: E2

14.7. Maritime transport in bulk according to IMO instruments

N.A.

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH)) , as retained and amended in UK law

BOLICONE M4 ALU PA

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)
Dir. 2000/39/EC (Occupational exposure limit values)
Regulation (EC) n. 1907/2006 (REACH)
Regulation (EC) n. 1272/2008 (CLP)
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
Regulation (EU) n. 286/2011 (ATP 2 CLP)
Regulation (EU) n. 618/2012 (ATP 3 CLP)
Regulation (EU) n. 487/2013 (ATP 4 CLP)
Regulation (EU) n. 944/2013 (ATP 5 CLP)
Regulation (EU) n. 605/2014 (ATP 6 CLP)
Regulation (EU) n. 2015/1221 (ATP 7 CLP)
Regulation (EU) n. 2016/918 (ATP 8 CLP)
Regulation (EU) n. 2016/1179 (ATP 9 CLP)
Regulation (EU) n. 2017/776 (ATP 10 CLP)
Regulation (EU) n. 2018/669 (ATP 11 CLP)
Regulation (EU) n. 2018/1480 (ATP 13 CLP)
Regulation (EU) n. 2019/521 (ATP 12 CLP)
Regulation (EU) n. 2020/217 (ATP 14 CLP)
Regulation (EU) n. 2020/1182 (ATP 15 CLP)
Regulation (EU) n. 2021/643 (ATP 16 CLP)
Regulation (EU) n. 2021/849 (ATP 17 CLP)
Regulation (EU) n. 2022/692 (ATP 18 CLP)
GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3
Restriction 40

Restrictions related to the substances contained:

Restriction 48
Restriction 69
Restriction 75

Listed or in compliance with the following international inventories:

Labelling of detergents (EC Regulations 648/2004 and 907/2006):

N.A.

Labelling of biocides (Regulations 1896/2000, 1687/2002, 2032/2003, 1048/2005, 1849/2006, 1451/2007 and Directive 98/8/EC):

N.A.

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH)) , as retained and amended in UK law
BOLICONE M4 ALU PA

N.A.

Where applicable, refer to the following regulatory provisions :

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments.

1999/13/EC (VOC directive)

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

Product belongs to category: P5c

15.2. Chemical safety assessment

No

SECTION 16: Other information

N.A.: Not Applicable or Not Available

Full text of phrases referred to in Section 3:

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

H336 May cause drowsiness or dizziness.

H318 Causes serious eye damage.

H302 Harmful if swallowed.

H317 May cause an allergic skin reaction.

H360 (Inhalation, Skin) May damage fertility or the unborn child if inhaled and in contact with skin.

H400 Very toxic to aquatic life.

H225 Highly flammable liquid and vapour.

H373 (hearing organs) May cause damage to organs (hearing organs) through prolonged or repeated exposure.

H370 (eyes, central nervous system) Causes damage to organs (eyes, central nervous system).

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH)) , as retained and amended in UK law

BOLICONE M4 ALU PA

H331 Toxic if inhaled.

H370 Causes damage to organs.

H371 May cause damage to organs.

H361d Suspected of damaging the unborn child.

H350 May cause cancer.

H411 Toxic to aquatic life with long lasting effects.

Hazard class and hazard category	Code	Description
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
Acute Tox. 3	3.1/3/Dermal	Acute toxicity (dermal), Category 3
Acute Tox. 3	3.1/3/Inhal	Acute toxicity (inhalation), Category 3
Acute Tox. 3	3.1/3/Oral	Acute toxicity (oral), Category 3
Acute Tox. 4	3.1/4/Dermal	Acute toxicity (dermal), Category 4
Acute Tox. 4	3.1/4/Inhal	Acute toxicity (inhalation), Category 4
Acute Tox. 4	3.1/4/Oral	Acute toxicity (oral), Category 4
Asp. Tox. 1	3.10/1	Aspiration hazard, Category 1
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Dam. 1	3.3/1	Serious eye damage, Category 1
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
Skin Sens. 1B	3.4.2/1B	Skin Sensitisation, Category 1B
Carc. 1B	3.6/1B	Carcinogenicity, Category 1B
Repr. 1B	3.7/1B	Reproductive toxicity, Category 1B
Repr. 2	3.7/2	Reproductive toxicity, Category 2
STOT SE 1	3.8/1	Specific target organ toxicity - single exposure, Category 1
STOT SE 2	3.8/2	Specific target organ toxicity - single exposure, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH)) , as retained and amended in UK law

BOLICONE M4 ALU PA

STOT RE 2	3.9/2	Specific target organ toxicity - repeated exposure, Category 2
Aquatic Acute 1	4.1/A1	Acute aquatic hazard, category 1
Aquatic Chronic 2	4.1/C2	Chronic (long term) aquatic hazard, category 2
Aquatic Chronic 3	4.1/C3	Chronic (long term) aquatic hazard, category 3

This safety data sheet has been completely updated in compliance to Regulation 2020/878. (EC) 1272/2008 [CLP] Yönetmeliğine göre karışımların sınıflandırmasını elde etmek için kullanılan sınıflandırma ve prosedür:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Flam. Liq. 2, H225	On basis of test data
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
STOT SE 3, H335	Calculation method
STOT RE 2, H373	Calculation method

Due to the integration of the Mader Aero products range into the Socomore Group, all Safety Data Sheets have been re-evaluated on the basis of consolidated information. This may have led to significant changes in our Safety Data Sheets. If you have any questions regarding these changes, you can contact us at the address indicated in section 1.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

CCNL - Appendix 1

Insert further consulted bibliography

Important confidentiality : this document contains confidential information that is proprietary to SOCOMORE. Subject to legal provisions determining otherwise, the distribution, republication or re-transmission of this document, in full or in part, must be limited to clearly identified individuals, either because they use the product, or to provide HSE information. Any communication of this document outside of this framework without our written consent is strictly forbidden.

SOCOMORE strongly advises every recipient of this safety data sheet to read it carefully and to consult

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH)) , as retained and amended in UK law**BOLICONE M4 ALU PA**

experts in the field if necessary or appropriate, in order to understand the information it contains, notably the possible dangers associated with this product. The users must ensure the conformity and completeness of this information with regards to their specific use of the product.

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the responsibility of the purchaser/user to ensure that their activities conform with current legislation in force.

The information is considered correct, but it is not exhaustive and it shall be used only as a guide which is based on the current knowledge of the substance or mixture and it is applicable to the safety precautions appropriate for the product.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
STOT SE:	May cause drowsiness or dizziness
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

**Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH)) , as retained
and amended in UK law**

BOLICONE M4 ALU PA

WGK: German Water Hazard Class.