

Safety Data Sheet
DIESTONE A 8290 - P28290

Safety Data Sheet dated 9/17/2018, version 1

1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: DIESTONE A 8290

Other means of identification:

SDS code: P28290

Recommended use of the chemical and restrictions on use

Recommended use:

Solvent

Cleaner

Industrial uses

Restrictions on use:

No uses advised against are identified.

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company:

Dysol Inc. - 791 Westport Parkway - Fort Worth, TX 76177 / Phone: 1-817-335-1826 /
csr-na@socomore.com/ Fax Number: 817-335-2405Distributor: SOCOMORE S.A.S. - Zone Industrielle du Prat - CS 23707 - 56037 VANNES
CEDEX - France - Tel : +33 (0)2 97 43 76 83 - Fax : +33 (0)2 97 54 20 26Distributor: Socomore Ltd - 5, Coe Avenue - Loughborough - Leicestershire - LE11 4SE - UK
- Tel: +44 1509 262040 - Fax: +44 1509 262046Distributor: Socomore Iberia - Calle Diputacio, 260 - 08007 Barcelona - Espana - Tel: +34 917
693 962 - Fax: +34 902 908 966Distributor: MagChem Inc. 1271, rue Ampere, suite 101, Boucherville, QC, J4B 5Z5 Canada -
Tel: 1-450 641 8500 - Fax: 1-450 655 1717Distributor: Socomore GmbH - c/o MAZARS GmbH - Theodor-Stern-Kai 1 - 60596 Frankfurt
am Main - Deutschland - Tel: +49 (0)89 20 70 28 83 - Fax: +49 (0) 89 88 91 98 16Distributor: Socomore Trading Shangai - 355 East Kang Qiao Road - Kang Qiao Industrial
Zone - Pudong - 201315 Shangai - Tel: 862158131133 - Fax: 862158131933Dystrybutor : SOCOMORE SPzoo - Ul. Piekna 18, 00-549 Warszawa Polska - Tel : +48 608
454 114 - Fax : +48 (22) 621 61 09

Competent person responsible for the safety data sheet:

techdirsocomore@socomore.com

Emergency phone number

CHEMTEL: 1-800-255-3924 (USA) / CANUTEC: 1-613-996-6666 (CANADA)

2. HAZARD(S) IDENTIFICATION

Classification of the chemical



Warning, Flam. Liq. 3, Flammable liquid and vapour.



Warning, Eye Irrit. 2A, Causes serious eye irritation.



Danger, Repr. 1B, May damage fertility or the unborn child.



Warning, STOT SE 3, May cause respiratory irritation.

Safety Data Sheet
DIESTONE A 8290 - P28290

Label elements

Hazard pictograms:



Danger

Hazard statements:

- H226 Flammable liquid and vapour.
- H319 Causes serious eye irritation.
- H360 May damage fertility or the unborn child.
- H335 May cause respiratory irritation.

Precautionary statements:

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing vapours.
- P264 Wash hands thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves and eye/face protection.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P312 Call a POISON CENTER/doctor if you feel unwell.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P370+P378 In case of fire, use a CO2 fire extinguisher to extinguish.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Hazards not otherwise classified identified during the classification process:

None

Ingredient(s) with unknown acute toxicity:

None.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

N.A.

Safety Data Sheet

DIESTONE A 8290 - P28290

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

>= 70% - < 80% 2-methoxy-1-methylethyl acetate

REACH No.: 01-2119475791-29, Index number: 607-195-00-7, CAS: 108-65-6, EC: 203-603-9

 B.6/3 Flam. Liq. 3 H226

>= 15% - < 20% DIACETONE-ALCOOL

REACH No.: 01-2119473975-21, CAS: 123-42-2, EC: 204-626-7

 A.3/2A Eye Irrit. 2A H319

 A.8/3 STOT SE 3 H335

>= 7% - < 10% HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

REACH No.: 01-2119463258-33, EC: 919-857-5

 B.6/3 Flam. Liq. 3 H226

 A.10/1 Asp. Tox. 1 H304

 A.8/3 STOT SE 3 H336

>= 0.1% - < 0.25% 2-methoxypropyl acetate

REACH No.: 01-2119475791-29, Index number: 607-251-00-0, CAS: 70657-70-4, EC: 274-724-2

 B.6/3 Flam. Liq. 3 H226

 A.7/1B Repr. 1B H360

 A.8/3 STOT SE 3 H335

4. FIRST-AID MEASURES

Description of necessary measures

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting. Obtain a medical examination.

In case of Inhalation:

In case of inhalation, consult a doctor immediately and show him packing or label.

Most important symptoms/effects, acute and delayed

Redness.

Safety Data Sheet

DIESTONE A 8290 - P28290

Repeated exposure may cause skin dryness or cracking.

Burning sensation.

Tumor.

Blurred vision.

Temporary burning sensation of nose and throat.

Cough

Difficulty breathing.

Vapours may cause drowsiness and dizziness.

Indication of immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

Treat symptomatically.

Call a doctor or poison control center for further instructions.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

In case of fire, use a CO₂ fire extinguisher to extinguish.

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties: yes

Oxidizing properties: N.A.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Remove persons to safety.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

Methods and materials for containment and cleaning up

Wash with plenty of water.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Do not use on extensive surface areas in premises where there are occupants.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Safety Data Sheet

DIESTONE A 8290 - P28290

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Avoid accumulating electrostatic charge.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

Safety electric system.

Storage temperature:

Store at ambient temperature.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

- OEL Type: ACGIH - TWA(8h): 150 ppm - STEL: 100 ppm

- OEL Type: National - TWA(8h): 275 mg/m³, 50 ppm - STEL: 550 mg/m³, 100 ppm -

Notes: France VLEC

- OEL Type: National - TWA(8h): 270 mg/m³, 50 ppm - Notes: GERMANY

- OEL Type: National - TWA(8h): 274 mg/m³, 50 ppm - STEL: 548 mg/m³, 100 ppm -

Notes: UK (WELs)

- OEL Type: National - TWA: 260 mg/m³ - STEL: 520 mg/m³ - Notes: POLAND

- OEL Type: EU - TWA(8h): 275 mg/m³, 50 ppm - STEL: 550 mg/m³, 100 ppm -

Notes: Skin

- OEL Type: AIHA

- TWA: 50 ppm

DIACETONE-ALCOOL - CAS: 123-42-2

- OEL Type: ACGIH - TWA(8h): 50 ppm - Notes: URT and eye irr

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

- OEL Type: National - TWA: 1200 mg/m³, 197 ppm - Notes: ExxonMobil

2-methoxypropyl acetate - CAS: 70657-70-4

- OEL Type: National - TWA: 28 mg/m³, 5 ppm - STEL: 224 mg/m³, 40 ppm - Notes:

Switzerland-Germany

DNEL Exposure Limit Values

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

Worker Industry: 153.5 mg/kg bw/day - Consumer: 54.8 mg/kg bw/day - Exposure:

Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 275 mg/m³ - Consumer: 33 mg/m³ - Exposure: Human Inhalation -

Frequency: Long Term, systemic effects

Consumer: 1.67 mg/kg bw/day - Exposure: Human Oral - Frequency: Long Term, systemic effects

DIACETONE-ALCOOL - CAS: 123-42-2

Consumer: 3.4 mg/kg bw/day - Exposure: Human Oral - Frequency: Long Term, systemic effects

Worker Professional: 240 mg/m³ - Consumer: 120 mg/m³ - Exposure: Human

Inhalation - Frequency: Short Term, local effects

Worker Professional: 9.4 mg/kg bw/day - Consumer: 3.4 mg/kg bw/day - Exposure:

Human Dermal - Frequency: Long Term, systemic effects

Safety Data Sheet

DIESTONE A 8290 - P28290

Worker Professional: 66.4 mg/m³ - Consumer: 11.8 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects

Worker Professional: 66.4 mg/m³ - Consumer: 11.8 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

Worker Industry: 208 mg/kg bw/day - Consumer: 125 mg/kg bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 871 mg/m³ - Consumer: 185 mg/kg bw/day - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 125 mg/kg bw/day - Exposure: Human Oral - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

Target: Fresh Water - Value: 0.635 mg/l

Target: Marine water - Value: 0.0635 mg/l

Target: Microorganisms in sewage treatments - Value: 100 mg/l

Target: Freshwater sediments - Value: 3.29 mg/kg

Target: Marine water sediments - Value: 0.329 mg/kg

Target: Soil (agricultural) - Value: 0.29 mg/kg

Target: PNEC intermittent - Value: 6.35 mg/l

DIACETONE-ALCOOL - CAS: 123-42-2

Target: Fresh Water - Value: 2 mg/l

Target: Marine water - Value: 0.2 mg/l

Target: Microorganisms in sewage treatments - Value: 82 mg/l

Target: Freshwater sediments - Value: 9.06 mg/kg

Target: Marine water - Value: 0.91 mg/kg

Target: Soil (agricultural) - Value: 0.63 mg/kg

Target: Water (intermittent discharge) - Value: 1 mg/l

Appropriate engineering controls:

None

Individual protection measures

Eye protection:

Safety goggles (EN 166)

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable gloves type: NF EN374

Butyl rubber (isobutylene-isoprene copolymer)

Respiratory protection:

Use respiratory protection where ventilation is insufficient or exposure is prolonged.

Thermal Hazards:

None

9. PHYSICAL AND CHEMICAL PROPERTIES

Properties	Value	Method:	Notes
Appearance and colour:	Colourless liquid	--	--
Odour:	N.A.	--	--
Odour threshold:	N.A.	--	--
pH:	N.A.	--	--
Melting point / freezing point:	Not Relevant	--	--

Safety Data Sheet

DIESTONE A 8290 - P28290

Initial boiling point and boiling range:	145°C	NF T67-101	--
Flash Point (°F):	106 °F	--	--
Flash point (°C):	41 °C	ISO 2592	--
Evaporation rate:	N.A.	--	--
Solid/gas flammability:	N.A.	--	liquid
Upper/lower flammability or explosive limits:	0.6-7%	--	--
Vapour pressure:	1,8 mmHg (20°C)	--	--
Vapour density:	4.5	--	--
Relative density:	0.94	ISO 649, ASTM D1298	--
Solubility in water:	N.A.	--	--
Solubility in oil:	N.A.	--	--
Partition coefficient (n-octanol/water):	N.A.	--	--
Auto-ignition temperature:	260°C	--	--
Decomposition temperature:	N.A.	--	--
Viscosity:	N.A.	--	--
Explosive properties:	yes	--	May form explosive mixtures with air.
Oxidizing properties:	N.A.	--	--

9.2. Other information

Properties	Value	Method:	Notes
Miscibility:	N.A.	--	--
Fat Solubility:	N.A.	--	--
Conductivity:	N.A.	--	--
Substance Groups relevant properties	N.A.	--	--

10. STABILITY AND REACTIVITY

Reactivity

It may generate dangerous reactions (See subsections below)

Chemical stability

It may generate dangerous reactions (See subsections below)

Possibility of hazardous reactions

None

Conditions to avoid

Avoid accumulating electrostatic charge.

Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

Hazardous decomposition products

None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological information of the product:

N.A.

Safety Data Sheet

DIESTONE A 8290 - P28290

Toxicological information of the main substances found in the product:

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Test: LD50 - Route: Skin - Species: Rat > 2000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 10.8 mg/l

Test: LC50 - Route: Skin - Species: Rabbit > 5000 mg/kg

DIACETONE-ALCOOL - CAS: 123-42-2

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 3002 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 7.6 mg/l

Test: LD50 - Route: Skin - Species: Rat > 1875 mg/kg

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg - Duration: 24 hours

Test: LC50 - Route: Inhalation - Species: Rat > 4951 mg/m³ - Duration: 8h

2-methoxypropyl acetate - CAS: 70657-70-4

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Test: LD50 - Route: Skin - Species: Rat > 2000 mg/kg

b) skin corrosion/irritation:

Test: LC50 - Route: Inhalation - Species: Rat > 10.8 mg/l

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS -

1

Substance(s) listed on the NTP report on Carcinogens:

None.

Substance(s) listed on the IARC Monographs:

None.

Substance(s) listed as OSHA Carcinogen(s):

None.

Substance(s) listed as NIOSH Carcinogen(s):

None.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae > 1000 mg/l

Endpoint: LC50 - Species: Fish = 134 mg/l

Endpoint: EC50 - Species: Daphnia = 408 mg/l

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Fish = 47.5 mg/l - Duration h: 336 - Notes: Oryzias latipes

Endpoint: NOEC - Species: Daphnia > 100 mg/l - Duration h: 504

DIACETONE-ALCOOL - CAS: 123-42-2

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 100 mg/l - Duration h: 96 - Notes: Oryzias latipes

Endpoint: EC50 - Species: Daphnia > 1000 mg/l - Duration h: 48 - Notes: Daphnia magna

Endpoint: EC50 - Species: Algae > 1000 mg/l - Duration h: 72 - Notes:

Pseudokirchnerella subcapitata

Safety Data Sheet

DIESTONE A 8290 - P28290

Endpoint: EC10 - Species: aquatic plants = 429 mg/l - Duration h: 72 - Notes: Pseudokirchneriella subcapitata

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 100 mg/l - Duration h: 504

Endpoint: NOEC - Species: Algae = 1000 mg/l - Duration h: 72 - Notes: Raphidocelis subcapitata

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 1000 mg/l - Duration h: 96 - Notes: Oncorhynchus mykiss

Endpoint: EC50 - Species: Algae > 1000 mg/l - Duration h: 72 - Notes: Pseudokirchnerella subcapitata

Endpoint: EC50 - Species: Daphnia > 1000 mg/l - Duration h: 48 - Notes: Daphnia magna

Endpoint: DSEO-R (NOELR) - Species: Algae = 3 mg/l - Duration h: 72 - Notes: Pseudokirchnerella subcapitata - biomass - OECD 201)

Endpoint: DSEO-R (NOELR) - Species: Algae = 100 mg/l - Duration h: 72 - Notes: Pseudokirchnerella subcapitata - growth rate - OECD 201)

b) Aquatic chronic toxicity:

Endpoint: DSEO-R (NOELR) - Species: Daphnia = 0.23 mg/l - Duration h: 504 - Notes: Daphnia magna - QSAR Petrotox

Endpoint: DSEO-R (NOELR) - Species: Fish = 0.13 mg/l - Duration h: 672 - Notes: Oncorhynchus mykiss - QSAR Petrotox

2-methoxypropyl acetate - CAS: 70657-70-4

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 134 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 408 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae > 1000 mg/l - Duration h: 96

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Fish = 47.5 mg/l - Duration h: 336 - Notes: Oryzias latipes

Endpoint: NOEC - Species: Daphnia > 100 mg/l - Duration h: 504

Persistence and degradability

DIACETONE-ALCOOL - CAS: 123-42-2

Biodegradability: Biodegradation in water - Test: N.A. - Duration: 21 days - %: 98.51 - Notes: N.A.

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

Biodegradability: Biodegradability rate - Test: N.A. - Duration: 28 days - %: 80 - Notes: N.A.

Biodegradability: Photodegradation (in air) - Test: N.A. - Duration: N.A. - %: N.A. - Notes: N.A.

Bioaccumulative potential

DIACETONE-ALCOOL - CAS: 123-42-2

Log Kow - Test: N.A. -0.09 - Duration: N.A. - Notes: N.A.

Mobility in soil

DIACETONE-ALCOOL - CAS: 123-42-2

Log Koc - Test: N.A. 0.52 - Duration: N.A. - Notes: N.A.

Other adverse effects

No harmful effects expected.

13. DISPOSAL CONSIDERATIONS

Waste treatment and disposal methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

Safety Data Sheet
DIESTONE A 8290 - P28290

14. TRANSPORT INFORMATION



UN number	
ADR-UN Number:	1993
DOT number:	UN1993
IATA-UN Number:	1993
IMDG-UN Number:	1993
UN proper shipping name	
ADR-Shipping Name:	FLAMMABLE LIQUID, N.O.S. (2-methoxy-1-methylethyl acetate, HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS)
DOT-Shipping Name:	FLAMMABLE LIQUID, N.O.S. (2-methoxy-1-methylethyl acetate, HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS)
IATA-Shipping Name:	FLAMMABLE LIQUID, N.O.S. (2-methoxy-1-methylethyl acetate, HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS)
IMDG-Shipping Name:	FLAMMABLE LIQUID, N.O.S. (2-methoxy-1-methylethyl acetate, HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS)
Transport hazard class(es)	
ADR-Class:	3
DOT Hazard Class:	3
ADR - Hazard identification number:	30
IATA-Class:	3
IATA-Label:	3
IMDG-Class:	3
Packing group	
ADR-Packing Group:	III
DOT Packing group:	III
IATA-Packing group:	III
IMDG-Packing group:	III
Environmental hazards	
ADR-Environmental Pollutant:	No
IMDG-Marine pollutant:	No
Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)	
N.A.	
Special precautions	
DOT Special provisions:	B1, B52, IB3, T4, TP1, TP29
DOT Labels:	3
ADR-Subsidiary risks:	-
ADR-S.P.:	274 601 640E
ADR-Transport category (Tunnel restriction code): (D/E)	
IATA-Passenger Aircraft:	355
IATA-Subsidiary risks:	-
IATA-Cargo Aircraft:	366
IATA-S.P.:	A3
IATA-ERG:	3L

Safety Data Sheet

DIESTONE A 8290 - P28290

IMDG-EmS: F-E , S-E
IMDG-Subsidiary risks: -
IMDG-Stowage and handling: Category A
IMDG-Segregation: -
Q.L.: 5L
Q.E.: E1

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

TSCA inventory: all the components are listed on the TSCA inventory.

TSCA listed substances:

2-methoxy-1-methylethyl acetate is listed in TSCA Section 8a - PAIR, Section 8b, Section 8d HSDR

DIACETONE-ALCOOL is listed in TSCA Section 8a - PAIR, Section 8b, Section 8d HSDR.

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances: no substances listed.

Section 304 - Hazardous substances: no substances listed.

Section 313 - Toxic chemical list: no substances listed.

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

No substances listed.

CAA - Clean Air Act

CAA listed substances:

DIACETONE-ALCOOL is listed in CAA Section 111.

CWA - Clean Water Act

CWA listed substances:

None.

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

None.

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

DIACETONE-ALCOOL.

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

DIACETONE-ALCOOL.

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

DIACETONE-ALCOOL.

The following substance(s) in this product has/have an identification by CAS number either in countries not affected by the REACH regulation or in regulations not yet

updated to reflect the new naming convention for hydrocarbon solvents:

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2%

AROMATIC (CAS: 64742-48-9)

16. OTHER INFORMATION

Full text of phrases referred to in Section 3:

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H304 May be fatal if swallowed and enters airways.

Safety Data Sheet

DIESTONE A 8290 - P28290

H336 May cause drowsiness or dizziness.
H360 May damage fertility or the unborn child.

Safety Data Sheet dated 9/17/2018, version 1

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average