

Regulation (EU) n. 2020/878

Master item code: P28279

Safety Data Sheet date: 27/11/2024, version 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name: DIESTONE D-SATWIPES/PROSAT/SOCOSAT

SDS code: P29004EU

References: SATWIPES C86 / SOCOSAT VP80 / SOCOSAT 16400

UFI: 0RH5-XK9C-VP2Q-VP09

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Solvent

Industrial uses

Uses advised against:

No uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Manufacturers:

Socomore SASU - Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - France -Tel. +33 (0)2 97 43 76 90

Manufacturing - Parc Gohelis - 56250 ELVEN France - Tel +33 (0)2 97 43 76 83 - Fax +33 (0)2 97 54 50 26

Socomore Ireland Ltd. - Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922 / Fax +353 21 4889923 / ireland@socomore.com

Distributors:

Socomore SASU - Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - France -Tel. +33 (0)2 97 43 76 90

Manufacturing - Parc Gohelis - 56250 ELVEN France - Tel +33 (0)2 97 43 76 83 - Fax +33 (0)2 97 54 50 26

Socomore Ireland Ltd. - Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922 / Fax +353 21 4889923 / ireland@socomore.com

Competent person responsible for the safety data sheet:

msdsinformation-eu@socomore.com

1.4. Emergency telephone number

France: ORFILA (INRS) +33 (0)1 45 42 59 59 International: CHEMTEL +1-813-248-0585.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture EC regulation criteria 1272/2008 (CLP)

Warning, Flam. Lig. 3, Flammable liquid and vapour.

♦ Warning, STOT SE 3, May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.



Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:



Warning

Hazard statements:

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing vapours.

P312 Call a POISON CENTER if you feel unwell.

P370+P378 In case of fire, use a CO2 fire extinguisher to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains

n-butyl acetate

2-methoxy-1-methylethyl acetate

1-methoxy-2-propanol; monopropylene glycol methyl ether

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number		Classification
>= 30% - < 40%	n-butyl acetate	Index number:		
		CAS:	123-86-4	EUH066
		EC:	204-658-1	
		REACH No.:	01-	



			2119485493 -29	
>= 30% - < 40%	2-methoxy-1- methylethyl acetate	Index number: CAS: EC: REACH No.:	108-65-6 203-603-9	◆ 2.6/3 Flam. Liq. 3 H226◆ 3.8/3 STOT SE 3 H336EUH066
>= 15% - < 20%	1-methoxy-2-propanol; monopropylene glycol methyl ether	Index number: CAS: EC: REACH No.:	-	© 2.6/3 Flam. Liq. 3 H226 © 3.8/3 STOT SE 3 H336 Acute Toxicity Estimate: ATE - Oral 3739 mg/kg bw ATE - Dermal 2001 mg/kg bw ATE - Inhalation (Vapours) 30,02 mg/l

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose of safely.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do not induce vomiting. Obtain a medical examination.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

No particular treatment.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

In case of fire, use a CO2 fire extinguisher to extinguish.



Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, ensure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contamined clothing should be changed before entering eating areas.

Do not eat or drink while working.

7.2. Conditions for safe storage, including any incompatibilities

Store under the same conditions as a combustible solid product.

Always keep in a well ventilated place.

Store at ambient temperatures. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

7.3. Specific end use(s)



None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

n-butyl acetate - CAS: 123-86-4

- OEL Type: National TWA: 241 mg/m3, 50 ppm STEL: 723 mg/m3, 150 ppm Behaviour: Binding Notes: France, VLEPC
- OEL Type: National TWA: 150 ppm STEL: 200 ppm Notes: United Kingdom
- OEL Type: National TWA(8h): 300 mg/m3, 62 ppm Notes: Germany
- OEL Type: ACGIH TWA(8h): 50 ppm STEL: 150 ppm Notes: Eye and URT irr
- OEL Type: National TWA(8h): 238 mg/m3, 50 ppm STEL: 712 mg/m3, 150 ppm -

Notes: BELGIQUE

- OEL Type: National TWA(8h): 480 mg/m3, 99 ppm Notes: PAYS-BAS
- OEL Type: National TWA: 480 mg/m3, 100 ppm STEL(Mow): 480 mg/m3, 100 ppm Notes: Österreich
- OEL Type: EU TWA(8h): 241 mg/m3, 50 ppm STEL: 723 mg/m3, 150 ppm 2-methoxy-1-methylethyl acetate CAS: 108-65-6
- OEL Type: ACGIH TWA(8h): 150 ppm STEL: 100 ppm
 - OEL Type: National TWA(8h): 275 mg/m3, 50 ppm STEL: 550 mg/m3, 100 ppm Behaviour: Binding Notes: France VLEPC
 - OEL Type: National TWA(8h): 270 mg/m3, 50 ppm Notes: GERMANY
 - OEL Type: National TWA(8h): 274 mg/m3, 50 ppm STEL: 548 mg/m3, 100 ppm Notes: UK (WELs)
 - OEL Type: National TWA: 260 mg/m3 STEL: 520 mg/m3 Notes: POLAND
 - OEL Type: EU TWA(8h): 275 mg/m3, 50 ppm STEL: 550 mg/m3, 100 ppm Notes: Skin
 - OEL Type: AIHA
- TWA: 50 ppm
 - OEL Type: National TWA: 275 mg/m3, 50 ppm STEL(5 min (Mow)): 550 mg/m3, 100 ppm Notes: Österreich
 - OEL Type: National TWA: 270 mg/m3, 50 ppm Notes: Norway (Skin)

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

- OEL Type: National TWA(8h): 188 mg/m3, 50 ppm STEL: 375 mg/m3, 100 ppm Behaviour: Binding Notes: France VLEC INRS TMP N°84
- OEL Type: National TWA: 370 mg/m3, 100 ppm Notes: Germany
- OEL Type: National TWA: 180 mg/m3 STEL: 360 mg/m3 Notes: Poland
- OEL Type: EU TWA(8h): 375 mg/m3, 100 ppm STEL: 563 mg/m3, 150 ppm Notes: Skin
- OEL Type: ACGIH TWA(8h): 50 ppm STEL: 100 ppm Notes: A4 Eye and URT irr
- OEL Type: National TWA: 187 mg/m3, 50 ppm STEL(15min (Miw)): 187 mg/m3, 50 ppm Notes: Austria
- OEL Type: National TWA(8h): 375 mg/m3, 100 ppm STEL(15min (Miw)): 560 mg/m3, 150 ppm Notes: United Kingdom Skin
- OEL Type: National TWA(8h): 188 mg/m3, 50 ppm STEL: 375 mg/m3, 100 ppm -



Notes: Canada (Gazette Officielle du Québec, January 4, 2023, Vol. 155, No.1)

- OEL Type: National - TWA: 180 mg/m3, 50 ppm - Notes: Norway (skin)

- OEL Type: DOW IHG - TWA: 1.5 ppm - STEL: 4.5 ppm

DNEL Exposure Limit Values

n-butyl acetate - CAS: 123-86-4

Worker Industry: 11 mg/kg - Consumer: 6 mg/kg - Exposure: Human Dermal - Frequency:

Long Term, systemic effects

Worker Industry: 300 mg/m3 - Consumer: 35.7 mg/m3 - Exposure: Human Inhalation -

Frequency: Long Term, systemic effects

Consumer: 2 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects Worker Industry: 600 mg/m3 - Consumer: 300 mg/m3 - Exposure: Human Inhalation -

Frequency: Short Term, systemic effects

Worker Industry: 11 mg/kg - Consumer: 2 mg/kg - Exposure: Human Oral - Frequency:

Short Term, systemic effects

Worker Industry: 600 mg/m3 - Consumer: 300 mg/m3 - Exposure: Human Inhalation -

Frequency: Short Term, local effects

Worker Industry: 300 mg/m3 - Consumer: 35.7 mg/m3 - Exposure: Human Inhalation -

Frequency: Long Term, local effects

Worker Industry: 11 mg/kg - Consumer: 6 mg/kg - Exposure: Human Dermal - Frequency:

Short Term, systemic effects

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

Worker Industry: 796 mg/kg b.w./day - Consumer: 320 mg/kg b.w./day - Exposure: Human

Dermal - Frequency: Long Term, systemic effects

Worker Industry: 275 mg/m3 - Consumer: 33 mg/m3 - Exposure: Human Inhalation -

Frequency: Long Term, systemic effects

Consumer: 36 mg/kg b.w./day - Exposure: Human Oral - Frequency: Long Term, systemic

effects

Worker Industry: 550 mg/m3 - Consumer: 33 mg/m3 - Exposure: Human Inhalation -

Frequency: Long Term, local effects

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

Worker Industry: 369 mg/m3 - Consumer: 43.9 mg/m3 - Exposure: Human Inhalation -

Frequency: Long Term, systemic effects

Worker Industry: 50.6 mg/kg b.w./day - Consumer: 18.1 mg/kg b.w./day - Exposure:

Human Dermal - Frequency: Long Term, systemic effects

Consumer: 3.3 mg/kg b.w./day - Exposure: Human Oral - Frequency: Long Term, systemic

effects

Worker Industry: 553.5 mg/m3 - Exposure: Human Inhalation - Frequency: Short Term

(acute)

PNEC Exposure Limit Values

n-butyl acetate - CAS: 123-86-4

Target: Fresh Water - Value: 0.18 mg/l Target: Marine water - Value: 0.018 mg/l

Target: Freshwater sediments - Value: 0.981 mg/kg

Target: Water (intermittent discharge) - Value: 0.36 mg/l



Target: Marine water sediments - Value: 0.0981 mg/kg

Target: Soil - Value: 0.0903 mg/kg

Target: Microorganisms in sewage treatments - Value: 35.6 mg/l

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

Target: Fresh Water - Value: 0.635 mg/l Target: Marine water - Value: 0.0635 mg/l

Target: Microorganisms in sewage treatments - Value: 100 mg/l

Target: Freshwater sediments - Value: 3.29 mg/kg dw Target: Marine water sediments - Value: 0.329 mg/kg dw

Target: Soil - Value: 0.29 mg/kg

Target: PNEC intermittent - Value: 6.35 mg/l

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

Target: Fresh Water - Value: 10 mg/l

Target: Freshwater sediments - Value: 41.6 mg/kg Target: Marine water sediments - Value: 4.17 mg/kg

Target: Soil (agricultural) - Value: 2.47 mg/kg

Target: Microorganisms in sewage treatments - Value: 100 mg/l

Target: Marine water - Value: 1 mg/l

Target: Water (intermittent discharge) - Value: 100 mg/l

Biological Exposure Index

N.A.

8.2. Exposure controls

See below, example of PPE to use.

Eye protection:

Safety goggles (EN 166)

Protection for skin:

Chemical protection clothing. (type 3 - EN14605) Chemical protection clothing. (type 5 - EN13982-1)

Chemical protection clothing. (type 6 - EN13034)

Protection for hands:

Suitable gloves type: NF EN374

Butyl rubber (isobutylene-isoprene copolymer)

Respiratory protection:

Use adequate protective respiratory equipment. Filtering Half-face mask (NF EN 149), class FFP1 Mask with filter "A1", brown colour (NF EN14387)

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

Other conditions affecting workers exposure:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties



Properties	Value	Method:	Notes	
Physical state:	Liquid coated on wipes			
Colour:	Colourless			
Odour:	N.A.			
Melting point/freezing point:	Not Relevant			
Boiling point or initial boiling point and boiling range:	117 °C			
Flammability:	Flam. Liq. 3, H226			
Lower and upper explosion limit:	N.A.			
Flash point (°C):	31 °C			
Auto-ignition temperature:	421°C			
Decomposition temperature:	N.A.			
pH:	N.A.			
Kinematic viscosity:	N.A.			
Solubility in water:	N.A.			
Solubility in oil:	N.A.			
Partition coefficient n-octanol/water (log value):	N.A.			
Vapour pressure:	6,8 mmHg (20°C)			
Density and/or relative density:	< 1			
Relative vapour density:	4			
Particle characteristics:				
Particle size:	N.A.			



9.2. Other information

No other relevant information

Volatile Organic compounds - VOCs = 918 g/l

N.A. = not available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological information of the product:

DIESTONE D-SATWIPES/PROSAT/SOCOSAT

Acute toxicity

Not classified

Based on available data, the classification criteria are not met

Skin corrosion/irritation

Not classified

Based on available data, the classification criteria are not met

Serious eye damage/irritation

Not classified

Based on available data, the classification criteria are not met

Respiratory or skin sensitisation

Not classified

Based on available data, the classification criteria are not met

Germ cell mutagenicity

Not classified

Based on available data, the classification criteria are not met

Carcinogenicity

Not classified

Based on available data, the classification criteria are not met

Reproductive toxicity

Not classified

Based on available data, the classification criteria are not met STOT-single exposure



The product is classified: STOT SE 3 H336

STOT-repeated exposure

Not classified

Based on available data, the classification criteria are not met

Aspiration hazard

Not classified

Based on available data, the classification criteria are not met

Toxicological information of the main substances found in the product:

n-butyl acetate - CAS: 123-86-4

Acute toxicity:

Test: LD50 - Route: Skin - Species: Rabbit > 14000 mg/kg

Test: LD50 - Route: Oral - Species: Rat = 10736 mg/kg

Test: LC50 - Route: Inhalation Dust - Species: Rat = 23.4 mg/l - Duration: 4h Test: LC50 - Route: Inhalation Mist - Species: Rat = 23.4 mg/l - Duration: 4h

Test: LC50 - Route: Inhalation (aerosol) - Species: Rabbit (male, female) = 0.74 mg/l -

Duration: 4h - Source: OECD 403

Test: LC50 - Route: Inhalation Vapour - Species: Rat > 21.1 mg/l - Duration: 4h - Source:

OECD 403

Test: LC0 - Route: Inhalation Vapour - Species: Rat > 38.32 mg/l - Duration: 6 hours

Reproductive toxicity:

Test: LOAEC - Route: Inhalation Vapour - Species: Rat = 1500 ppm - Source: OECD 414 Test: NOAEC - Route: Inhalation Vapour - Species: mouse (Male, female) = 2000 ppm -

Duration: 90 Jours - Source: OECD 416

STOT-repeated exposure:

Test: NOAEC - Route: Inhalation - Species: Rat (Male, female) = 500 ppm - Duration: 13

weeks - Source: EPA OTS 798.2450

Test: NOAEL - Route: Oral - Species: Rat (Male, female) = 125 mg/kg bw/day - Duration:

13 weeks

Test: LOAEL

- Route: Oral - Species: mouse (Male, female) = 500 mg/kg bw/day - Duration: 13 days

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg - Source: OECD 401

Test: LD50 - Route: Skin - Species: Rat > 2000 mg/kg - Source: OECD 402

Test: LC50 - Route: Inhalation - Species: Rat > 10.8 mg/l

Test: LC50 - Route: Skin - Species: Rabbit > 5000 mg/kg - Source: OECD 402

Test: LC0 - Route: Inhalation Vapour - Species: Rabbit = 23.5 mg/l - Source: OECD 403

Test: ATE - Route: Oral > 5000 mg/kg

Test: ATE - Route: Inhalation Vapour > 23.5 mg/l - Duration: 6 hours

Test: ATE - Route: Skin > 5000 mg/kg

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

Acute toxicity

ATE - Oral 3739 mg/kg bw

ATE - Dermal 2001 mg/kg bw

ATE - Inhalation (Vapours) 30,02 mg/l



Test: LD50 - Route: Oral - Species: Rat (male) = 3739 mg/kg - Source: OECD 401 Test: LD50 - Route: Oral - Species: Rat (female) = 4277 mg/kg - Source: OECD 401

Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 5 mg/l - Duration: 4h

Test: LC50 - Route: Inhalation Vapour - Species: Rat (Male, female) = 30.02 mg/l -

Duration: 4h - Source: OECD 403 Test: ATE - Route: Oral = 3739 mg/kg

Test: ATE - Route: Inhalation Vapour = 30.02 mg/l - Duration: 4h

11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration >= 0.1%

Other toxicological information:

None.

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

DIESTONE D-SATWIPES/PROSAT/SOCOSAT

Not classified for environmental hazards

Based on available data, the classification criteria are not met

n-butyl acetate - CAS: 123-86-4

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae = 647.7 mg/l - Duration h: 72 - Notes: Desmodesmus subspicatus

Endpoint: NOEC - Species: Algae = 200 mg/l - Notes: Desmodesmus subspicatus

Endpoint: EC50 - Species: Aquatic plants = 397 mg/l - Duration h: 72 - Notes: DIN 38412 Part. 9,

Pseudokirchneriella subcapitata

Endpoint: LC50 - Species: Fish = 18 mg/l - Duration h: 96 - Notes: OECD 203, Pimephales promelas

Endpoint: EC50 - Species: bacteria = 356 mg/l - Duration h: 40 - Notes: Tetrahymena pyriformis

Endpoint: EC50 - Species: Daphnia = 44 mg/l - Duration h: 48 - Notes: OECD 202

Endpoint: ErC50 - Species: Aquatic plants = 397 mg/l - Duration h: 72 - Notes: OECD 201,

Pseudokirchneri

ella subcapitata

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 23 mg/l - Duration h: 504 - Notes: OCDE 211

Endpoint: NOEC - Species: Aquatic plants = 196 mg/l - Duration h: 72 - Notes: OECD 201,

Pseudokirchneri

ella subcapitata

Endpoint: IC50 - Species: bacteria = 356 mg/l - Duration h: 40 - Notes: TETRATOX assay, Tetrahymena pyriformis

d) Terrestrial toxicity:

Endpoint: EC50 > 1000 mg/kg - Duration h: 336 - Notes: Lactuca sativa



2-methoxy-1-methylethyl acetate - CAS: 108-65-6

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Aquatic plants > 1000 mg/l - Duration h: 72 - Notes: Selenastrum

capricornutum, OECD 201

Endpoint: LC50 - Species: Fish = 134 mg/l - Duration h: 96 - Notes: Oncorhynchus mykiss, OECD

203

Endpoint: EC50 - Species: Invertebrates > 500 mg/l - Duration h: 48 - Notes: Daphnia magna

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Fish = 47.5 mg/l - Duration h: 336 - Notes: Oryzias latipes, OECD 204 Endpoint: NOEC - Species: Invertebrates > 100 mg/l - Duration h: 504 - Notes: Daphnia magna, OECD 202

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 1000 mg/l - Duration h: 96 - Notes: Leuciscus idus, LC/EC/IC50

Endpoint: LC50 - Species: Daphnia > 1000 mg/l - Duration h: 48 - Notes: LC/EC/IC50

Endpoint: LC50 - Species: Algae > 1000 mg/l - Notes: LC/EC/IC50

Endpoint: LC50 - Species: Fish < 4600 mg/l - Duration h: 96 - Notes: Leuciscus idus

12.2. Persistence and degradability

n-butyl acetate - CAS: 123-86-4

Biodegradability: Biodegradability rate - Test: OECD 301D - Duration: 5 days - %: 83% - Notes: CEE 92/69, C.4-E

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

Biodegradability: Biological oxygen demand (BOD) - Test: OECD 301F - Duration: 28 days - %:

83% - Notes: ISO 9408; 92/69/CEE, C.4-D

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

Biodegradability: Readily biodegradable

12.3. Bioaccumulative potential

n-butyl acetate - CAS: 123-86-4

BCF 15.3

Log Kow 2.3 - Notes: 25 °C

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

BCF < 100

Log Pow < 3

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

Log Pow 0.37

12.4. Mobility in soil

n-butyl acetate - CAS: 123-86-4

Log Koc 1.268

Volatility (H: Henry's Law Constant) 28.5 Pa.m³/mol - Notes: 25 °C

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration >= 0.1%

12.7. Other adverse effects

No harmful effects expected.



SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

Codes of wastes (Décision 2001/573/EC, Directive 2006/12/EEC, Directive 94/31/EEC on hazardous waste):

15 02 02* absorbents, filter materials (including oil filters not otherwise specified), wiping cloths, protective clothing contaminated by dangerous substances

SECTION 14: Transport information



14.1. UN number or ID number

ADR-UN Number: 3175
IATA-UN Number: 3175
IMDG-UN Number: 3175

14.2. UN proper shipping name

ADR-Shipping Name: SOLIDS or mixtures of solids (such as preparations and wastes)

CONTAINING FLAMMABLE LIQUID, N.O.S. having a flash-point up to 60 °C (n-butyl acetate, 2-methoxy-1-methylethyl acetate)

IATA-Shipping Name: SOLIDS or mixtures of solids (such as preparations and wastes)

CONTAINING FLAMMABLE LIQUID, N.O.S. having a flash-point

up to 60 °C (n-butyl acetate, 2-methoxy-1-methylethyl acetate)

IMDG-Shipping Name: SOLIDS or mixtures of solids (such as preparations and wastes)

CONTAINING FLAMMABLE LIQUID, N.O.S. having a flash-point up to 60 °C (n-butyl acetate, 2-methoxy-1-methylethyl acetate)

14.3. Transport hazard class(es)

ADR-Class: 4.1

ADR - Hazard identification number: 40

IATA-Class: 4.1 IATA-Label: 4.1 IMDG-Class: 4.1

14.4. Packing group

ADR-Packing Group: II
IATA-Packing group: II
IMDG-Packing group: II

14.5. Environmental hazards

ADR-Enviromental Pollutant: No IMDG-Marine pollutant: No IMDG-EmS: E.A. (1997)

IMDG-EmS: F-A , S-I

14.6. Special precautions for user

ADR-Subsidiary hazards: -

ADR-S.P.: 216 274 601

ADR-Transport category (Tunnel restriction code): 2 (E)

IATA-Passenger Aircraft: 445
IATA-Subsidiary hazards: -



IATA-Cargo Aircraft: 448
IATA-S.P.: A46
IATA-ERG: 3L
IMDG-Subsidiary hazards: -

IMDG-Stowage and handling: Category B

IMDG-Segregation: -

Q.L.: 1K Q.E.: E2

14.7. Maritime transport in bulk according to IMO instruments

N.A

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Regulation (EU) n. 2021/849 (ATP 17 CLP)

Regulation (EU) n. 2022/692 (ATP 18 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restriction 40

Restrictions related to the substances contained:

Restriction 30

Restriction 75



Listed or in compliance with the following international inventories: N.A.

Labelling of detergents (EC Regulations 648/2004 and 907/2006):

N.A.

Labelling of biocides (Regulations 1896/2000, 1687/2002, 2032/2003, 1048/2005, 1849/2006, 1451/2007 and Directive 98/8/EC):

N.A.

N.A.

Where applicable, refer to the following regulatory provisions:

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments.

1999/13/EC (VOC directive) Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1
Product belongs to category: P5c

15.2. Chemical safety assessment

Nο

SECTION 16: Other information

N.A.: Not Applicable or Not Available

Full text of phrases referred to in Section 3:

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

Hazard class and hazard category	Code	Description
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3



This safety data sheet has been completely updated in compliance to Regulation 2020/878. Paragraphs modified from the previous revision:

SECTION 1: Identification of the substance/mixture and of the company/undertaking

SECTION 2: Hazards identification

SECTION 3: Composition/information on ingredients SECTION 8: Exposure controls/personal protection

SECTION 9: Physical and chemical properties

SECTION 11: Toxicological information SECTION 12: Ecological information SECTION 15: Regulatory information

(EC) 1272/2008 [CLP] Yönetmeligine göre karisimlarin siniflandirmasini elde etmek için kullanılan siniflandirma ve prosedür:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Flam. Liq. 3, H226	On basis of test data
STOT SE 3, H336	Calculation method

This document was prepared by a competent person who has received appropriate training. Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

CCNL - Appendix 1

Insert further consulted bibliography

Important confidentiality: this document contains confidential information that is proprietary to SOCOMORE. Subject to legal provisions determining otherwise, the distribution, republication or re-transmission of this document, in full or in part, must be limited to clearly identified individuals, either because they use the product, or to provide HSE information. Any communication of this document outside of this framework without our written consent is strictly forbidden.

SOCOMORE strongly advises every recipient of this safety data sheet to read it carefully and to consult experts in the field if necessary or appropriate, in order to understand the information it contains, notably the possible dangers associated with this product. The users must ensure the conformity and completeness of this information with regards to their specific use of the product.

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the responsibility of the purchaser/user to ensure that their activities conform with current legislation in force.



The information is considered correct, but it is not exhaustive and it shall be used only as a guide which is based on the current knowledge of the substance or mixture and it is applicable to the safety precautions appropriate for the product.

ADR: European Agreement concerning the International Carriage of

Dangerous Goods by Road.

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of

Chemicals.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport

Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization"

(ICAO).

IMDG: International Maritime Code for Dangerous Goods.INCI: International Nomenclature of Cosmetic Ingredients.

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LTE: Long-term exposure.

PNEC: Predicted No Effect Concentration.

RID: Regulation Concerning the International Transport of Dangerous Goods

by Rail.

STE: Short-term exposure.

STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity.

STOT SE: May cause drowsiness or dizziness

TLV: Threshold Limiting Value.
TWA: Time-weighted average

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day.

(ACGIH Standard).

WGK: German Water Hazard Class.