

## Safety Data Sheet

### DIESTONE DLS-SATWIPES/PROSAT/SOCOSAT - P29003

Master item code: P28280

Safety Data Sheet date: 30/9/2024, version 2

---

#### 1. Identification

##### GHS Product Identifier

Mixture identification:

Trade name: DIESTONE DLS-SATWIPES/PROSAT/SOCOSAT

SDS code: P29003

##### Recommended use of the chemical and restrictions on use

Recommended use:

Solvent

Cleaner

Industrial uses

Restrictions on use:

No uses advised against are identified.

##### Supplier's details

###### Manufacturers:

Socomore SASU - Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - France

-Tel. +33 (0)2 97 43 76 90

Manufacturing - Parc Gohelis - 56250 ELVEN France - Tel +33 (0)2 97 43 76 83 - Fax +33 (0)2 97 54 50 26

Socomore Ireland Ltd. - Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922 / Fax +353 21 4889923 / ireland@socomore.com

###### Distributors:

Surface Prep New Zealand Ltd, 301/ 6-8 Heather Street Parnell, Auckland 1052, NEW

ZEALAND, PH 021 455595 / info@surfaceprep.co.nz

##### Competent person responsible for the safety data sheet:

msdsinformation-eu@socomore.com

##### Emergency phone number:

New Zealand emergency phone number: 0800 764 766 (0800 POISON)

International : CHEMTEL +1-813-248-0585.

---

#### 2. Hazards identification

Classification complies with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS Ed.7) and is consistent with ERMA New Zealand Approval number (HSNO) which is reported in Section 15.

- ⚠ Warning, Flam. Liq. 3, Flammable liquid and vapour.
- ⚠ Warning, Eye Irrit. 2A, Causes serious eye irritation.
- ⚠ Warning, STOT SE 3, May cause drowsiness or dizziness.

**Safety Data Sheet****DIESTONE DLS-SATWIPES/PROSAT/SOCOSAT - P29003****GHS label elements, including precautionary statements**

Hazard pictograms:



Warning

Hazard statements:

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof [electrical/ventilating/lighting/...] equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/clothing and eye/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor/... if you feel unwell.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use a CO2 fire extinguisher to extinguish.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

**Other hazards which do not result in a classification:**

No other hazards

---

**3. Composition/information on ingredients****Substances**

N.A.




(N.A. = not applicable)

**Safety Data Sheet****DIESTONE DLS-SATWIPES/PROSAT/SOCOSAT - P29003****Mixtures**

Hazardous components within the meaning of GHS and related classification:




>= 30% - < 60% 1-methoxy-2-propanol; monopropylene glycol methyl ether

REACH No.: 01-2119457435-35, Index number: 603-064-00-3, CAS: 107-98-2, EC: 203-539-1

-  2.6/3 Flam. Liq. 3 H226
-  3.3/2A Eye Irrit. 2A H319
-  3.8/3 STOT SE 3 H336




>= 10% - < 12.5% 2-methoxy-1-methylethyl acetate

REACH No.: 01-2119475791-29, Index number: 607-195-00-7, CAS: 108-65-6, EC: 203-603-9

-  2.6/3 Flam. Liq. 3 H226
-  3.3/2A Eye Irrit. 2A H319
-  3.8/3 STOT SE 3 H336

>= 5% - < 7% HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

REACH No.: 01-2119463258-33, EC: 919-857-5

-  2.6/3 Flam. Liq. 3 H226
-  3.10/1 Asp. Tox. 1 H304
-  3.8/3 STOT SE 3 H336

% = weight/weight

NOTE: The Hazard Classifications listed in this section refer to the chemical at a pure concentration. The actual concentration of chemicals has been withheld as trade secret.

---

**4. First-aid measures****Description of necessary first-aid measures**

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting. Obtain a medical examination.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

**Most important symptoms/effects, acute and delayed**

## Safety Data Sheet

### DIESTONE DLS-SATWIPES/PROSAT/SOCOSAT - P29003

None

#### Indication of immediate medical attention and special treatment needed, if necessary

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

No particular treatment.

---

## 5. Fire-fighting measures

#### Suitable extinguishing media

In case of fire: Use a CO2 fire extinguisher to extinguish.

#### Unsuitable extinguishing media

None in particular.

#### Special hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

#### Hazardous combustion products:

None

Explosive properties: N.A.

Oxidizing properties: N.A.

#### Special protective actions for fire-fighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

---

## 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

**For non emergency personnel:**

**For emergency responders:**

#### Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

#### Methods and material for containment and cleaning up

Wash with plenty of water.

---

## 7. Handling and storage

#### Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

#### Advice on general occupational hygiene:

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

#### Conditions for safe storage, including any incompatibilities

Store under the same conditions as a combustible solid product.

## Safety Data Sheet

### DIESTONE DLS-SATWIPES/PROSAT/SOCOSAT - P29003

Avoid vapor emissions.

Always keep in a well ventilated place.

Store at ambient temperatures. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Avoid accumulating electrostatic charge.

#### Incompatible materials:

None in particular.

#### Instructions as regards storage premises:

Cool and adequately ventilated.

Safety electric system.

---

## 8. Exposure controls/personal protection

### Control parameters

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

- OEL Type: National - TWA(8h): 188 mg/m<sup>3</sup>, 50 ppm - STEL: 375 mg/m<sup>3</sup>, 100 ppm -

Behaviour: Binding - Notes: France VLEC - INRS TMP N°84

- OEL Type: National - TWA: 370 mg/m<sup>3</sup>, 100 ppm - Notes: Germany

- OEL Type: National - TWA: 180 mg/m<sup>3</sup> - STEL: 360 mg/m<sup>3</sup> - Notes: Poland

- OEL Type: EU - TWA(8h): 375 mg/m<sup>3</sup>, 100 ppm - STEL: 563 mg/m<sup>3</sup>, 150 ppm - Notes:

Skin

- OEL Type: ACGIH - TWA(8h): 50 ppm - STEL: 100 ppm - Notes: A4 - Eye and URT irr

- OEL Type: National - TWA: 187 mg/m<sup>3</sup>, 50 ppm - STEL(15min (Miw)): 187 mg/m<sup>3</sup>, 50

ppm - Notes: Austria

- OEL Type: National - TWA(8h): 375 mg/m<sup>3</sup>, 100 ppm - STEL(15min (Miw)): 560 mg/m<sup>3</sup>,

150 ppm - Notes: United Kingdom - Skin

- OEL Type: National - TWA(8h): 188 mg/m<sup>3</sup>, 50 ppm - STEL: 375 mg/m<sup>3</sup>, 100 ppm -

Notes: Canada (Gazette Officielle du Québec, January 4, 2023, Vol. 155, No.1)

- OEL Type: National - TWA: 180 mg/m<sup>3</sup>, 50 ppm - Notes: Norway (skin)

- OEL Type: DOW IHG - TWA: 1.5 ppm - STEL: 4.5 ppm

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

- OEL Type: ACGIH - TWA(8h): 150 ppm - STEL: 100 ppm

- OEL Type: National - TWA(8h): 275 mg/m<sup>3</sup>, 50 ppm - STEL: 550 mg/m<sup>3</sup>, 100 ppm -

Behaviour: Binding - Notes: France VLEPC

- OEL Type: National - TWA(8h): 270 mg/m<sup>3</sup>, 50 ppm - Notes: GERMANY

- OEL Type: National - TWA(8h): 274 mg/m<sup>3</sup>, 50 ppm - STEL: 548 mg/m<sup>3</sup>, 100 ppm -

Notes: UK (WELs)

- OEL Type: National - TWA: 260 mg/m<sup>3</sup> - STEL: 520 mg/m<sup>3</sup> - Notes: POLAND

- OEL Type: EU - TWA(8h): 275 mg/m<sup>3</sup>, 50 ppm - STEL: 550 mg/m<sup>3</sup>, 100 ppm - Notes:

Skin

- OEL Type: AIHA

- TWA: 50 ppm

- OEL Type: National - TWA: 275 mg/m<sup>3</sup>, 50 ppm - STEL(5 min (Mow)): 550 mg/m<sup>3</sup>, 100

ppm - Notes: Österreich

## Safety Data Sheet

### DIESTONE DLS-SATWIPES/PROSAT/SOCOSAT - P29003

- OEL Type: National - TWA: 270 mg/m<sup>3</sup>, 50 ppm - Notes: Norway (Skin)
- HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS
- OEL Type: National - TWA: 1200 mg/m<sup>3</sup>, 197 ppm - Notes: ExxonMobil
- OEL Type: National - TWA: 300 mg/m<sup>3</sup> - STEL: 900 mg/m<sup>3</sup> - Notes: Poland (NDS, DNSCh)
- OEL Type: National - TWA: 300 mg/m<sup>3</sup>, 50 ppm - STEL: 600 mg/m<sup>3</sup>, 100 ppm - Notes: Germany
- OEL Type: National - TWA: 300 mg/m<sup>3</sup>, 50 ppm - STEL: 600 mg/m<sup>3</sup>, 100 ppm - Notes: Switzerland

#### DNEL Exposure Limit Values

- 1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2
  - Worker Industry: 369 mg/m<sup>3</sup> - Consumer: 43.9 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
  - Worker Industry: 50.6 mg/kg b.w./day - Consumer: 18.1 mg/kg b.w./day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
  - Consumer: 3.3 mg/kg b.w./day - Exposure: Human Oral - Frequency: Long Term, systemic effects
  - Worker Industry: 553.5 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term (acute)
- 2-methoxy-1-methylethyl acetate - CAS: 108-65-6
  - Worker Industry: 796 mg/kg b.w./day - Consumer: 320 mg/kg b.w./day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
  - Worker Industry: 275 mg/m<sup>3</sup> - Consumer: 33 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
  - Consumer: 36 mg/kg b.w./day - Exposure: Human Oral - Frequency: Long Term, systemic effects
  - Worker Industry: 550 mg/m<sup>3</sup> - Consumer: 33 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, local effects
- HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS
  - Worker Industry: 208 mg/kg b.w./day - Consumer: 125 mg/kg b.w./day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
  - Worker Industry: 871 mg/m<sup>3</sup> - Consumer: 185 mg/kg b.w./day - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
  - Consumer: 125 mg/kg b.w./day - Exposure: Human Oral - Frequency: Long Term, systemic effects

#### PNEC Exposure Limit Values

- 1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2
  - Target: Fresh Water - Value: 10 mg/l
  - Target: Freshwater sediments - Value: 41.6 mg/kg
  - Target: Marine water sediments - Value: 4.17 mg/kg
  - Target: Soil (agricultural) - Value: 2.47 mg/kg
  - Target: Microorganisms in sewage treatments - Value: 100 mg/l
  - Target: Marine water - Value: 1 mg/l
  - Target: Water (intermittent discharge) - Value: 100 mg/l
- 2-methoxy-1-methylethyl acetate - CAS: 108-65-6

## Safety Data Sheet

### DIESTONE DLS-SATWIPES/PROSAT/SOCOSAT - P29003

Target: Fresh Water - Value: 0.635 mg/l

Target: Marine water - Value: 0.0635 mg/l

Target: Microorganisms in sewage treatments - Value: 100 mg/l

Target: Freshwater sediments - Value: 3.29 mg/kg dw

Target: Marine water sediments - Value: 0.329 mg/kg dw

Target: Soil - Value: 0.29 mg/kg

Target: PNEC intermittent - Value: 6.35 mg/l

#### Appropriate engineering controls:

None

#### Individual protection measures, such as personal protective equipment (PPE)

##### Eye protection:

Safety goggles (EN 166)

##### Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

##### Protection for hands:

Suitable gloves type: NF EN374

Butyl caoutchouc (butyl rubber).

##### Respiratory protection:

Use adequate protective respiratory equipment.

Filtering Half-face mask (NF EN 149), class FFP1

Mask with filter "A1" , brown colour (NF EN14387)

##### Thermal Hazards:

None

## 9. Physical and chemical properties

Properties	Value	Method:	Notes
Physical state:	Liquid coated on wipes	--	--
Colour:	Colourless	--	--
Odour:	N.A.	--	--
pH:	Not Relevant	--	--
Kinematic viscosity:	N.A.	--	--
Melting point / freezing point:	Not Relevant	--	--
Initial boiling point and boiling range:	117 °C	--	--
Flammability:	The product is classified:	--	--

## Safety Data Sheet

### DIESTONE DLS-SATWIPES/PROSAT/SOCOSAT - P29003

	Flammable liquid and vapour.		
Flash point (°C):	> 21 °C - ≤ 55 °C	--	--
Upper/lower flammability or explosive limits:	0.6% - 13.1% (V)	--	--
Vapour pressure:	5,9 KPa (20°C)	--	--
Vapour density:	3.4	--	--
Relative density:	< 1	--	--
Solubility in water:	N.A.	--	--
Solubility in oil:	N.A.	--	--
Partition coefficient (n-octanol/water):	N.A.	--	--
Auto-ignition temperature:	276°C	--	--
Decomposition temperature:	N.A.	--	--
Particle characteristics:			
Particle size:	N.A.	--	--

#### SECTION 10: Stability and reactivity

##### Reactivity

It may generate dangerous reactions (See subsections below)

##### Chemical stability

It may generate dangerous reactions (See subsections below)

##### Possibility of hazardous reactions

None

##### Conditions to avoid

Avoid accumulating electrostatic charge.

##### Incompatible materials

Avoid contact with combustible materials. The product could catch fire.



**Safety Data Sheet****DIESTONE DLS-SATWIPES/PROSAT/SOCOSAT - P29003****Hazardous decomposition products**

None.

**11. Toxicological information****Information on toxicological effects**

Toxicological information of the product:

DIESTONE DLS-SATWIPES/PROSAT/SOCOSAT

Acute toxicity

Not classified

Based on available data, the classification criteria are not met

Skin corrosion/irritation

Not classified

Based on available data, the classification criteria are not met

Serious eye damage/irritation

The product is classified: Eye Irrit. 2A H319

Respiratory or skin sensitisation

Not classified

Based on available data, the classification criteria are not met

Germ cell mutagenicity

Not classified

Based on available data, the classification criteria are not met

Carcinogenicity

Not classified

Based on available data, the classification criteria are not met

Reproductive toxicity

Not classified

Based on available data, the classification criteria are not met

STOT-single exposure

The product is classified: STOT SE 3 H336

STOT-repeated exposure

Not classified

Based on available data, the classification criteria are not met

Aspiration hazard

Not classified

Based on available data, the classification criteria are not met

Toxicological information of the main substances found in the product:

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat (male) = 3739 mg/kg - Source: OECD 401

Test: LD50 - Route: Oral - Species: Rat (female) = 4277 mg/kg - Source: OECD 401

Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 5 mg/l - Duration: 4h

Test: LC50 - Route: Inhalation Vapour - Species: Rat (Male, female) = 30.02 mg/l -

**Safety Data Sheet****DIESTONE DLS-SATWIPES/PROSAT/SOCOSAT - P29003**

Duration: 4h - Source: OECD 403

Test: ATE - Route: Oral = 3739 mg/kg

Test: ATE - Route: Inhalation Vapour = 30.02 mg/l - Duration: 4h

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg - Source: OECD 401

Test: LD50 - Route: Skin - Species: Rat > 2000 mg/kg - Source: OECD 402

Test: LC50 - Route: Inhalation - Species: Rat > 10.8 mg/l

Test: LC50 - Route: Skin - Species: Rabbit > 5000 mg/kg - Source: OECD 402

Test: LC0 - Route: Inhalation Vapour - Species: Rabbit = 23.5 mg/l - Source: OECD 403

Test: ATE - Route: Oral > 5000 mg/kg

Test: ATE - Route: Inhalation Vapour > 23.5 mg/l - Duration: 6 hours

Test: ATE - Route: Skin > 5000 mg/kg

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg - Duration: 4h - Source: OECD 401

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg - Duration: 24 hours - Source: OECD 402

Test: LC50 - Route: Inhalation - Species: Rat > 4951 mg/m<sup>3</sup> - Duration: 4h - Source: OECD 403

---

**12. Ecological information****Toxicity**

Adopt good working practices, so that the product is not released into the environment.

DIESTONE DLS-SATWIPES/PROSAT/SOCOSAT

Not classified for environmental hazards

Based on available data, the classification criteria are not met

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 1000 mg/l - Duration h: 96 - Notes: Leuciscus idus, LC/EC/IC50

Endpoint: LC50 - Species: Daphnia > 1000 mg/l - Duration h: 48 - Notes: LC/EC/IC50

Endpoint: LC50 - Species: Algae > 1000 mg/l - Notes: LC/EC/IC50

Endpoint: LC50 - Species: Fish < 4600 mg/l - Duration h: 96 - Notes: Leuciscus idus

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Aquatic plants > 1000 mg/l - Duration h: 72 - Notes: Selenastrum capricornutum, OECD 201

Endpoint: LC50 - Species: Fish = 134 mg/l - Duration h: 96 - Notes: Oncorhynchus mykiss, OECD 203

Endpoint: EC50 - Species: Invertebrates > 500 mg/l - Duration h: 48 - Notes: Daphnia magna

b) Aquatic chronic toxicity:

**Safety Data Sheet****DIESTONE DLS-SATWIPES/PROSAT/SOCOSAT - P29003**

Endpoint: NOEC - Species: Fish = 47.5 mg/l - Duration h: 336 - Notes: Oryzias latipes, OECD 204

Endpoint: NOEC - Species: Invertebrates > 100 mg/l - Duration h: 504 - Notes: Daphnia magna, OECD 202

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 1000 mg/l - Duration h: 96 - Notes: Oncorhynchus mykiss

Endpoint: EC50 - Species: Algae > 1000 mg/l - Duration h: 72 - Notes: Pseudokirchnerella subcapitata

Endpoint: EC50 - Species: Daphnia > 1000 mg/l - Duration h: 48 - Notes: Daphnia magna

Endpoint: DSEO-R (NOELR) - Species: Algae = 3 mg/l - Duration h: 72 - Notes:

Pseudokirchnerella subcapitata - biomass - OECD 201)

Endpoint: DSEO-R (NOELR) - Species: Algae = 100 mg/l - Duration h: 72 - Notes:

Pseudokirchnerella subcapitata - growth rate - OECD 201)

b) Aquatic chronic toxicity:

Endpoint: DSEO-R (NOELR) - Species: Daphnia = 0.23 mg/l - Duration h: 504 - Notes: Daphnia magna - QSAR Petrotox

Endpoint: DSEO-R (NOELR) - Species: Fish = 0.13 mg/l - Duration h: 672 - Notes:

Oncorhynchus mykiss - QSAR Petrotox

**Persistence and degradability**

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

Biodegradability: Readily biodegradable

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

Biodegradability: Biological oxygen demand (BOD) - Test: OECD 301F - Duration: 28 days

- %: 83% - Notes: ISO 9408; 92/69/CEE, C.4-D

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

Biodegradability: Biodegradability rate - Duration: 28 days - %: 80%

Biodegradability: Photodegradation (in air)

**Bioaccumulative potential**

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

Log Pow 0.37

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

BCF < 100

Log Pow < 3

**Mobility in soil**

N.A.

**Other adverse effects**

Wassergefährdungsklasse (Deutschland): 2

---

**13. Disposal considerations****Disposal methods:**

Disposal should be in accordance with applicable regional, national and local laws and regulations. Please consult Technical Data Sheet for details.

**Safety Data Sheet**

**DIESTONE DLS-SATWIPES/PROSAT/SOCOSAT - P29003**

**14. Transport information**



**UN number**

ADR-UN Number: 3175  
 IATA-UN Number: 3175  
 IMDG-UN Number: 3175

**UN proper shipping name**

ADR-Shipping Name: SOLIDS or mixtures of solids (such as preparations and wastes) CONTAINING FLAMMABLE LIQUID, N.O.S. having a flash-point up to 60 °C(1-methoxy-2-propanol; monopropylene glycol methyl ether, 2-methoxy-1-methylethyl acetate)

IATA-Shipping Name: SOLIDS or mixtures of solids (such as preparations and wastes) CONTAINING FLAMMABLE LIQUID, N.O.S. having a flash-point up to 60 °C(1-methoxy-2-propanol; monopropylene glycol methyl ether, 2-methoxy-1-methylethyl acetate)

IMDG-Shipping Name: SOLIDS or mixtures of solids (such as preparations and wastes) CONTAINING FLAMMABLE LIQUID, N.O.S. having a flash-point up to 60 °C(1-methoxy-2-propanol; monopropylene glycol methyl ether, 2-methoxy-1-methylethyl acetate)

**Transport hazard class(es)**

ADR-Class: 4.1  
 ADR - Hazard identification number: 40  
 IATA-Class: 4.1  
 IATA-Label: 4.1  
 IMDG-Class: 4.1

**Packing group, if applicable**

ADR-Packing Group: II  
 IATA-Packing group: II  
 IMDG-Packing group: II

**Environmental hazards**

ADR-Environmental Pollutant: No  
 IMDG-Marine pollutant: No

**Special precautions for user**

ADR-Subsidiary hazards: -  
 ADR-S.P.: 216 274 601  
 ADR-Transport category (Tunnel restriction code): 2 (E)  
 IATA-Passenger Aircraft: 445  
 IATA-Subsidiary hazards: -  
 IATA-Cargo Aircraft: 448  
 IATA-S.P.: A46  
 IATA-ERG: 3L  
 IMDG-EmS: F-A , S-I

## Safety Data Sheet

### DIESTONE DLS-SATWIPES/PROSAT/SOCOSAT - P29003

IMDG-Subsidiary hazards: -  
IMDG-Stowage and handling: Category B  
IMDG-Segregation: -

**Transport in bulk according to IMO instruments**

N.A.

---

## 15. Regulatory information

### **Safety, health and environmental regulations specific for the product in question.**

This Safety Data Sheet has been prepared according to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS), Seventh revised edition.

### **International Inventories:**

The substances are listed or exempted from registration in the following international inventories:

AICS - Australian Inventory of Chemical Substances  
Canada (DSL): All the substances of this product are listed on the DSL list.  
IECSC - Inventory of Existing Chemical Substances Produced or Imported in China  
Japan (ENCS) - Japanese Existing and New Chemical Substances Inventory  
KECI - Korean Existing Chemical Inventory  
NZIoC - New Zealand Inventory of Chemicals  
PICCS - Philippine Inventory of Chemicals and Chemical Substances  
TCSI - Taiwan Chemical Substance Inventory  
TSCA - Toxic Substances Control Act

HSNO Group Standard Approval: HSR002528

The following substance(s) in this product has/have an identification by CAS number either in countries not affected by the REACH regulation or in regulations not yet updated to reflect the new naming convention for hydrocarbon solvents:

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS (CAS: 64742-48-9)

---

## 16. Other information

This document was prepared by a competent person who has received appropriate training. Classification complies with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS Ed.7) and is consistent with ERMA New Zealand Approval number (HSNO) which is reported in Section 15.

Full text of phrases referred to in Section 3:

H226 Flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H304 May be fatal if swallowed and enters airways.

Main bibliographic sources:

P29003/2

Page 13 / 15

## Safety Data Sheet

### DIESTONE DLS-SATWIPES/PROSAT/SOCOSAT - P29003

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,  
Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van  
Nostrand Reinold

CCNL - Appendix 1

Insert further consulted bibliography

Important confidentiality : this document contains confidential information that is proprietary to SOCOMORE. Subject to legal provisions determining otherwise, the distribution, republication or re-transmission of this document, in full or in part, must be limited to clearly identified individuals, either because they use the product, or to provide HSE information. Any communication of this document outside of this framework without our written consent is strictly forbidden.

SOCOMORE strongly advises every recipient of this safety data sheet to read it carefully and to consult experts in the field if necessary or appropriate, in order to understand the information it contains, notably the possible dangers associated with this product. The users must ensure the conformity and completeness of this information with regards to their specific use of the product.

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the responsibility of the purchaser/user to ensure that their activities conform with current legislation in force.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.

## Safety Data Sheet

### DIESTONE DLS-SATWIPES/PROSAT/SOCOSAT - P29003

STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.

Safety Data Sheet date: 30/9/2024, version 2