

**Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))
DILUANT DL 108**

Regulation (EU) n. 2020/878

Safety Data Sheet date: 16/1/2024, version 1**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Trade name: DILUANT DL 108
SDS code: 100410EU
UFI: 5CCG-1C70-JA9C-4A30

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Industrial uses
Thinner

1.3. Details of the supplier of the safety data sheet**Manufacturers:**

Socomore SASU

Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - France

Tel : +33 (0)2 97 43 76 83 - Fax : +33 (0)2 97 54 50 26

Socomore Ireland Ltd. - Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922 / Fax
+353 21 4889923 / ireland@socomore.com

Distributors:

Socomore SASU

Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - France

Tel : +33 (0)2 97 43 76 83 - Fax : +33 (0)2 97 54 50 26

Socomore Ireland Ltd. - Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922 / Fax
+353 21 4889923 / ireland@socomore.com

Competent person responsible for the safety data sheet:

techdirsocomore@socomore.com

1.4. Emergency telephone number

France : ORFILA (INRS) +33 (0)1 45 42 59 59

International : CHEMTEL +1-813-248-0585.

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****EC regulation criteria 1272/2008 (CLP)**

- ⚠ Warning, Flam. Liq. 3, Flammable liquid and vapour.
- ⚠ Warning, Acute Tox. 4, Harmful in contact with skin.
- ⚠ Warning, Acute Tox. 4, Harmful if inhaled.
- ⚠ Warning, Skin Irrit. 2, Causes skin irritation.
- ⚠ Warning, Eye Irrit. 2, Causes serious eye irritation.
- ⚠ Warning, STOT SE 3, May cause respiratory irritation.
- ⚠ Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure.
- ⚠ Danger, Asp. Tox. 1, May be fatal if swallowed and enters airways.
Aquatic Chronic 3, Harmful to aquatic life with long lasting effects.

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

DILUANT DL 108

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:



Danger

Hazard statements:

H226 Flammable liquid and vapour.

H312+H332 Harmful in contact with skin or if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/...

P331 Do NOT induce vomiting.

P370+P378 In case of fire: Use dry sand, chemical powder or alcohol-resistant foam for extinction.

P403+P235 Store in a well-ventilated place. Keep cool.

Special Provisions:

None

Contains

reaction mass of ethylbenzene and xylene

ethylbenzene

toluene

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration $\geq 0.1\%$

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))
DILUANT DL 108

| Qty | Name | Ident. Number | Classification |
|-----------------------|--|---|--|
| >= 80% - < 90% | reaction mass of ethylbenzene and xylene | CAS: 1330-20-7 EC: 905-588-0 REACH No.: 01-2119488216-32 | <ul style="list-style-type: none"> ⚠ 2.6/3 Flam. Liq. 3 H226 ⚠ 3.10/1 Asp. Tox. 1 H304 ⚠ 3.1/4/Dermal Acute Tox. 4 H312 ⚠ 3.1/4/Inhal Acute Tox. 4 H332 ⚠ 3.2/2 Skin Irrit. 2 H315 ⚠ 3.3/2 Eye Irrit. 2 H319 ⚠ 3.8/3 STOT SE 3 H335 ⚠ 3.9/2 STOT RE 2 H373 4.1/C3 Aquatic Chronic 3 H412 Acute Toxicity Estimate: ATE - Dermal 1100 mg/kg bw ATE - Inhalation (Vapours) 11 mg/l |
| >= 15% - < 20% | ethylbenzene | Index number: 601-023-00-4 CAS: 100-41-4 EC: 202-849-4 REACH No.: 01-2119489370-35 | <ul style="list-style-type: none"> ⚠ 2.6/2 Flam. Liq. 2 H225 ⚠ 3.2/2 Skin Irrit. 2 H315 ⚠ 3.3/2 Eye Irrit. 2 H319 4.1/C3 Aquatic Chronic 3 H412 ⚠ 3.1/4/Inhal Acute Tox. 4 H332 ⚠ 3.9/2 STOT RE 2 H373 (hearing organs) ⚠ 3.10/1 Asp. Tox. 1 H304 Acute Toxicity Estimate: ATE - Inhalation (Vapours) 11 mg/l |
| >= 1% - < 3% | toluene | Index number: 601-021-00-3 CAS: 108-88-3 EC: 203-625-9 REACH No.: 01-2119471310-51 | <ul style="list-style-type: none"> ⚠ 2.6/2 Flam. Liq. 2 H225 ⚠ 3.7/2 Repr. 2 H361d ⚠ 3.10/1 Asp. Tox. 1 H304 ⚠ 3.9/2 STOT RE 2 H373 ⚠ 3.2/2 Skin Irrit. 2 H315 ⚠ 3.8/3 STOT SE 3 H336 4.1/C3 Aquatic Chronic 3 H412 |
| >= 0.001% - < 0.1% | Cumene | Index number: 601-024-00-X CAS: 98-82-8 EC: 202-704-5 | <ul style="list-style-type: none"> ⚠ 2.6/3 Flam. Liq. 3 H226 ⚠ 3.6/1B Carc. 1B H350 ⚠ 3.10/1 Asp. Tox. 1 H304 ⚠ 3.8/3 STOT SE 3 H335 ⚠ 4.1/C2 Aquatic Chronic 2 H411 |

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

**Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))
DILUANT DL 108**

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do NOT induce vomiting.

In case of Inhalation:

If breathing is irregular or stopped, administer artificial respiration.

In case of inhalation, consult a doctor immediately and show the packing or label.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

No particular treatment.

SECTION 5: Firefighting measures**5.1. Extinguishing media**

Suitable extinguishing media:

Foam.

Carbon dioxide (CO₂)

Dry powder

Extinguishing media which must not be used for safety reasons:

High power water jet

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

DILUANT DL 108

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, ensure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

7.2. Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Store at ambient temperatures. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

7.3. Specific end use(s)

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

reaction mass of ethylbenzene and xylene - CAS: 1330-20-7

- OEL Type: National - TWA(8h): 221 mg/m³, 50 ppm - STEL: 442 mg/m³, 100 ppm -

Notes: France VLEC - TMP N° 4Bis, 84

- OEL Type: National - TWA(8h): 440 mg/m³, 100 ppm - Notes: Germany - DFG, H

- OEL Type: National - TWA(8h): 220 mg/m³, 50 ppm - STEL: 441 mg/m³, 100 ppm -

Notes: UK (WELs)

- OEL Type: EU - TWA(8h): 221 mg/m³, 50 ppm - STEL: 442 mg/m³, 100 ppm - Notes:

Skin

- OEL Type: ACGIH - TWA(8h): 20 ppm - Notes: A4, BEI - URT and eye irr; hematologic eff; CNS impair

- OEL Type: National - TWA: 435 mg/m³, 100 ppm - STEL: 870 mg/m³, 200 ppm - Notes: Swiss - SUVA

- OEL Type: National - TWA: 221 mg/m³, 50 ppm - STEL(15min (Miw)): 442 mg/m³, 100

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

DILUANT DL 108

ppm - Notes: Österreich

- OEL Type: National - TWA: 221 mg/m³, 50 ppm - Notes: TWA:Poland

ethylbenzene - CAS: 100-41-4

- OEL Type: National - TWA(8h): 88.4 mg/m³, 20 ppm - Notes: Germany - EU, H

- OEL Type: National - TWA(8h): 88.4 mg/m³, 20 ppm - STEL: 442 mg/m³, 100 ppm -

Notes: France VLEC - TMP N° 84

- OEL Type: National - TWA(8h): 441 mg/m³, 100 ppm - STEL: 552 mg/m³, 125 ppm -

Notes: UK (WELs)

- OEL Type: EU - TWA(8h): 442 mg/m³, 100 ppm - STEL: 884 mg/m³, 200 ppm - Notes:

Skin

- OEL Type: ACGIH - TWA(8h): 20 ppm - Notes: OTO; A3, BEI - URT & eye irr; ototoxicity;

kidney eff; CNS impair

- OEL Type: National - STEL: 220 mg/m³ - Notes: Swiss

- OEL Type: MAK - TWA: 440 mg/m³, 100 ppm - STEL(5 min (Mow)): 880 mg/m³, 200

ppm - Notes: Österreich

toluene - CAS: 108-88-3

- OEL Type: National - TWA(8h): 190 mg/m³ - Notes: Germany - DFG, H, Y

- OEL Type: National - TWA(8h): 76.8 mg/m³, 20 ppm - STEL(15min (Miw)): 384 mg/m³,

100 ppm - Notes: France VLEC - TMP N° 4bis, 84

- OEL Type: EU - TWA(8h): 192 mg/m³, 50 ppm - STEL: 384 mg/m³, 100 ppm - Notes:

Skin

- OEL Type: National - TWA: 191 mg/m³, 50 ppm - STEL: 384 mg/m³, 100 ppm - Notes:

UK (WELs)

- OEL Type: ACGIH - TWA(8h): 20 ppm - Notes: OTO; A4; BEI - CNS, visual & hearing

impair; female repro system eff; pregnancy loss

- OEL Type: MAK - TWA: 190 mg/m³, 50 ppm - STEL(15min (Miw)): 380 mg/m³, 100

ppm - Notes: Österreich

Cumene - CAS: 98-82-8

- OEL Type: EU - TWA(8h): 50 mg/m³, 10 ppm - STEL: 250 mg/m³, 50 ppm - Notes: Skin

- OEL Type: ACGIH - TWA(8h): 5 ppm - Notes: A3 - URT adenoma, neurological eff

- OEL Type: National - TWA(8h): 50 mg/m³, 10 ppm - STEL(15min (Miw)): 250 mg/m³,

50 ppm - Behaviour: Binding - Notes: France, VLEPC / peau

- OEL Type: National - TWA: 50 mg/m³ - STEL: 250 mg/m³ - Notes: Poland (Skin / skóra)

DNEL Exposure Limit Values

reaction mass of ethylbenzene and xylene - CAS: 1330-20-7

Worker Industry: 77 mg/m³ - Consumer: 14.8 mg/m³ - Exposure: Human Inhalation -

Frequency: Long Term, systemic effects

Worker Industry: 289 mg/m³ - Consumer: 174 mg/kg b.w./day - Exposure: Human

Inhalation - Frequency: Short Term, local effects

Worker Industry: 289 mg/m³ - Consumer: 174 mg/kg b.w./day - Exposure: Human

Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 180 mg/kg b.w./day - Consumer: 108 mg/kg b.w./day - Exposure: Human

Dermal - Frequency: Long Term, systemic effects

Consumer: 1.6 mg/kg b.w./day - Exposure: Human Oral - Frequency: Long Term, systemic effects

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

DILUANT DL 108

ethylbenzene - CAS: 100-41-4

Worker Industry: 77 mg/m³ - Consumer: 15 mg/m³ - Exposure: Human Inhalation -
Frequency: Long Term, systemic effects

Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

Worker Industry: 180 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 293 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects

toluene - CAS: 108-88-3

Worker Professional: 384 mg/m³ - Consumer: 226 mg/m³ - Exposure: Human Inhalation -
Frequency: Short Term, systemic effects

Worker Professional: 192 mg/m³ - Consumer: 56.5 mg/m³ - Exposure: Human Inhalation -
Frequency: Long Term, systemic effects

Worker Professional: 180 mg/kg - Consumer: 226 mg/kg - Exposure: Human Dermal -
Frequency: Long Term, systemic effects

Consumer: 8.13 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

Worker Professional: 384 mg/m³ - Consumer: 226 mg/m³ - Exposure: Human Inhalation -
Frequency: Short Term, local effects

PNEC Exposure Limit Values

reaction mass of ethylbenzene and xylene - CAS: 1330-20-7

Target: Fresh Water - Value: 0.327 mg/l

Target: Water (intermittent discharge) - Value: 0.327 mg/l

Target: Marine water - Value: 0.327 mg/l

Target: Sewage treatment plant - Value: 6.58 mg/l

Target: Freshwater sediments - Value: 12.46 mg/kg

Target: Marine water sediments - Value: 12.46 mg/kg

Target: Soil - Value: 2.31 mg/kg

ethylbenzene - CAS: 100-41-4

Target: Marine water - Value: 0.01 mg/l - Notes:: factor assessment : 10

Target: Marine water - Value: 0.1 mg/l - Notes:: factor assessment : 18

Target: PNEC predator - Value: 2.68 mg/kg - Notes:: ECHA

toluene - CAS: 108-88-3

Target: Fresh Water - Value: 0.68 mg/l

Target: Freshwater sediments - Value: 16.39 mg/kg

Target: Soil (agricultural) - Value: 2.89 mg/kg

Target: Microorganisms in sewage treatments - Value: 13.61 mg/l

Biological Exposure Index

reaction mass of ethylbenzene and xylene - CAS: 1330-20-7

Remark: ACGIH BEL (2009)

Remark: FR IBE (1997)

8.2. Exposure controls

See below, example of PPE to use.

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

DILUANT DL 108

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use respiratory protection where ventilation is insufficient or exposure is prolonged.

Use adequate protective respiratory equipment.

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

Other conditions affecting workers exposure:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Properties | Value | Method: | Notes |
|---|--|---------|-------|
| Physical state: | Liquid | -- | -- |
| Colour: | Colourless | -- | -- |
| Odour: | de solvant/ solvent-like | -- | -- |
| Melting point/freezing point: | Not Relevant | -- | -- |
| Boiling point or initial boiling point and boiling range: | >36°C | -- | -- |
| Flammability: | Flam. Liq. 3, H226 | -- | -- |
| Lower and upper explosion limit: | N.A. | -- | -- |
| Flash point (°C): | ~23°C | -- | -- |
| Auto-ignition temperature: | N.A. | -- | -- |
| Decomposition temperature: | N.A. | -- | -- |
| pH: | Not Relevant | -- | -- |
| Kinematic viscosity: | <= 20,5 mm ² / sec (40 °C) | -- | -- |
| Solubility in water: | immiscible | -- | -- |

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

DILUANT DL 108

| | | | |
|--|-----------------------------------|----|----|
| Solubility in oil: | N.A. | -- | -- |
| Partition coefficient n-octanol/water (log value): | N.A. | -- | -- |
| Vapour pressure: | <1.000 hPa (50°C) | -- | -- |
| Density and/or relative density: | ~0.87 g/cm ³ (23°C) | -- | -- |
| Relative vapour density: | N.A. | -- | -- |
| Particle characteristics: | | | |
| Particle size: | N.A. | -- | -- |

9.2. Other information

| Properties | Value | Method: | Notes |
|------------|--------------------------|---------|-------|
| Viscosity: | <20.4 mm ² /s | -- | -- |

Volatile Organic compounds - VOCs = 100 %

N.A. = not available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

Strong oxidizers.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological information of the product:

DILUANT DL 108

Acute toxicity

The product is classified: Acute Tox. 4 H312; Acute Tox. 4 H332

ATEmix - Dermal 1342,99 mg/kg bw

ATEmix - Inhalation (Vapours) 11,1916 mg/l

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))
DILUANT DL 108

Skin corrosion/irritation

The product is classified: Skin Irrit. 2 H315

Serious eye damage/irritation

The product is classified: Eye Irrit. 2 H319

Respiratory or skin sensitisation

Not classified

Based on available data, the classification criteria are not met

Germ cell mutagenicity

Not classified

Based on available data, the classification criteria are not met

Carcinogenicity

Not classified

Based on available data, the classification criteria are not met

Reproductive toxicity

Not classified

Based on available data, the classification criteria are not met

STOT-single exposure

The product is classified: STOT SE 3 H335

STOT-repeated exposure

The product is classified: STOT RE 2 H373

Aspiration hazard

The product is classified: Asp. Tox. 1 H304

Toxicological information of the main substances found in the product:

reaction mass of ethylbenzene and xylene - CAS: 1330-20-7

Acute toxicity

ATE - Dermal 1100 mg/kg bw

ATE - Inhalation (Vapours) 11 mg/l

Test: LD50 - Route: Skin = 1100 mg/kg

Test: LC50 - Route: Inhalation Vapour = 11 mg/l

Carcinogenicity:

Test: NOAEL - Route: Oral - Species: Rat > 500 mg/kg bw/day

Reproductive toxicity:

Test: NOAEC - Route: Inhalation - Species: Rat = 500 ppm - Notes: fertilité/fertility

Test: NOAEC - Route: Inhalation - Species: Rat = 100 ppm - Notes:
développement/development

Aspiration hazard:

= 0.812 cP - Notes: @20°C

ethylbenzene - CAS: 100-41-4

Acute toxicity

ATE - Inhalation (Vapours) 11 mg/l

Test: LD50 - Route: Skin - Species: Rabbit = 4100 mg/kg

Test: LD50 - Route: Oral - Species: Rat = 3500 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 20 mg/l - Duration: 4h

Test: LCL0 - Route: Inhalation - Species: Rat = 4000 ppm - Duration: 4h

toluene - CAS: 108-88-3

**Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))
DILUANT DL 108**

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 5580 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

Test: LC50 - Route: Inhalation Vapour - Species: Rat = 28.1 mg/l - Duration: 4h

11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration $\geq 0.1\%$

Other toxicological information:

reaction mass of ethylbenzene and xylene

Skin contact:

Irritating effect

Ingestion:

Ingestion may cause irritation of the digestive tract, nausea, vomiting and diarrhea, abdominal pain.

Harmful by inhalation.

-

toluene

Skin contact:

Irritating effect

Eye contact:

Irritating effect

Inhalation of high concentration of vapours may cause irritation of the respiratory system.

Inhalation of high concentration vapours causes a narcotic reaction on the central nervous system, and severe lung damage.

Ingestion may cause irritation of the digestive tract, nausea, vomiting and diarrhea, abdominal pain.

Risk of central nervous system depression.

SECTION 12: Ecological information**12.1. Toxicity**

Adopt good working practices, so that the product is not released into the environment.

DILUANT DL 108

The product is classified: Aquatic Chronic 3 - H412

reaction mass of ethylbenzene and xylene - CAS: 1330-20-7

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 2.6 mg/l - Duration h: 96 - Notes: Oncorhynchus mykiss

Endpoint: IC50 - Species: Aquatic invertebrates = 1 mg/kg/d - Duration h: 24 - Notes: Daphnia magna

Endpoint: EC50 - Species: Aquatic plants = 2.2 mg/l - Duration h: 73 - Notes: Pseudokirchneriella subcapitata

Endpoint: NOEC - Species: activated sludge = 157 mg/l - Duration h: 3

Endpoint: NOEC - Species: Fish > 1.3 mg/l - Duration h: 1344 - Notes: Oncorhynchus mykiss

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

DILUANT DL 108

Endpoint: NOAEL - Species: Aquatic invertebrates = 1.17 mg/l - Duration h: 168 - Notes: Ceriodaphnia dubia

ethylbenzene - CAS: 100-41-4

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia > 1.37 mg/l - Duration h: 48

Endpoint: EC50 - Species: Daphnia < 4.4 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish = 4.2 mg/l - Duration h: 96 - Notes: Oncorhynchus mykiss

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Fish > 1 mg/l

toluene - CAS: 108-88-3

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae = 134 mg/l - Duration h: 3 - Notes: Chlorella vulgaris

Endpoint: EC50 - Species: Daphnia = 3.78 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish = 5.5 mg/l - Duration h: 96 - Notes: Oncorhynchus kisutch

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 0.74 mg/l - Duration h: 168 - Notes: Ceriodaphnia dubia

Endpoint: NOEC - Species: Algae = 10 mg/l - Duration h: 72 - Notes: Skeletonema costatum

Endpoint: EC50 - Species: Daphnia = 3.23 mg/l - Duration h: 168 - Notes: Ceriodaphnia dubia

Endpoint: LOEC

- Species: Daphnia = 2.76 mg/kg/d - Duration h: 168 - Notes: Ceriodaphnia dubia

Endpoint: NOEC - Species: Fish = 1.39 mg/l - Duration h: 960 - Notes: Oncorhynchus kisutch

Endpoint: LOEC

- Species: Fish = 2.77 mg/l - Duration h: 960 - Notes: Oncorhynchus kisutch

c) Bacteria toxicity:

Endpoint: NOEC - Species: bacteria = 29 mg/l - Duration h: 16 - Notes: pseudomonas putida

12.2. Persistence and degradability

toluene - CAS: 108-88-3

Biodegradability: Readily biodegradable - Duration: 14 days - %: 100

12.3. Bioaccumulative potential

ethylbenzene - CAS: 100-41-4

Log Kow 3.15

toluene - CAS: 108-88-3

BCF 90

Log Pow 2.65

12.4. Mobility in soil

reaction mass of ethylbenzene and xylene - CAS: 1330-20-7

Log Koc 2.73 - Notes: @20-25°C

Volality (H: Henry's Law Constant) 623-665 Pa m³/mol - Notes: @25°C

Surface tension 29.76 mN/m - Notes: @25°C

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration >= 0.1%

12.7. Other adverse effects

No harmful effects expected.

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

DILUANT DL 108

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

Codes of wastes (Décision 2001/573/EC, Directive 2006/12/EEC, Directive 94/31/EEC on hazardous waste):

14 06 03* Other solvents and solvent mixtures

SECTION 14: Transport information



14.1. UN number or ID number

| | |
|-----------------|------|
| ADR-UN Number: | 1263 |
| IATA-UN Number: | 1263 |
| IMDG-UN Number: | 1263 |

14.2. UN proper shipping name

| | |
|---------------------|------------------------|
| ADR-Shipping Name: | PAINT RELATED MATERIAL |
| IATA-Shipping Name: | PAINT RELATED MATERIAL |
| IMDG-Shipping Name: | PAINT RELATED MATERIAL |

14.3. Transport hazard class(es)

| | |
|-------------------------------------|----|
| ADR-Class: | 3 |
| ADR - Hazard identification number: | 30 |
| IATA-Class: | 3 |
| IATA-Label: | 3 |
| IMDG-Class: | 3 |

14.4. Packing group

| | |
|---------------------|-----|
| ADR-Packing Group: | III |
| IATA-Packing group: | III |
| IMDG-Packing group: | III |

14.5. Environmental hazards

| | |
|------------------------------|------------------|
| ADR-Environmental Pollutant: | No |
| IMDG-Marine pollutant: | No |
| IMDG-EmS: | F-E , <u>S-E</u> |

14.6. Special precautions for user

| | |
|---|-------------|
| ADR-Subsidiary hazards: | - |
| ADR-S.P.: | 163 367 650 |
| ADR-Transport category (Tunnel restriction code): | 3 (D/E) |
| IATA-Passenger Aircraft: | 355 |
| IATA-Subsidiary hazards: | - |
| IATA-Cargo Aircraft: | 366 |
| IATA-S.P.: | A3 A72 A192 |
| IATA-ERG: | 3L |
| IMDG-Subsidiary hazards: | - |
| IMDG-Stowage and handling: | Category A |
| IMDG-Segregation: | - |
| Q.L.: | 5L |

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))
DILUANT DL 108

Q.E.: E1

14.7. Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Regulation (EU) n. 2021/849 (ATP 17 CLP)

Regulation (EU) n. 2022/692 (ATP 18 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restriction 40

Restrictions related to the substances contained:

Restriction 48

Restriction 75

Listed or in compliance with the following international inventories:

Labelling of detergents (EC Regulations 648/2004 and 907/2006):

N.A.

Labelling of biocides (Regulations 1896/2000, 1687/2002, 2032/2003, 1048/2005, 1849/2006,

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))
DILUANT DL 108

1451/2007 and Directive 98/8/EC):

N.A.

N.A.

Where applicable, refer to the following regulatory provisions :

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments.

1999/13/EC (VOC directive)

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

Product belongs to category: P5c

15.2. Chemical safety assessment

No

SECTION 16: Other information

N.A.: Not Applicable or Not Available

Full text of phrases referred to in Section 3:

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

H225 Highly flammable liquid and vapour.

H373 (hearing organs) May cause damage to organs (hearing organs) through prolonged or repeated exposure.

H361d Suspected of damaging the unborn child.

H336 May cause drowsiness or dizziness.

H350 May cause cancer.

H411 Toxic to aquatic life with long lasting effects.

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

DILUANT DL 108

| Hazard class and hazard category | Code | Description |
|----------------------------------|--------------|--|
| Flam. Liq. 2 | 2.6/2 | Flammable liquid, Category 2 |
| Flam. Liq. 3 | 2.6/3 | Flammable liquid, Category 3 |
| Acute Tox. 4 | 3.1/4/Dermal | Acute toxicity (dermal), Category 4 |
| Acute Tox. 4 | 3.1/4/Inhal | Acute toxicity (inhalation), Category 4 |
| Asp. Tox. 1 | 3.10/1 | Aspiration hazard, Category 1 |
| Skin Irrit. 2 | 3.2/2 | Skin irritation, Category 2 |
| Eye Irrit. 2 | 3.3/2 | Eye irritation, Category 2 |
| Carc. 1B | 3.6/1B | Carcinogenicity, Category 1B |
| Repr. 2 | 3.7/2 | Reproductive toxicity, Category 2 |
| STOT SE 3 | 3.8/3 | Specific target organ toxicity - single exposure, Category 3 |
| STOT RE 2 | 3.9/2 | Specific target organ toxicity - repeated exposure, Category 2 |
| Aquatic Chronic 2 | 4.1/C2 | Chronic (long term) aquatic hazard, category 2 |
| Aquatic Chronic 3 | 4.1/C3 | Chronic (long term) aquatic hazard, category 3 |

This safety data sheet has been completely updated in compliance to Regulation 2020/878. Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

| Classification according to Regulation (EC) Nr. 1272/2008 | Classification procedure |
|---|--------------------------|
| Flam. Liq. 3, H226 | On basis of test data |
| Acute Tox. 4, H312 | Calculation method |
| Acute Tox. 4, H332 | Calculation method |
| Skin Irrit. 2, H315 | Calculation method |
| Eye Irrit. 2, H319 | Calculation method |
| STOT SE 3, H335 | Calculation method |

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

DILUANT DL 108

| | |
|-------------------------|--------------------|
| STOT RE 2, H373 | Calculation method |
| Asp. Tox. 1, H304 | Calculation method |
| Aquatic Chronic 3, H412 | Calculation method |

Due to the integration of the Mader Aero products range into the Socomore Group, all Safety Data Sheets have been re-evaluated on the basis of consolidated information. This may have led to significant changes in our Safety Data Sheets. If you have any questions regarding these changes, you can contact us at the address indicated in section 1.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,
Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van
Nostrand Reinold

CCNL - Appendix 1

Insert further consulted bibliography

Important confidentiality : this document contains confidential information that is proprietary to SOCOMORE. Subject to legal provisions determining otherwise, the distribution, republication or re-transmission of this document, in full or in part, must be limited to clearly identified individuals, either because they use the product, or to provide HSE information. Any communication of this document outside of this framework without our written consent is strictly forbidden.

SOCOMORE strongly advises every recipient of this safety data sheet to read it carefully and to consult experts in the field if necessary or appropriate, in order to understand the information it contains, notably the possible dangers associated with this product. The users must ensure the conformity and completeness of this information with regards to their specific use of the product.

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the responsibility of the purchaser/user to ensure that their activities conform with current legislation in force.

The information is considered correct, but it is not exhaustive and it shall be used only as a guide which is based on the current knowledge of the substance or mixture and it is applicable to the safety precautions appropriate for the product.

| | |
|-------------|--|
| ADR: | European Agreement concerning the International Carriage of Dangerous Goods by Road. |
| ATE: | Acute Toxicity Estimate |
| ATEmix: | Acute toxicity Estimate (Mixtures) |
| CAS: | Chemical Abstracts Service (division of the American Chemical Society). |
| CLP: | Classification, Labeling, Packaging. |
| DNEL: | Derived No Effect Level. |
| EINECS: | European Inventory of Existing Commercial Chemical Substances. |
| GefStoffVO: | Ordinance on Hazardous Substances, Germany. |

**Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))
DILUANT DL 108**

| | |
|-----------|---|
| GHS: | Globally Harmonized System of Classification and Labeling of Chemicals. |
| IATA: | International Air Transport Association. |
| IATA-DGR: | Dangerous Goods Regulation by the "International Air Transport Association" (IATA). |
| ICAO: | International Civil Aviation Organization. |
| ICAO-TI: | Technical Instructions by the "International Civil Aviation Organization" (ICAO). |
| IMDG: | International Maritime Code for Dangerous Goods. |
| INCI: | International Nomenclature of Cosmetic Ingredients. |
| KSt: | Explosion coefficient. |
| LC50: | Lethal concentration, for 50 percent of test population. |
| LD50: | Lethal dose, for 50 percent of test population. |
| LTE: | Long-term exposure. |
| PNEC: | Predicted No Effect Concentration. |
| RID: | Regulation Concerning the International Transport of Dangerous Goods by Rail. |
| STE: | Short-term exposure. |
| STEL: | Short Term Exposure limit. |
| STOT: | Specific Target Organ Toxicity. |
| STOT SE: | May cause drowsiness or dizziness |
| TLV: | Threshold Limiting Value. |
| TWA: | Time-weighted average |
| TWATLV: | Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard). |
| WGK: | German Water Hazard Class. |