

# Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

## DILUANT DL TD 20

Regulation (EU) n. 2020/878

Safety Data Sheet date: 2/9/2024, version 1

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Trade name: DILUANT DL TD 20  
SDS code: 103258AEU  
UFI: 8UVW-6J6F-NK9M-QMNX

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:  
Industrial uses  
Thinner

#### 1.3. Details of the supplier of the safety data sheet

##### Manufacturers:

Socomore SASU - Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - France  
-Tel. +33 (0)2 97 43 76 90

Manufacturing - Parc Gohelis - 56250 ELVEN France - Tel +33 (0)2 97 43 76 83 - Fax +33 (0)2 97 54 50 26

Socomore Ireland Ltd. - Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922 / Fax +353 21 4889923 / ireland@socomore.com

##### Distributors:

Socomore SASU - Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - France  
-Tel. +33 (0)2 97 43 76 90

Manufacturing - Parc Gohelis - 56250 ELVEN France - Tel +33 (0)2 97 43 76 83 - Fax +33 (0)2 97 54 50 26

Socomore Ireland Ltd. - Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922 / Fax +353 21 4889923 / ireland@socomore.com

##### Competent person responsible for the safety data sheet:

msdsinformation-eu@socomore.com

#### 1.4. Emergency telephone number





France : ORFILA (INRS) +33 (0)1 45 42 59 59  
International : CHEMTEL +1-813-248-0585.

---






### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### EC regulation criteria 1272/2008 (CLP)

-  Warning, Flam. Liq. 3, Flammable liquid and vapour.
-  Warning, Acute Tox. 4, Harmful in contact with skin.
-  Warning, Acute Tox. 4, Harmful if inhaled.
-  Warning, Skin Irrit. 2, Causes skin irritation.

**Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))**  
**DILUANT DL TD 20**

-  Warning, Eye Irrit. 2, Causes serious eye irritation.
-  Warning, STOT SE 3, May cause respiratory irritation.
-  Warning, STOT SE 3, May cause drowsiness or dizziness.
-  Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure.
-  Danger, Asp. Tox. 1, May be fatal if swallowed and enters airways.

Aquatic Chronic 3, Harmful to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

**2.2. Label elements**

Hazard pictograms:



Danger

Hazard statements:

H226 Flammable liquid and vapour.

H312+H332 Harmful in contact with skin or if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P370+P378 In case of fire: Use dry sand, chemical powder or alcohol-resistant foam for extinction.

P403+P235 Store in a well-ventilated place. Keep cool.

Special Provisions:

None

Contains

reaction mass of ethylbenzene and xylene

1-methoxy-2-propanol; monopropylene glycol methyl ether

ethylbenzene

toluene

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

## Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

### DILUANT DL TD 20

#### 2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration  $\geq 0.1\%$




















## SECTION 3: Composition/information on ingredients

#### 3.1. Substances

N.A.










#### 3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

| Qty                         | Name  | Ident. Number   | Classification   |
|-----------------------------|---|---|--|
| $\geq 60\%$ -<br>$< 70\%$   | reaction mass of ethylbenzene and xylene                | CAS: 1330-20-7<br>EC: 905-588-0<br>REACH No.: 01-21194882<br>16-32                              |  2.6/3 Flam. Liq. 3 H226<br> 3.10/1 Asp. Tox. 1 H304<br> 3.1/4/Dermal Acute Tox. 4 H312<br> 3.1/4/Inhal Acute Tox. 4 H332<br> 3.2/2 Skin Irrit. 2 H315<br> 3.3/2 Eye Irrit. 2 H319<br> 3.8/3 STOT SE 3 H335<br> 3.9/2 STOT RE 2 H373<br>4.1/C3 Aquatic Chronic 3 H412<br>Acute Toxicity Estimate:<br>ATE - Dermal 1100 mg/kg bw<br>ATE - Inhalation (Vapours) 11 mg/l |
| $\geq 15\%$ -<br>$< 20\%$   | 1-methoxy-2-propanol; monopropylene glycol methyl ether | Index number: 603-064-00-3<br>CAS: 107-98-2<br>EC: 203-539-1<br>REACH No.: 01-21194574<br>35-35 |  2.6/3 Flam. Liq. 3 H226<br> 3.8/3 STOT SE 3 H336<br>Acute Toxicity Estimate:<br>ATE - Oral 3739 mg/kg bw<br>ATE - Dermal 2001 mg/kg bw<br>ATE - Inhalation (Vapours) 30,02 mg/l   |
| $\geq 12.5\%$ -<br>$< 15\%$ | ethylbenzene  | Index number: 601-023-00-4<br>CAS: 100-41-4<br>EC: 202-849-4<br>REACH No.: 01-21194893<br>70-35 |  2.6/2 Flam. Liq. 2 H225<br> 3.2/2 Skin Irrit. 2 H315<br> 3.3/2 Eye Irrit. 2 H319<br>4.1/C3 Aquatic Chronic 3 H412<br> 3.1/4/Inhal Acute Tox. 4 H332<br> 3.9/2 STOT RE 2 H373 (hearing organs)<br> 3.10/1 Asp. Tox. 1 H304<br>Acute Toxicity Estimate:<br>ATE - Inhalation (Vapours) 11 mg/l   |
| $\geq 1\%$ -<br>$< 3\%$     | toluene   | Index number: 601-021-00-3<br>CAS: 108-88-3<br>EC: 203-625-9                                    |  2.6/2 Flam. Liq. 2 H225<br> 3.7/2 Repr. 2 H361d<br> 3.10/1 Asp. Tox. 1 H304  |

## Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

### DILUANT DL TD 20

|                       |        |   |   |
|-----------------------|--------|---|---|
|                       |        | REACH No.: 01-21194713<br>10-51                             |  3.9/2 STOT RE 2 H373<br> 3.2/2 Skin Irrit. 2 H315<br> 3.8/3 STOT SE 3 H336<br> 4.1/C3 Aquatic Chronic 3 H412   |
| >= 0.001% -<br>< 0.1% | Cumene | Index number: 601-024-00-X<br>CAS: 98-82-8<br>EC: 202-704-5 |  2.6/3 Flam. Liq. 3 H226<br> 3.6/1B Carc. 1B H350<br> 3.10/1 Asp. Tox. 1 H304<br> 3.8/3 STOT SE 3 H335<br> 4.1/C2 Aquatic Chronic 2 H411 |

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap. Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do NOT induce vomiting.

In case of Inhalation:

If breathing is irregular or stopped, administer artificial respiration.

In case of inhalation, consult a doctor immediately and show the packing or label.

### 4.2. Most important symptoms and effects, both acute and delayed

None

### 4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

No particular treatment.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media:

Carbon dioxide (CO<sub>2</sub>)

Dry powder

Foam.

Extinguishing media which must not be used for safety reasons:

High power water jet

### 5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

## Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

### DILUANT DL TD 20

#### 5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

---

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

#### 6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

#### 6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

#### 6.4. Reference to other sections

See also section 8 and 13

---

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, ensure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

#### 7.2. Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Store at ambient temperatures. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

#### 7.3. Specific end use(s)

None in particular

---

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Occupational exposure limit values

## Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

### DILUANT DL TD 20

reaction mass of ethylbenzene and xylene - CAS: 1330-20-7

- OEL Type: National - TWA(8h): 221 mg/m<sup>3</sup>, 50 ppm - STEL: 442 mg/m<sup>3</sup>, 100 ppm - Notes: France VLEC - TMP N° 4Bis, 84
- OEL Type: National - TWA(8h): 440 mg/m<sup>3</sup>, 100 ppm - Notes: Germany - DFG, H
- OEL Type: National - TWA(8h): 220 mg/m<sup>3</sup>, 50 ppm - STEL: 441 mg/m<sup>3</sup>, 100 ppm - Notes: UK (WELs)
- OEL Type: EU - TWA(8h): 221 mg/m<sup>3</sup>, 50 ppm - STEL: 442 mg/m<sup>3</sup>, 100 ppm - Notes: Skin
- OEL Type: ACGIH - TWA(8h): 20 ppm - Notes: A4, BEI - URT and eye irr; hematologic eff; CNS impair
- OEL Type: National - TWA: 435 mg/m<sup>3</sup>, 100 ppm - STEL: 870 mg/m<sup>3</sup>, 200 ppm - Notes: Swiss - SUVA
- OEL Type: National - TWA: 221 mg/m<sup>3</sup>, 50 ppm - STEL(15min (Miw)): 442 mg/m<sup>3</sup>, 100 ppm - Notes: Österreich
- OEL Type: National - TWA: 221 mg/m<sup>3</sup>, 50 ppm - Notes: TWA:Poland

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

- OEL Type: National - TWA(8h): 188 mg/m<sup>3</sup>, 50 ppm - STEL: 375 mg/m<sup>3</sup>, 100 ppm - Behaviour: Binding - Notes: France VLEC - INRS TMP N°84
- OEL Type: National - TWA: 370 mg/m<sup>3</sup>, 100 ppm - Notes: Germany
- OEL Type: National - TWA: 180 mg/m<sup>3</sup> - STEL: 360 mg/m<sup>3</sup> - Notes: Poland
- OEL Type: EU - TWA(8h): 375 mg/m<sup>3</sup>, 100 ppm - STEL: 563 mg/m<sup>3</sup>, 150 ppm - Notes: Skin
- OEL Type: ACGIH - TWA(8h): 50 ppm - STEL: 100 ppm - Notes: A4 - Eye and URT irr
- OEL Type: National - TWA: 187 mg/m<sup>3</sup>, 50 ppm - STEL(15min (Miw)): 187 mg/m<sup>3</sup>, 50 ppm - Notes: Austria
- OEL Type: National - TWA(8h): 375 mg/m<sup>3</sup>, 100 ppm - STEL(15min (Miw)): 560 mg/m<sup>3</sup>, 150 ppm - Notes: United Kingdom - Skin
- OEL Type: National - TWA(8h): 188 mg/m<sup>3</sup>, 50 ppm - STEL: 375 mg/m<sup>3</sup>, 100 ppm - Notes: Canada (Gazette Officielle du Québec, January 4, 2023, Vol. 155, No.1)
- OEL Type: National - TWA: 180 mg/m<sup>3</sup>, 50 ppm - Notes: Norway (skin)
- OEL Type: DOW IHG - TWA: 1.5 ppm - STEL: 4.5 ppm

ethylbenzene - CAS: 100-41-4

- OEL Type: National - TWA(8h): 88.4 mg/m<sup>3</sup>, 20 ppm - Notes: Germany - EU, H
- OEL Type: National - TWA(8h): 88.4 mg/m<sup>3</sup>, 20 ppm - STEL: 442 mg/m<sup>3</sup>, 100 ppm - Notes: France VLEC - TMP N° 84
- OEL Type: National - TWA(8h): 441 mg/m<sup>3</sup>, 100 ppm - STEL: 552 mg/m<sup>3</sup>, 125 ppm - Notes: UK (WELs)
- OEL Type: EU - TWA(8h): 442 mg/m<sup>3</sup>, 100 ppm - STEL: 884 mg/m<sup>3</sup>, 200 ppm - Notes: Skin
- OEL Type: ACGIH - TWA(8h): 20 ppm - Notes: OTO; A3, BEI - URT & eye irr; ototoxicity; kidney eff; CNS impair
- OEL Type: National - STEL: 220 mg/m<sup>3</sup> - Notes: Swiss
- OEL Type: MAK - TWA: 440 mg/m<sup>3</sup>, 100 ppm - STEL(5 min (Mow)): 880 mg/m<sup>3</sup>, 200 ppm - Notes: Osterreich

toluene - CAS: 108-88-3

- OEL Type: National - TWA(8h): 190 mg/m<sup>3</sup> - Notes: Germany - DFG, H, Y
- OEL Type: National - TWA(8h): 76.8 mg/m<sup>3</sup>, 20 ppm - STEL(15min (Miw)): 384 mg/m<sup>3</sup>, 100 ppm - Behaviour: Binding - Notes: France VLEC - TMP N° 4bis, 84 ; peau
- OEL Type: EU - TWA(8h): 192 mg/m<sup>3</sup>, 50 ppm - STEL: 384 mg/m<sup>3</sup>, 100 ppm - Notes: Skin
- OEL Type: National - TWA: 191 mg/m<sup>3</sup>, 50 ppm - STEL: 384 mg/m<sup>3</sup>, 100 ppm - Notes: UK (WELs)

## Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

### DILUANT DL TD 20

- OEL Type: ACGIH - TWA(8h): 20 ppm - Notes: OTO; A4; BEI - CNS, visual & hearing impair; female repro system eff; pregnancy loss
- OEL Type: MAK - TWA: 190 mg/m<sup>3</sup>, 50 ppm - STEL(15min (Miw)): 380 mg/m<sup>3</sup>, 100 ppm - Notes: Osterreich

Cumene - CAS: 98-82-8

- OEL Type: EU - TWA(8h): 50 mg/m<sup>3</sup>, 10 ppm - STEL: 250 mg/m<sup>3</sup>, 50 ppm - Notes: Skin
- OEL Type: ACGIH - TWA(8h): 5 ppm - Notes: A3 - URT adenoma, neurological eff
- OEL Type: National - TWA(8h): 50 mg/m<sup>3</sup>, 10 ppm - STEL(15min (Miw)): 250 mg/m<sup>3</sup>, 50 ppm - Behaviour: Binding - Notes: France, VLEPC / peau
- OEL Type: National - TWA: 50 mg/m<sup>3</sup> - STEL: 250 mg/m<sup>3</sup> - Notes: Poland (Skin / skóra)

#### DNEL Exposure Limit Values

reaction mass of ethylbenzene and xylene - CAS: 1330-20-7

Worker Industry: 77 mg/m<sup>3</sup> - Consumer: 14.8 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Industry: 289 mg/m<sup>3</sup> - Consumer: 174 mg/kg b.w./day - Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Industry: 289 mg/m<sup>3</sup> - Consumer: 174 mg/kg b.w./day - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 180 mg/kg b.w./day - Consumer: 108 mg/kg b.w./day - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Consumer: 1.6 mg/kg b.w./day - Exposure: Human Oral - Frequency: Long Term, systemic effects

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

Worker Industry: 369 mg/m<sup>3</sup> - Consumer: 43.9 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Industry: 50.6 mg/kg b.w./day - Consumer: 18.1 mg/kg b.w./day - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Consumer: 3.3 mg/kg b.w./day - Exposure: Human Oral - Frequency: Long Term, systemic effects

Worker Industry: 553.5 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term (acute)

ethylbenzene - CAS: 100-41-4

Worker Industry: 77 mg/m<sup>3</sup> - Consumer: 15 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

Worker Industry: 180 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 293 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, local effects

toluene - CAS: 108-88-3

Worker Professional: 384 mg/m<sup>3</sup> - Consumer: 226 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Professional: 192 mg/m<sup>3</sup> - Consumer: 56.5 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Professional: 180 mg/kg - Consumer: 226 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Consumer: 8.13 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

Worker Professional: 384 mg/m<sup>3</sup> - Consumer: 226 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, local effects



## Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

### DILUANT DL TD 20

#### PNEC Exposure Limit Values

reaction mass of ethylbenzene and xylene - CAS: 1330-20-7

Target: Fresh Water - Value: 0.327 mg/l

Target: Water (intermittent discharge) - Value: 0.327 mg/l

Target: Marine water - Value: 0.327 mg/l

Target: Sewage treatment plant - Value: 6.58 mg/l

Target: Freshwater sediments - Value: 12.46 mg/kg

Target: Marine water sediments - Value: 12.46 mg/kg

Target: Soil - Value: 2.31 mg/kg

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

Target: Fresh Water - Value: 10 mg/l

Target: Freshwater sediments - Value: 41.6 mg/kg

Target: Marine water sediments - Value: 4.17 mg/kg

Target: Soil (agricultural) - Value: 2.47 mg/kg

Target: Microorganisms in sewage treatments - Value: 100 mg/l

Target: Marine water - Value: 1 mg/l

Target: Water (intermittent discharge) - Value: 100 mg/l

ethylbenzene - CAS: 100-41-4

Target: Marine water - Value: 0.01 mg/l - Notes:: factor assessment : 10

Target: Marine water - Value: 0.1 mg/l - Notes:: factor assessment : 18

Target: PNEC predator - Value: 2.68 mg/kg - Notes:: ECHA

toluene - CAS: 108-88-3

Target: Fresh Water - Value: 0.68 mg/l

Target: Freshwater sediments - Value: 16.39 mg/kg

Target: Soil (agricultural) - Value: 2.89 mg/kg

Target: Microorganisms in sewage treatments - Value: 13.61 mg/l

#### Biological Exposure Index

reaction mass of ethylbenzene and xylene - CAS: 1330-20-7

Remark: ACGIH BEL (2009)

Remark: FR IBE (1997)

#### **8.2. Exposure controls**

See below, example of PPE to use.

##### Eye protection:

Use close fitting safety goggles, don't use eye lens.

##### Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

##### Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

##### Respiratory protection:

Use respiratory protection where ventilation is insufficient or exposure is prolonged.

Use adequate protective respiratory equipment.

##### Thermal Hazards:

None

##### Environmental exposure controls:

None

##### Appropriate engineering controls:

None

##### Other conditions affecting workers exposure:

None



## Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

### DILUANT DL TD 20

#### SECTION 9: Physical and chemical properties

##### 9.1. Information on basic physical and chemical properties

| Properties  | Value                                | Method: | Notes |
|---|--------------------------------------|---------|-------|
| Physical state:   | Liquid                               | --      | --    |
| Colour:   | Colourless                           | --      | --    |
| Odour:  | De solvent/Solvent-like              | --      | --    |
| Melting point/freezing point:                             | Not Relevant                         | --      | --    |
| Boiling point or initial boiling point and boiling range: | >36°C                                | --      | --    |
| Flammability:   | Flam. Liq. 3, H226                   | --      | --    |
| Lower and upper explosion limit:                          | N.A.                                 | --      | --    |
| Flash point (°C):   | ~23°C                                | --      | --    |
| Auto-ignition temperature:                                | N.A.                                 | --      | --    |
| Decomposition temperature:                                | Not Relevant                         | --      | --    |
| pH:   | Not Relevant                         | --      | --    |
| Kinematic viscosity:                                      | <= 20,5 mm <sup>2</sup> /sec (40 °C) | --      | --    |
| Solubility in water:                                      | Immiscible                           | --      | --    |
| Solubility in oil:  | N.A.                                 | --      | --    |
| Partition coefficient n-octanol/water (log value):        | N.A.                                 | --      | --    |
| Vapour pressure:  | <1.000 hPa (50°C)                    | --      | --    |
| Density and/or relative density:                          | ~0.88 g/cm <sup>3</sup> (23°C)       | --      | --    |
| Relative vapour density:                                  | N.A.                                 | --      | --    |
| Particle characteristics:                                 |                                      |         |       |
| Particle size:  | N.A.                                 | --      | --    |

##### 9.2. Other information

| Properties | Value                           | Method: | Notes |
|------------|---------------------------------|---------|-------|
| Viscosity: | <20.4 mm <sup>2</sup> /s (40°C) | --      | --    |

Volatile Organic compounds - VOCs = 100 %

N.A. = not available

#### SECTION 10: Stability and reactivity

##### 10.1. Reactivity

Stable under normal conditions

##### 10.2. Chemical stability

Stable under normal conditions

##### 10.3. Possibility of hazardous reactions

## Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

### DILUANT DL TD 20

None

#### 10.4. Conditions to avoid

Stable under normal conditions.

#### 10.5. Incompatible materials

Strong oxidizers.

#### 10.6. Hazardous decomposition products

None.

---

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological information of the product:

DILUANT DL TD 20

Acute toxicity

The product is classified: Acute Tox. 4 H312; Acute Tox. 4 H332

ATEmix - Dermal 1678,74 mg/kg bw

ATEmix - Inhalation (Vapours) 13,9895 mg/l

Skin corrosion/irritation

The product is classified: Skin Irrit. 2 H315

Serious eye damage/irritation

The product is classified: Eye Irrit. 2 H319

Respiratory or skin sensitisation

Not classified

Based on available data, the classification criteria are not met

Germ cell mutagenicity

Not classified

Based on available data, the classification criteria are not met

Carcinogenicity

Not classified

Based on available data, the classification criteria are not met

Reproductive toxicity

Not classified

Based on available data, the classification criteria are not met

STOT-single exposure

The product is classified: STOT SE 3 H335; STOT SE 3 H336

STOT-repeated exposure

The product is classified: STOT RE 2 H373

Aspiration hazard

The product is classified: Asp. Tox. 1 H304

Toxicological information of the main substances found in the product:

reaction mass of ethylbenzene and xylene - CAS: 1330-20-7

Acute toxicity

ATE - Dermal 1100 mg/kg bw

ATE - Inhalation (Vapours) 11 mg/l

Test: LD50 - Route: Skin = 1100 mg/kg

Test: LC50 - Route: Inhalation Vapour = 11 mg/l

Carcinogenicity:

Test: NOAEL - Route: Oral - Species: Rat > 500 mg/kg bw/day

Reproductive toxicity:

Test: NOAEC - Route: Inhalation - Species: Rat = 500 ppm - Notes: fertilité/fertility

Test: NOAEC - Route: Inhalation - Species: Rat = 100 ppm - Notes:

développement/development

Aspiration hazard:

= 0.812 cP - Notes: @20°C

## Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

### DILUANT DL TD 20

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

Acute toxicity

ATE - Oral 3739 mg/kg bw

ATE - Dermal 2001 mg/kg bw

ATE - Inhalation (Vapours) 30,02 mg/l

Test: LD50 - Route: Oral - Species: Rat (male) = 3739 mg/kg - Source: OECD 401

Test: LD50 - Route: Oral - Species: Rat (female) = 4277 mg/kg - Source: OECD 401

Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 5 mg/l - Duration: 4h

Test: LC50 - Route: Inhalation Vapour - Species: Rat (Male, female) = 30.02 mg/l - Duration: 4h - Source: OECD 403

Test: ATE - Route: Oral = 3739 mg/kg

Test: ATE - Route: Inhalation Vapour = 30.02 mg/l - Duration: 4h

ethylbenzene - CAS: 100-41-4

Acute toxicity

ATE - Inhalation (Vapours) 11 mg/l

Test: LD50 - Route: Skin - Species: Rabbit = 4100 mg/kg

Test: LD50 - Route: Oral - Species: Rat = 3500 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 20 mg/l - Duration: 4h

Test: LCL0 - Route: Inhalation - Species: Rat = 4000 ppm - Duration: 4h

toluene - CAS: 108-88-3

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 5580 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

Test: LC50 - Route: Inhalation Vapour - Species: Rat = 28.1 mg/l - Duration: 4h

#### 11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration  $\geq$  0.1%

Other toxicological information:

reaction mass of ethylbenzene and xylene

Skin contact:

Irritating effect

Ingestion:

Ingestion may cause irritation of the digestive tract, nausea, vomiting and diarrhea, abdominal pain.

Harmful by inhalation.

-

toluene

Skin contact:

Irritating effect

Eye contact:

Irritating effect

Inhalation of high concentration of vapours may cause irritation of the respiratory system.

Inhalation of high concentration vapours causes a narcotic reaction on the central nervous system, and severe lung damage.

Ingestion may cause irritation of the digestive tract, nausea, vomiting and diarrhea, abdominal pain.

Risk of central nervous system depression.

## Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

### DILUANT DL TD 20

#### SECTION 12: Ecological information

##### 12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

DILUANT DL TD 20

The product is classified: Aquatic Chronic 3 - H412

reaction mass of ethylbenzene and xylene - CAS: 1330-20-7

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 2.6 mg/l - Duration h: 96 - Notes: Oncorhynchus mykiss

Endpoint: IC50 - Species: Aquatic invertebrates = 1 mg/kg/d - Duration h: 24 - Notes: Daphnia magna

Endpoint: EC50 - Species: Aquatic plants = 2.2 mg/l - Duration h: 73 - Notes:

Pseudokirchneriella subcapitata

Endpoint: NOEC - Species: activated sludge = 157 mg/l - Duration h: 3

Endpoint: NOEC - Species: Fish > 1.3 mg/l - Duration h: 1344 - Notes: Oncorhynchus mykiss

Endpoint: NOAEL - Species: Aquatic invertebrates = 1.17 mg/l - Duration h: 168 - Notes: Ceriodaphnia dubia

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 1000 mg/l - Duration h: 96 - Notes: Leuciscus idus, LC/EC/IC50

Endpoint: LC50 - Species: Daphnia > 1000 mg/l - Duration h: 48 - Notes: LC/EC/IC50

Endpoint: LC50 - Species: Algae > 1000 mg/l - Notes: LC/EC/IC50

Endpoint: LC50 - Species: Fish < 4600 mg/l - Duration h: 96 - Notes: Leuciscus idus

ethylbenzene - CAS: 100-41-4

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia > 1.37 mg/l - Duration h: 48

Endpoint: EC50 - Species: Daphnia < 4.4 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish = 4.2 mg/l - Duration h: 96 - Notes: Oncorhynchus mykiss

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Fish > 1 mg/l

toluene - CAS: 108-88-3

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae = 134 mg/l - Duration h: 3 - Notes: Chlorella vulgaris

Endpoint: EC50 - Species: Daphnia = 3.78 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish = 5.5 mg/l - Duration h: 96 - Notes: Oncorhynchus kisutch

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 0.74 mg/l - Duration h: 168 - Notes: Ceriodaphnia dubia

Endpoint: NOEC - Species: Algae = 10 mg/l - Duration h: 72 - Notes: Skeletonema costatum

Endpoint: EC50 - Species: Daphnia = 3.23 mg/l - Duration h: 168 - Notes: Ceriodaphnia dubia

Endpoint: LOEC

- Species: Daphnia = 2.76 mg/kg/d - Duration h: 168 - Notes: Ceriodaphnia dubia

Endpoint: NOEC - Species: Fish = 1.39 mg/l - Duration h: 960 - Notes: Oncorhynchus kisutch

Endpoint: LOEC

- Species: Fish = 2.77 mg/l - Duration h: 960 - Notes: Oncorhynchus kisutch

c) Bacteria toxicity:

Endpoint: NOEC - Species: bacteria = 29 mg/l - Duration h: 16 - Notes: pseudomonas putida

##### 12.2. Persistence and degradability

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

Biodegradability: Readily biodegradable

toluene - CAS: 108-88-3

Biodegradability: Readily biodegradable - Duration: 14 days - %: 100

##### 12.3. Bioaccumulative potential

## Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

### DILUANT DL TD 20

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

Log Pow 0.37

ethylbenzene - CAS: 100-41-4

Log Kow 3.15

toluene - CAS: 108-88-3

BCF 90

Log Pow 2.65

#### 12.4. Mobility in soil

reaction mass of ethylbenzene and xylene - CAS: 1330-20-7

Log Koc 2.73 - Notes: @20-25°C

Volatility (H: Henry's Law Constant) 623-665 Pa m<sup>3</sup>/mol - Notes: @25°C

Surface tension 29.76 mN/m - Notes: @25°C

#### 12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

#### 12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration >= 0.1%

#### 12.7. Other adverse effects

No harmful effects expected.

---

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

Codes of wastes (Décision 2001/573/EC, Directive 2006/12/EEC, Directive 94/31/EEC on hazardous waste):

08 01 11\* wastes of paint and varnish containing organic solvents or other dangerous substances

---

### SECTION 14: Transport information



#### 14.1. UN number or ID number

ADR-UN Number: 1263

IATA-UN Number: 1263

IMDG-UN Number: 1263

#### 14.2. UN proper shipping name

ADR-Shipping Name: PAINT RELATED MATERIAL

IATA-Shipping Name: PAINT RELATED MATERIAL

IMDG-Shipping Name: PAINT RELATED MATERIAL

#### 14.3. Transport hazard class(es)

ADR-Class: 3

ADR - Hazard identification number: 30

IATA-Class: 3

IATA-Label: 3

IMDG-Class: 3

#### 14.4. Packing group

ADR-Packing Group: III

IATA-Packing group: III

IMDG-Packing group: III

#### 14.5. Environmental hazards

## Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

### DILUANT DL TD 20

ADR-Environmental Pollutant: No  
 IMDG-Marine pollutant: No  
 IMDG-EmS: F-E , S-E

#### 14.6. Special precautions for user

ADR-Subsidiary hazards: -  
 ADR-S.P.: 163 367 650  
 ADR-Transport category (Tunnel restriction code): 3 (D/E)  
 IATA-Passenger Aircraft: 355  
 IATA-Subsidiary hazards: -  
 IATA-Cargo Aircraft: 366  
 IATA-S.P.: A3 A72 A192  
 IATA-ERG: 3L  
 IMDG-Subsidiary hazards: -  
 IMDG-Stowage and handling: Category A  
 IMDG-Segregation: -  
 Q.L.: 5L  
 Q.E.: E1

#### 14.7. Maritime transport in bulk according to IMO instruments

N.A.

---

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)  
 Dir. 2000/39/EC (Occupational exposure limit values)  
 Regulation (EC) n. 1907/2006 (REACH)  
 Regulation (EC) n. 1272/2008 (CLP)  
 Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013  
 Regulation (EU) n. 286/2011 (ATP 2 CLP)  
 Regulation (EU) n. 618/2012 (ATP 3 CLP)  
 Regulation (EU) n. 487/2013 (ATP 4 CLP)  
 Regulation (EU) n. 944/2013 (ATP 5 CLP)  
 Regulation (EU) n. 605/2014 (ATP 6 CLP)  
 Regulation (EU) n. 2015/1221 (ATP 7 CLP)  
 Regulation (EU) n. 2016/918 (ATP 8 CLP)  
 Regulation (EU) n. 2016/1179 (ATP 9 CLP)  
 Regulation (EU) n. 2017/776 (ATP 10 CLP)  
 Regulation (EU) n. 2018/669 (ATP 11 CLP)  
 Regulation (EU) n. 2018/1480 (ATP 13 CLP)  
 Regulation (EU) n. 2019/521 (ATP 12 CLP)  
 Regulation (EU) n. 2020/217 (ATP 14 CLP)  
 Regulation (EU) n. 2020/1182 (ATP 15 CLP)  
 Regulation (EU) n. 2021/643 (ATP 16 CLP)  
 Regulation (EU) n. 2021/849 (ATP 17 CLP)  
 Regulation (EU) n. 2022/692 (ATP 18 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3  
 Restriction 40

Restrictions related to the substances contained:

Restriction 30

## Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

### DILUANT DL TD 20

Restriction 48  
Restriction 75

Listed or in compliance with the following international inventories:

Labelling of detergents (EC Regulations 648/2004 and 907/2006):  
N.A.

Labelling of biocides (Regulations 1896/2000, 1687/2002, 2032/2003, 1048/2005, 1849/2006, 1451/2007 and Directive 98/8/EC):  
N.A.

N.A.

Where applicable, refer to the following regulatory provisions :

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments.

1999/13/EC (VOC directive)

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

Product belongs to category: P5c

#### 15.2. Chemical safety assessment

No

---

#### SECTION 16: Other information

N.A.: Not Applicable or Not Available

Full text of phrases referred to in Section 3:

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

H336 May cause drowsiness or dizziness.

H225 Highly flammable liquid and vapour.

H373 (hearing organs) May cause damage to organs (hearing organs) through prolonged or repeated exposure.

H361d Suspected of damaging the unborn child.

H350 May cause cancer.

H411 Toxic to aquatic life with long lasting effects.



## Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

### DILUANT DL TD 20

| Hazard class and hazard category | Code         | Description  |
|----------------------------------|--------------|--|
| Flam. Liq. 2                     | 2.6/2        | Flammable liquid, Category 2                                   |
| Flam. Liq. 3                     | 2.6/3        | Flammable liquid, Category 3                                   |
| Acute Tox. 4                     | 3.1/4/Dermal | Acute toxicity (dermal), Category 4                            |
| Acute Tox. 4                     | 3.1/4/Inhal  | Acute toxicity (inhalation), Category 4                        |
| Asp. Tox. 1                      | 3.10/1       | Aspiration hazard, Category 1                                  |
| Skin Irrit. 2                    | 3.2/2        | Skin irritation, Category 2                                    |
| Eye Irrit. 2                     | 3.3/2        | Eye irritation, Category 2                                     |
| Carc. 1B                         | 3.6/1B       | Carcinogenicity, Category 1B                                   |
| Repr. 2                          | 3.7/2        | Reproductive toxicity, Category 2                              |
| STOT SE 3                        | 3.8/3        | Specific target organ toxicity - single exposure, Category 3   |
| STOT RE 2                        | 3.9/2        | Specific target organ toxicity - repeated exposure, Category 2 |
| Aquatic Chronic 2                | 4.1/C2       | Chronic (long term) aquatic hazard, category 2                 |
| Aquatic Chronic 3                | 4.1/C3       | Chronic (long term) aquatic hazard, category 3                 |

(EC) 1272/2008 [CLP] Yönetmeliğine göre karışımların sınıflandırmasını elde etmek için kullanılan sınıflandırma ve prosedür:

| Classification according to Regulation (EC) Nr. 1272/2008 | Classification procedure |
|---|--------------------------|
| Flam. Liq. 3, H226  | On basis of test data    |
| Acute Tox. 4, H312  | Calculation method       |
| Acute Tox. 4, H332  | Calculation method       |
| Skin Irrit. 2, H315                                       | Calculation method       |
| Eye Irrit. 2, H319  | Calculation method       |
| STOT SE 3, H335   | Calculation method       |
| STOT SE 3, H336   | Calculation method       |
| STOT RE 2, H373   | Calculation method       |
| Asp. Tox. 1, H304   | Calculation method       |
| Aquatic Chronic 3, H412                                   | Calculation method       |

Due to the integration of the Mader Aero products range into the Socomore Group, all Safety Data Sheets have been re-evaluated on the basis of consolidated information. This may have led to significant changes in our Safety Data Sheets. If you have any questions regarding these changes, you can contact us at the address indicated in section 1.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

CCNL - Appendix 1

Insert further consulted bibliography

Important confidentiality : this document contains confidential information that is proprietary to SOCOMORE. Subject to legal provisions determining otherwise, the distribution, republication or re-transmission of this document, in full or in part, must be limited to clearly identified individuals, either because they use the product, or to provide HSE information. Any communication of this document outside of this framework without our written consent is strictly forbidden.

## Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

### DILUANT DL TD 20

SOCOMORE strongly advises every recipient of this safety data sheet to read it carefully and to consult experts in the field if necessary or appropriate, in order to understand the information it contains, notably the possible dangers associated with this product. The users must ensure the conformity and completeness of this information with regards to their specific use of the product. The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the responsibility of the purchaser/user to ensure that their activities conform with current legislation in force.

The information is considered correct, but it is not exhaustive and it shall be used only as a guide which is based on the current knowledge of the substance or mixture and it is applicable to the safety precautions appropriate for the product.

|             |  |
|-------------|--|
| ADR:        | European Agreement concerning the International Carriage of Dangerous Goods by Road. |
| ATE:        | Acute Toxicity Estimate  |
| ATEmix:     | Acute toxicity Estimate (Mixtures)   |
| CAS:        | Chemical Abstracts Service (division of the American Chemical Society).              |
| CLP:        | Classification, Labeling, Packaging.   |
| DNEL:       | Derived No Effect Level.   |
| EINECS:     | European Inventory of Existing Commercial Chemical Substances.                       |
| GefStoffVO: | Ordinance on Hazardous Substances, Germany.  |
| GHS:        | Globally Harmonized System of Classification and Labeling of Chemicals.              |
| IATA:       | International Air Transport Association.   |
| IATA-DGR:   | Dangerous Goods Regulation by the "International Air Transport Association" (IATA).  |
| ICAO:       | International Civil Aviation Organization.   |
| ICAO-TI:    | Technical Instructions by the "International Civil Aviation Organization" (ICAO).    |
| IMDG:       | International Maritime Code for Dangerous Goods.                                     |
| INCI:       | International Nomenclature of Cosmetic Ingredients.                                  |
| KSt:        | Explosion coefficient.   |
| LC50:       | Lethal concentration, for 50 percent of test population.                             |
| LD50:       | Lethal dose, for 50 percent of test population.                                      |
| LTE:        | Long-term exposure.  |
| PNEC:       | Predicted No Effect Concentration.   |
| RID:        | Regulation Concerning the International Transport of Dangerous Goods by Rail.        |
| STE:        | Short-term exposure.   |
| STEL:       | Short Term Exposure limit.   |
| STOT:       | Specific Target Organ Toxicity.  |
| STOT SE:    | May cause drowsiness or dizziness  |
| TLV:        | Threshold Limiting Value.  |
| TWA:        | Time-weighted average  |
| TWATLV:     | Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).    |
| WGK:        | German Water Hazard Class.   |