

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH)), as retained and amended in UK law LFPH 006 VERNIS INCOL BT

Regulation (EU) n. 2020/878

Safety Data Sheet date: 4/11/2024, version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name: LFPH 006 VERNIS INCOL BT

SDS code: 100275EU

UFI: 30GE-MYU3-V994-681A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Industrial uses

Paint/Coating

1.3. Details of the supplier of the safety data sheet

Manufacturers:

Socomore SASU - Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - France -Tel. +33 (0)2 97 43 76 90

Manufacturing - Parc Gohelis - 56250 ELVEN France - Tel +33 (0)2 97 43 76 83 - Fax +33 (0)2 97 54 50 26

Socomore Ireland Ltd. - Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922 / Fax +353 21 4889923 / ireland@socomore.com

Distributors:

Socomore SASU - Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - France -Tel. +33 (0)2 97 43 76 90

Manufacturing - Parc Gohelis - 56250 ELVEN France - Tel +33 (0)2 97 43 76 83 - Fax +33 (0)2 97 54 50 26

Socomore Ireland Ltd. - Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922 / Fax +353 21 4889923 / ireland@socomore.com

Competent person responsible for the safety data sheet:

msdsinformation-eu@socomore.com

1.4. Emergency telephone number

UK NPIS 0344 892 0111

France: ORFILA (INRS) +33 (0)1 45 42 59 59 International: CHEMTEL +1-813-248-0585.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

Amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567

- Warning, Skin Irrit. 2, Causes skin irritation.
- Warning, Eye Irrit. 2, Causes serious eye irritation.
- ◆ Warning, STOT SE 3, May cause respiratory irritation.

Adverse physicochemical, human health and environmental effects:



LFPH 006 VERNIS INCOL BT

No other hazards

2.2. Label elements

Hazard pictograms:



Warning

Hazard statements:

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

Precautionary statements:

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P312 Call a POISON CENTER/doctor/... if you feel unwell.

P337+P313 If eye irritation persists: Get medical advice/attention.

P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

EUH208 Contains formaldehyde. May produce an allergic reaction.

Contains

triethylamine

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification: Amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567

Qty	Name	ldent. Number		Classification
>= 5% - < 7%	1-PROPOXY-2- PROPANOL	CAS: EC: REACH No.:	216-372-4	© 2.6/3 Flam. Liq. 3 H226 ① 3.3/2 Eye Irrit. 2 H319
>= 1% -	triethylamine	CAS:	121-44-8	♦ 2.6/2 Flam. Liq. 2 H225



LFPH 006 VERNIS INCOL BT

	LIMIO INCOL D	-		
< 3%		EC: REACH No.:	204-469-4 01- 2119475467 -26	♦ 3.3/1 Eye Dam. 1 H318 ♦ 3.1/4/Oral Acute Tox. 4 H302 ♦ 3.1/3/Dermal Acute Tox. 3 H311 ♦ 3.1/3/Inhal Acute Tox. 3 H331 ♦ 3.2/1A Skin Corr. 1A H314 • 3.8/3 STOT SE 3 H335 Specific Concentration Limits: C >= 1%: STOT SE 3 H335 Acute Toxicity Estimate: ATE - Oral 730 mg/kg bw ATE - Dermal 580 mg/kg bw ATE - Inhalation (Vapours) 7,22 mg/l
>= 0.1% - < 0.25%	(2- Methoxymethylethoxy)- propanol	Index number: CAS: EC: REACH No.:	603_998_97 _1 34590-94-8 252-104-2 01- 2119450011 -60	Substance with a Union workplace exposure limit.
>= 0.001% - < 0.1%	formaldehyde	CAS: EC: REACH No.:	50-00-0 200-001-8 01- 2119488953 -20	 ♦ 3.1/3/Oral Acute Tox. 3 H301 ♦ 3.1/2/Inhal Acute Tox. 2 H330 ♦ 3.1/3/Dermal Acute Tox. 3 H311 ♦ 3.2/1B Skin Corr. 1B H314 ♦ 3.3/1 Eye Dam. 1 H318 ♦ 3.4.2/1A Skin Sens. 1A H317 ♦ 3.5/2 Muta. 2 H341 ♦ 3.6/1B Carc. 1B H350 ♦ 3.8/3 STOT SE 3 H335 Specific Concentration Limits: C >= 25%: Skin Corr. 1B H314 5% <= C < 25%: Skin Irrit. 2 H315 5% <= C < 25%: Eye Irrit. 2 H319 C >= 5%: STOT SE 3 H335 C >= 0,2%: Skin Sens. 1A H317 Acute Toxicity Estimate: ATE - Oral 100 mg/kg bw ATE - Dermal 270 mg/kg bw ATE - Inhalation (Gas) 100 ppmV
>= 0.001% - < 0.1%	methanol	Index number: CAS: EC:	603-001-00-X 67-56-1 200-659-6	 2.6/2 Flam. Liq. 2 H225 3.8/1 STOT SE 1 H370 (eyes, central nervous system) 3.1/3/Oral Acute Tox. 3 H301



LFPH 006 VERNIS INCOL BT

♦ 3.1/3/Dermal Acute Tox. 3 H311
♦ 3.1/3/Inhal Acute Tox. 3 H331
Specific Concentration Limits:
C >= 10%: STOT SE 1 H370
3% <= C < 10%: STOT SE 2 H371
Acute Toxicity Estimate:
ATE - Oral 100 mg/kg bw
ATE - Dermal 300 mg/kg bw
ATE - Inhalation (Vapours) 3 mg/l

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting. Obtain a medical examination.

In case of Inhalation:

In case of inhalation, consult a doctor immediately and show the packing or label.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

No particular treatment.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Extinguishing media which must not be used for safety reasons:

High power water jet

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.



LFPH 006 VERNIS INCOL BT

5.3. Advice for firefighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, ensure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contamined clothing should be changed before entering eating areas.

Do not eat or drink while working.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

Keep away from frost.

Product should be stored at above freezing conditions.(>0°C)

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values



LFPH 006 VERNIS INCOL BT

1-PROPOXY-2-PROPANOL - CAS: 1569-01-3

- OEL Type: ACGIH - TWA: 25 ppm

triethylamine - CAS: 121-44-8

- OEL Type: EU TWA(8h): 8.4 mg/m3, 2 ppm STEL: 12.6 mg/m3, 3 ppm Notes: Skin
- OEL Type: ACGIH TWA(8h): 0.5 ppm STEL: 1 ppm Notes: Skin, A4 Visual impair, URT irr
- OEL Type: National TWA: 4.2 mg/m3, 1 ppm STEL: 12.6 mg/m3, 1 ppm Behaviour: Binding Notes: France

(2-Methoxymethylethoxy)-propanol - CAS: 34590-94-8

- OEL Type: National TWA(8h): 310 mg/m3 Notes: Germany Notes DFG, EU
- OEL Type: National TWA(8h): 308 mg/m3, 50 ppm Behaviour: Binding Notes: France VLEC TMP N° 84 (peau)
- OEL Type: EU TWA(8h): 308 mg/m3, 50 ppm Notes: Skin
- OEL Type: National TWA: 270 mg/m3 STEL: 550 mg/m3 Notes: Czech Republic
- OEL Type: ACGIH TWA(8h): 50 ppm Notes: Liver & CNS eff
- OEL Type: National TWA(8h): 308 mg/m3, 50 ppm Notes: UK Skin
- OEL Type: National TWA: 307 mg/m3, 50 ppm STEL(5 min (Mow)): 614 mg/m3, 100 ppm Notes: Österreich
- OEL Type: National TWA: 308 mg/m3, 50 ppm Notes: TWA Poland
- OEL Type: National TWA: 240 mg/m3 STEL: 480 mg/m3 Notes: Poland (NDS, NDSCh)

formaldehyde - CAS: 50-00-0

- OEL Type: EU TWA(8h): 0,37 mg/m3, 0,3 ppm STEL: 0,74 mg/m3, 0,6 ppm Notes: Dermal sensitisation
- OEL Type: ACGIH TWA(8h): 0.1 ppm STEL: 0.3 ppm Notes: DSEN, RSEN, A1 URT and eye irr, URT cancer
- OEL Type: National TWA(8h): 0.37 mg/m3, 0.3 ppm STEL(15'): 0.74 mg/m3, 0.6 ppm
- Notes: France (INRS)

methanol - CAS: 67-56-1

- OEL Type: National TWA(8h): 260 mg/m3, 200 ppm STEL: 1300 mg/m3, 1000 ppm Notes: France VLEC
- OEL Type: EU TWA(8h): 260 mg/m3, 200 ppm Notes: Skin
- OEL Type: ACGIH TWA(8h): 200 ppm STEL: 250 ppm Notes: Skin, BEI Headache, eye dam, dizziness, nausea
- OEL Type: TWA TWA: 200 ppm

DNEL Exposure Limit Values

1-PROPOXY-2-PROPANOL - CAS: 1569-01-3

Worker Industry: 217 mg/m3 - Consumer: 26 mg/m3 - Exposure: Human Inhalation -

Frequency: Long Term, systemic effects

Consumer: 2.2 mg/kg b.w./day - Exposure: Human Oral - Frequency: Long Term, systemic effects

triethylamine - CAS: 121-44-8

Worker Industry: 8.4 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

(2-Methoxymethylethoxy)-propanol - CAS: 34590-94-8



LFPH 006 VERNIS INCOL BT

Worker Industry: 65 mg/kg b.w./day - Consumer: 15 mg/kg b.w./day - Exposure: Human

Dermal - Frequency: Long Term, systemic effects

Worker Industry: 310 mg/m3 - Consumer: 37.2 mg/m3 - Exposure: Human Inhalation -

Frequency: Long Term, systemic effects

Consumer: 1.67 mg/kg b.w./day - Exposure: Human Oral - Frequency: Long Term,

systemic effects

formaldehyde - CAS: 50-00-0

Worker Industry: 9 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term,

systemic effects

Worker Industry: 0.375 mg/m3 - Consumer: 0.1 mg/m3 - Exposure: Human Inhalation -

Frequency: Long Term, local effects

Worker Industry: 240 mg/kg b.w./day - Consumer: 102 mg/kg b.w./day - Exposure: Human

Dermal - Frequency: Long Term, systemic effects

Worker Industry: 0.75 mg/m3 - Exposure: Human Inhalation - Frequency: Short Term, local

effects

Consumer: 4.1 mg/kg b.w./day - Exposure: Human Oral - Frequency: Long Term, systemic

effects

Worker Industry: 0.037 mg/cm2 - Consumer: 0.012 mg/cm2 - Exposure: Human Dermal -

Frequency: Long Term, local effects

methanol - CAS: 67-56-1

Worker Industry: 40 mg/kg b.w./day - Consumer: 8 mg/kg b.w./day - Exposure: Human

Dermal - Frequency: Short Term, systemic effects

Worker Industry: 40 mg/kg b.w./day - Consumer: 8 mg/kg b.w./day - Exposure: Human

Dermal - Frequency: Long Term, systemic effects

Worker Industry: 260 mg/m3 - Exposure: Human Inhalation - Frequency: Short Term,

systemic effects

Worker Industry: 260 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, local

effects

Worker Industry: 260 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term,

systemic effects

PNEC Exposure Limit Values

1-PROPOXY-2-PROPANOL - CAS: 1569-01-3

Target: Fresh Water - Value: 0.1 mg/l Target: Marine water - Value: 0.01 mg/l

Target: Microorganisms in sewage treatments - Value: 4 mg/l

Target: Freshwater sediments - Value: 0.386 mg/l - Notes:: mg/kg p.s. Target: Marine water sediments - Value: 0.0386 mg/kg - Notes:: mg/kg p.s.

Target: Soil (agricultural) - Value: 0.0185 mg/kg - Notes:: mg/kg p.s.

Target: PNEC intermittent - Value: 1 mg/l

triethylamine - CAS: 121-44-8

Target: Fresh Water - Value: 0.064 mg/l

Target: Freshwater sediments - Value: 0.1992 mg/kg

Target: Marine water - Value: 0.0064 mg/l

Target: Sewage treatment plant - Value: 100 mg/l

Target: Soil - Value: 2.361 mg/kg



LFPH 006 VERNIS INCOL BT

Target: Intermittent discharge - Value: 0.064 mg/l (2-Methoxymethylethoxy)-propanol - CAS: 34590-94-8

Target: Fresh Water - Value: 19 mg/l Target: Marine water - Value: 1.9 mg/l

Target: Microorganisms in sewage treatments - Value: 4168 mg/l
Target: Freshwater sediments - Value: 70.2 mg/kg - Notes:: mg/kg p.s.
Target: Marine water sediments - Value: 7.02 mg/kg - Notes:: mg/kg p.s.

Target: Soil (agricultural) - Value: 2.74 mg/kg - Notes:: mg/kg p.s.

Target: Water (intermittent discharge) - Value: 190 mg/l

formaldehyde - CAS: 50-00-0

Target: Fresh Water - Value: 0.44 mg/l Target: Marine water - Value: 0.44 mg/l

Target: Intermittent discharge - Value: 4.44 mg/l Target: Sewage treatment plant - Value: 0.19 mg/l Target: Freshwater sediments - Value: 2.3 mg/kg Target: Marine water sediments - Value: 2.3 mg/kg

Target: Soil - Value: 0.2 mg/kg

methanol - CAS: 67-56-1

Target: Fresh Water - Value: 20.8 mg/l Target: Marine water - Value: 2.08 mg/l

Target: Freshwater sediments - Value: 77 mg/kg Target: Marine water sediments - Value: 7.7 mg/kg Target: Soil (agricultural) - Value: 3.18 mg/kg

Target: Microorganisms in sewage treatments - Value: 100 mg/l

Biological Exposure Index

N.A.

8.2. Exposure controls

See below, example of PPE to use.

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton. Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber. Respiratory protection:

Use respiratory protection where ventilation is insufficient or exposure is prolonged.

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

Other conditions affecting workers exposure:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties



LFPH 006 VERNIS INCOL BT

Properties	Value	Method:	Notes
Physical state:	Liquid		
Colour:	Colourless		
Odour:	inodore/ odorless		
Melting point/freezing point:	Not Relevant		
Boiling point or initial boiling point and boiling range:	>36°C		
Flammability:	N.A.		
Lower and upper explosion limit:	N.A.		
Flash point (°C):	>94°C		
Auto-ignition temperature:	N.A.		
Decomposition temperature:	Not Relevant		
pH:	7		
Kinematic viscosity:	> 20,5 mm2/ sec (40 °C)		
Solubility in water:	miscible		
Solubility in oil:	N.A.		
Partition coefficient n-octanol/water (log value):	N.A.		
Vapour pressure:	<1.000 hPa(50°C)		
Density and/or relative density:	~1.06 g/cm3 (23°C)		
Relative vapour density:	N.A.		
Particle characteristics:			
Particle size:	N.A.		



Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH)), as retained and amended in UK law LFPH 006 VERNIS INCOL BT

9.2. Other information

Properties	Value	Method:	Notes
Viscosity:	>20.6 mm2/s (40°C)		

Volatile Organic compounds - VOCs = 5.53 % Volatile Organic compounds - VOCs = 58.62 g/l

N.A. = not available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

Strong oxidizers.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological information of the product:

LFPH 006 VERNIS INCOL BT

Acute toxicity

Not classified

Based on available data, the classification criteria are not met

ATEmix - Oral 22824,2 mg/kg bw

ATEmix - Dermal 13694,5 mg/kg bw

ATEmix - Inhalation (Vapours) 136,945 mg/l

Skin corrosion/irritation

The product is classified: Skin Irrit. 2 H315

Serious eye damage/irritation

The product is classified: Eye Irrit. 2 H319

Respiratory or skin sensitisation

Not classified

Based on available data, the classification criteria are not met

Germ cell mutagenicity

Not classified

Based on available data, the classification criteria are not met

Carcinogenicity



LFPH 006 VERNIS INCOL BT

Not classified

Based on available data, the classification criteria are not met

Reproductive toxicity

Not classified

Based on available data, the classification criteria are not met

STOT-single exposure

The product is classified: STOT SE 3 H335

STOT-repeated exposure

Not classified

Based on available data, the classification criteria are not met

Aspiration hazard

Not classified

Based on available data, the classification criteria are not met

Toxicological information of the main substances found in the product:

1-PROPOXY-2-PROPANOL - CAS: 1569-01-3

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg

Test: LC50 - Route: Inhalation Vapour - Species: Rat = 8.34 mg/l - Duration: 4h

Respiratory or skin sensitisation:

Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg

triethylamine - CAS: 121-44-8

Acute toxicity

ATE - Oral 730 mg/kg bw

ATE - Dermal 580 mg/kg bw

ATE - Inhalation (Vapours) 7,22 mg/l

Test: LD50 - Route: Oral - Species: Rat (Male, female) = 730 mg/kg - Source: OECD 401

Test: LD50 - Route: Skin - Species: Rabbit (male) = 580 mg/kg - Source: OECD 402

Test: LC50 - Route: Inhalation - Species: Rat (Male, female) = 7.22 mg/l - Duration: 4h -

Source: OECD 403

Test: ATE - Route: Oral = 730 mg/kg

Test: ATE - Route: Skin = 580 mg/kg

Test: ATE - Route: Inhalation = 7.22 mg/l

(2-Methoxymethylethoxy)-propanol - CAS: 34590-94-8

Acute toxicity

ATE - Oral 5001 mg/kg bw

ATE - Dermal 9510 mg/kg bw

ATE - Inhalation (Vapours) 3,35 mg/l

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit = 9510 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 3350 mg/m3 - Notes: aerosol, 7h

Test: ATE - Route: Oral > 5000 mg/kg

Test: ATE - Route: Inhalation Vapour = 3.35 mg/l - Duration: 7h

Test: ATE - Route: Skin = 9510 mg/kg

formaldehyde - CAS: 50-00-0

Acute toxicity



LFPH 006 VERNIS INCOL BT

ATE - Oral 100 mg/kg bw

ATE - Dermal 270 mg/kg bw

ATE - Inhalation (Gas) 100 ppmV

Test: ATE - Route: Oral = 100 mg/kg

Test: ATE - Route: Inhalation Gas = 100 ppm - Duration: 4h

Test: ATE - Route: Skin = 270 mg/kg

STOT-repeated exposure:

Test: NOAEL - Route: Inhalation Vapour - Species: Rat = 1.06 mg/l - Duration: 90 Jours

Test: NOAEL - Route: Inhalation Gas - Species: Rat = 6 ppm - Duration: 28 days

Test: LOAEL

- Route: Inhalation Gas - Species: Rat = 10 ppm - Duration: 28 days

methanol - CAS: 67-56-1

Acute toxicity

ATE - Oral 100 mg/kg bw

ATE - Dermal 300 mg/kg bw

ATE - Inhalation (Vapours) 3 mg/l

Test: ATE - Route: Oral = 100 mg/kg

Test: ATE - Route: Inhalation Vapour = 3 mg/l - Duration: 4h

Test: ATE - Route: Skin = 300 mg/kg

Test: LD50 - Route: Oral - Species: Rat = 100 mg/kg Test: LD50 - Route: Skin - Species: Rat = 300 mg/kg

Test: LC50 - Route: Inhalation Vapour - Species: Rat = 3 mg/l - Duration: 4h

11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration >= 0.1%

Other toxicological information:

1-PROPOXY-2-PROPANOL

May cause moderate eye irritation.

Skin contact:

Prolonged contact may cause irritation.

Repeated-dose toxicity:

Eyes: possible effect on the central nervous system

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

LFPH 006 VERNIS INCOL BT

Not classified for environmental hazards

Based on available data, the classification criteria are not met

1-PROPOXY-2-PROPANOL - CAS: 1569-01-3

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 100 mg/l - Duration h: 96 Endpoint: LC50 - Species: Daphnia > 100 mg/l - Duration h: 48



LFPH 006 VERNIS INCOL BT

Endpoint: EC50 - Species: Algae = 1.466 mg/l - Duration h: 96

c) Bacteria toxicity:

Endpoint: EC50 - Species: bacteria = 3.800 mg/l - Duration h: 16

triethylamine - CAS: 121-44-8

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 24 mg/l - Duration h: 96 - Notes: Oryzias latipes; OECD 203 Endpoint: LC50 - Species: Daphnia = 48 mg/l - Duration h: 48 - Notes: Ceriodaphnia dubia;

OECD 202

Endpoint: EC50r - Species: Algae = 8 mg/l - Duration h: 72 - Notes: Pseudokirchneriella subcapitata; OECD 201

Endpoint: EC50 - Species: bacteria = 95 mg/l - Duration h: 17 - Notes: Pseudomonas putida; DIN 38412, part 8

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 11 mg/l - Duration h: 504 - Notes: Daphnia magna; OECD 211

(2-Methoxymethylethoxy)-propanol - CAS: 34590-94-8

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 1000 mg/l - Duration h: 96 - Notes: Poecilia reticulata Endpoint: LC50 - Species: Daphnia > 1000 mg/l - Duration h: 96 - Notes: Crangon crangon Endpoint: EC50 - Species: Algae > 969 mg/l

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia > 0.5 mg/l - Duration h: 528 - Notes: LOEC: > 0,5 mg/l, 22 days

e) Plant toxicity:

Endpoint: NOEC = 250000 mg/l

formaldehyde - CAS: 50-00-0

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 6.7 mg/l - Duration h: 96

Endpoint: EC50 - Species: Aquatic invertebrates = 5.8 mg/l - Duration h: 48 - Notes: OECD 202, Daphnia pulex

Endpoint: EC50 - Species: Aquatic plants = 4.89 mg/l - Duration h: 72 - Notes: OECD 201, Desmodesmus subspicatus

Endpoint: EC50 - Species: Microorganisms = 34.1 mg/l - Duration h: 120

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Fish >= 48 mg/l - Duration h: 672 - Notes: Oryzias latipes

Endpoint: NOEC - Species: Aquatic invertebrates >= 6.4 mg/l - Duration h: 504 - Notes: OECD 211, Daphnia magna

methanol - CAS: 67-56-1

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 15400 mg/l - Duration h: 96 - Notes: Lepomis macrochirus Endpoint: EC50 - Species: Daphnia > 10000 mg/l - Duration h: 48 - Notes: Daphnia magna Endpoint: EC50 - Species: Algae = 22000 mg/l - Duration h: 96 - Notes: Pseudokirchneriella subcapitata; OECD 201

Endpoint: IC50 - Species: Microorganisms > 1000 mg/l - Duration h: 3

b) Aquatic chronic toxicity:



LFPH 006 VERNIS INCOL BT

Endpoint: NOEC - Species: Fish = 15800 mg/l - Duration h: 200 - Notes: Oryzias latipes

12.2. Persistence and degradability

1-PROPOXY-2-PROPANOL - CAS: 1569-01-3

Biodegradability: Biodegradability rate - Test: OECD 301A - Duration: 28 days - %: 91.5

triethylamine - CAS: 121-44-8

Biodegradability: Readily biodegradable - Test: Aerobic - Duration: 29 days - %: 80.3% - Notes:

OECD 301 B

(2-Methoxymethylethoxy)-propanol - CAS: 34590-94-8

Biodegradability: Biodegradability rate - Test: OECD 301F - Duration: 28 days - %: 75 Biodegradability: Biodegradability rate - Test: OECD 302B - Duration: 13 days - %: 93

formaldehyde - CAS: 50-00-0

Biodegradability: Readily biodegradable - Test: OECD 301C - Duration: 14 days - %: 91%

methanol - CAS: 67-56-1

Biodegradability: Readily biodegradable - Duration: 20 days - %: 95%

12.3. Bioaccumulative potential

1-PROPOXY-2-PROPANOL - CAS: 1569-01-3

BCF < 100

Log Pow 0.621

triethylamine - CAS: 121-44-8

BCF < 0.5 - Duration: 42 days - Notes: Cyprinus carpio; OECD 305 C

(2-Methoxymethylethoxy)-propanol - CAS: 34590-94-8

Log Pow 1.01

BCF < 100

formaldehyde - CAS: 50-00-0

Log Pow 0.35

methanol - CAS: 67-56-1

Log Pow -0.77

12.4. Mobility in soil

1-PROPOXY-2-PROPANOL - CAS: 1569-01-3

Log Koc 1-1,9

Volatility (H: Henry's Law Constant) 3,44*10^-7atm m3/mol - Notes: 25°C

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration >= 0.1%

12.7. Other adverse effects

No harmful effects expected.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force. Codes of wastes (Décision 2001/573/EC, Directive 2006/12/EEC, Directive 94/31/EEC on hazardous waste):

08 01 11* wastes of paint and varnish containing organic solvents or other dangerous substances



LFPH 006 VERNIS INCOL BT

14.1. UN number or ID number

Not classified as dangerous in the meaning of ADR, IATA and IMDG transport regulations.

14.2. UN proper shipping name

N.A.

14.3. Transport hazard class(es)

N.A.

14.4. Packing group

N.A

14.5. Environmental hazards

ADR-Enviromental Pollutant: No IMDG-Marine pollutant: No

14.6. Special precautions for user

N.A.

14.7. Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Regulation (EU) n. 2021/849 (ATP 17 CLP)

Regulation (EU) n. 2022/692 (ATP 18 CLP)

GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:



LFPH 006 VERNIS INCOL BT

Restriction 3

Restrictions related to the substances contained:

Restriction 40

Restriction 69

Restriction 75

Listed or in compliance with the following international inventories:

Labelling of detergents (EC Regulations 648/2004 and 907/2006):

N.A.

Labelling of biocides (Regulations 1896/2000, 1687/2002, 2032/2003, 1048/2005, 1849/2006, 1451/2007 and Directive 98/8/EC):

N.A.

N.A.

Where applicable, refer to the following regulatory provisions :

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments.

1999/13/EC (VOC directive)

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

None

15.2. Chemical safety assessment

No

SECTION 16: Other information

N.A.: Not Applicable or Not Available

Full text of phrases referred to in Section 3:

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

H225 Highly flammable liquid and vapour.

H318 Causes serious eye damage.

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H331 Toxic if inhaled.



LFPH 006 VERNIS INCOL BT

H314 Causes severe skin burns and eye damage.

H335 May cause respiratory irritation.

H301 Toxic if swallowed.

H330 Fatal if inhaled.

H317 May cause an allergic skin reaction.

H341 Suspected of causing genetic defects.

H350 May cause cancer.

H315 Causes skin irritation.

H370 (eyes, central nervous system) Causes damage to organs (eyes, central nervous system).

H370 Causes damage to organs.

H371 May cause damage to organs.

Hazard class and hazard category	Code	Description
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
Acute Tox. 2	3.1/2/Inhal	Acute toxicity (inhalation), Category 2
Acute Tox. 3	3.1/3/Dermal	Acute toxicity (dermal), Category 3
Acute Tox. 3	3.1/3/Inhal	Acute toxicity (inhalation), Category 3
Acute Tox. 3	3.1/3/Oral	Acute toxicity (oral), Category 3
Acute Tox. 4	3.1/4/Oral	Acute toxicity (oral), Category 4
Skin Corr. 1A	3.2/1A	Skin corrosion, Category 1A
Skin Corr. 1B	3.2/1B	Skin corrosion, Category 1B
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Dam. 1	3.3/1	Serious eye damage, Category 1
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
Skin Sens. 1A	3.4.2/1A	Skin Sensitisation, Category 1A
Muta. 2	3.5/2	Germ cell mutagenicity, Category 2
Carc. 1B	3.6/1B	Carcinogenicity, Category 1B
STOT SE 1	3.8/1	Specific target organ toxicity - single exposure, Category 1
STOT SE 2	3.8/2	Specific target organ toxicity - single exposure, Category 2



Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH)), as retained and amended in UK law LFPH 006 VERNIS INCOL BT

STOT SE 3	3.8/3	Specific target organ toxicity - single exposure,
		Category 3

This safety data sheet has been completely updated in compliance to Regulation 2020/878. (EC) 1272/2008 [CLP] Yönetmeligine göre karisimlarin siniflandirmasini elde etmek için kullanılan siniflandirma ve prosedür:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
STOT SE 3, H335	Calculation method

Due to the integration of the Mader Aero products range into the Socomore Group, all Safety Data Sheets have been re-evaluated on the basis of consolidated information. This may have led to significant changes in our Safety Data Sheets. If you have any questions regarding these changes, you can contact us at the address indicated in section 1.

This document was prepared by a competent person who has received appropriate training. Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

CCNL - Appendix 1

Insert further consulted bibliography

Important confidentiality: this document contains confidential information that is proprietary to SOCOMORE. Subject to legal provisions determining otherwise, the distribution, republication or re-transmission of this document, in full or in part, must be limited to clearly identified individuals, either because they use the product, or to provide HSE information. Any communication of this document outside of this framework without our written consent is strictly forbidden.

SOCOMORE strongly advises every recipient of this safety data sheet to read it carefully and to consult experts in the field if necessary or appropriate, in order to understand the information it contains, notably the possible dangers associated with this product. The users must ensure the conformity and completeness of this information with regards to their specific use of the product.

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the responsibility of the purchaser/user to ensure that their activities conform with current legislation in force.

The information is considered correct, but it is not exhaustive and it shall be used only as a guide which is based on the current knowledge of the substance or mixture and it is applicable to the safety



LFPH 006 VERNIS INCOL BT

precautions appropriate for the product.

ADR: European Agreement concerning the International Carriage of

Dangerous Goods by Road.

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of

Chemicals.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport

Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization"

(ICAO).

IMDG: International Maritime Code for Dangerous Goods.

INCI: International Nomenclature of Cosmetic Ingredients.

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LTE: Long-term exposure.

PNEC: Predicted No Effect Concentration.

RID: Regulation Concerning the International Transport of Dangerous Goods

by Rail.

STE: Short-term exposure.

STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity.

STOT SE: May cause drowsiness or dizziness

TLV: Threshold Limiting Value.
TWA: Time-weighted average

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day.

(ACGIH Standard).

WGK: German Water Hazard Class.