

Regulation (EU) n. 2020/878

Master item code: C932002

Safety Data Sheet date: 3/1/2025, version 8

Trade name:	r MEK - SATWIPES / PROSAT / SOCOSAT
SDS code:	P29101EU
References:	SATWIPES C86 /SOCOSAT I80 / SOCOSAT 16400
UFI:	3N5U-5U44-PP2D-8CFC
-	ed uses of the substance or mixture and uses advised against
Recommended use:	
Solvent	
Cleaner	
Industrial uses	
Uses advised against:	
No uses advised	against are identified.
4.0 Details of the own	- Kon of the confects data also t
1.3. Details of the sup Manufacturers:	oplier of the safety data sheet
	J - Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - Franc
-Tel. +33 (0)2 9	
()	Parc Gohelis - 56250 ELVEN France - Tel +33 (0)2 97 43 76 83 - Fax +33
-	
97 54 50 26	
97 54 50 26 Socomore Irelar	nd Ltd Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922
Socomore Irelar	nd Ltd Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922 23 / ireland@socomore.com
Socomore Irelar	nd Ltd Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922 3 / ireland@socomore.com
Socomore Irelar +353 21 488992 Distributors:	3 / ireland@socomore.com J - Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - Franc
Socomore Irelar +353 21 488992 Distributors: Socomore SASI -Tel. +33 (0)2 9	3 / ireland@socomore.com J - Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - Franc
Socomore Irelar +353 21 488992 Distributors: Socomore SASU -Tel. +33 (0)2 9 Manufacturing - 97 54 50 26	23 / ireland@socomore.com J - Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - Franc 7 43 76 90
Socomore Irelar +353 21 488992 Distributors: Socomore SASU -Tel. +33 (0)2 9 Manufacturing - 97 54 50 26 Socomore Irelar	23 / ireland@socomore.com J - Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - Franc 7 43 76 90 Parc Gohelis - 56250 ELVEN France - Tel +33 (0)2 97 43 76 83 - Fax +33
Socomore Irelar +353 21 488992 Distributors: Socomore SASI -Tel. +33 (0)2 9 Manufacturing - 97 54 50 26 Socomore Irelar +353 21 488992	23 / ireland@socomore.com J - Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - Franc 7 43 76 90 Parc Gohelis - 56250 ELVEN France - Tel +33 (0)2 97 43 76 83 - Fax +33 nd Ltd Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922
Socomore Irelar +353 21 488992 Distributors: Socomore SASU -Tel. +33 (0)2 9 Manufacturing - 97 54 50 26 Socomore Irelar +353 21 488992 Competent per	23 / ireland@socomore.com J - Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - Franc 7 43 76 90 Parc Gohelis - 56250 ELVEN France - Tel +33 (0)2 97 43 76 83 - Fax +33 nd Ltd Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922 23 / ireland@socomore.com
Socomore Irelar +353 21 488992 Distributors: Socomore SASU -Tel. +33 (0)2 9 Manufacturing - 97 54 50 26 Socomore Irelar +353 21 488992 Competent per msdsinformation	23 / ireland@socomore.com J - Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - Franc 7 43 76 90 Parc Gohelis - 56250 ELVEN France - Tel +33 (0)2 97 43 76 83 - Fax +33 nd Ltd Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922 23 / ireland@socomore.com son responsible for the safety data sheet: n-eu@socomore.com
Socomore Irelar +353 21 488992 Distributors: Socomore SASU -Tel. +33 (0)2 9 Manufacturing - 97 54 50 26 Socomore Irelar +353 21 488992 Competent per msdsinformatior	23 / ireland@socomore.com J - Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - Franc 7 43 76 90 Parc Gohelis - 56250 ELVEN France - Tel +33 (0)2 97 43 76 83 - Fax +33 nd Ltd Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922 23 / ireland@socomore.com son responsible for the safety data sheet: n-eu@socomore.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

^(*) Danger, Flam. Liq. 2, Highly flammable liquid and vapour.

⁽¹⁾ Warning, Eye Irrit. 2, Causes serious eye irritation.

socomore

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH)) MEK - SATWIPES / PROSAT / SOCOSAT

Warning, STOT SE 3, May cause drowsiness or dizziness. EUH066 Repeated exposure may cause skin dryness or cracking. Adverse physicochemical, human health and environmental effects:

No other hazards **2.2. Label elements** Hazard pictograms:



Danger

Hazard statements:

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P261 Avoid breathing vapours.

P280 Wear protective gloves and eye/face protection.

P370+P378 In case of fire, use a CO2 fire extinguisher to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

Special Provisions:

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains

butanone; ethyl methyl ketone

Special provisions according to Annex XVII of REACH and subsequent amendments: None

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	ldent. Numbe	ər	Classification
- 0070	butanone; ethyl methyl ketone	Index number:		 ♦ 2.6/2 Flam. Liq. 2 H225 ● 3.3/2 Eye Irrit. 2 H319
		CAS:	78-93-3	🍄 3.8/3 STOT SE 3 H336
		EC:	201-159-0	EUH066



SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting. Obtain a medical examination.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

Burning sensation.

Repeated exposure may cause skin dryness or cracking.

Swelling

Blurred vision.

Tearing.

Swollen eyelids.

Itching.

Vapours may cause drowsiness and dizziness.

Temporary burning sensation in the nose and throat.

Cough

Difficult breathing.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

Call a doctor or poison control center for further instructions.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Water Foam. Multipurpose powders class ABC Powders class BC Carbon dioxide (CO2) Extinguishing media which must not be used for safety reasons: None in particular.

P29101EU - version 8 Page 3 / 14

socomore

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH)) MEK - SATWIPES / PROSAT / SOCOSAT

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, ensure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contamined clothing should be changed before entering eating areas.

Do not eat or drink while working.

7.2. Conditions for safe storage, including any incompatibilities

Store under the same conditions as a combustible solid product.

Always keep in a well ventilated place.

Store at ambient temperatures. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

7.3. Specific end use(s)

None in particular



SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

butanone; ethyl methyl ketone - CAS: 78-93-3

- OEL Type: National - TWA: 600 mg/m3, 200 ppm - STEL: 900 mg/m3, 300 ppm - Notes: France VLEC

- OEL Type: EU - TWA(8h): 600 mg/m3, 200 ppm - STEL: 900 mg/m3, 300 ppm

- OEL Type: ACGIH - TWA(8h): 200 ppm - STEL: 300 ppm - Notes: BEI - URT irr, CNS and PNS impair

OEL Type: National - TWA: 600 mg/m3, 200 ppm - Notes: AGW, Germany
OEL Type: MAK - TWA: 295 mg/m3, 100 ppm - STEL(30min (Miw)): 590 mg/m3, 200 ppm - Notes: Österreich

DNEL Exposure Limit Values

butanone; ethyl methyl ketone - CAS: 78-93-3

Worker Industry: 1161 mg/kg - Consumer: 412 mg/kg - Exposure: Human Dermal -Frequency: Short Term (acute) - Notes: 1 day

Worker Industry: 600 mg/m3 - Consumer: 106 mg/m3 - Exposure: Human Inhalation - Frequency: Short Term (acute)

Consumer: 31 mg/kg - Exposure: Human Oral - Frequency: Short Term (acute)

PNEC Exposure Limit Values

butanone; ethyl methyl ketone - CAS: 78-93-3

Target: Fresh Water - Value: 55.8 mg/l

Target: Marine water - Value: 55.8 mg/l

Target: Freshwater sediments - Value: 284.74 mg/kg

Target: Marine water sediments - Value: 287.7 mg/kg

Target: Soil (agricultural) - Value: 22.5 mg/kg

Biological Exposure Index

N.A.

8.2. Exposure controls

See below, example of PPE to use.
Eye protection:
Safety goggles (EN 166)
Use closed fitting safety goggles, don't use eye lens.
Protection for skin:
Chemical protection clothing. (type 3 - EN14605)
Chemical protection clothing. (type 5 - EN13982-1)
Chemical protection clothing. (type 6 - EN13034)
Protection for hands:
Suitable gloves type: NF EN374
PVA (Polyvinyl alcohol).
Butyl rubber (isobutylene-isoprene copolymer)
Respiratory protection:
Use adequate protective respiratory equipment.
Filtering Half-face mask (NF EN 149), class FFP1



Mask with filter "A1" , brown colour (NF EN14387) Thermal Hazards: None Environmental exposure controls: None Appropriate engineering controls: None Other conditions affecting workers exposure:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes
Physical state:	Liquid coated on wipes		
Colour:	Colourless		
Odour:	N.A.		
Melting point/freezing point:	N.A.		
Boiling point or initial boiling point and boiling range:	80 °C		
Flammability:	Flam. Liq. 2, H225		
Lower and upper explosion limit:	N.A.		
Flash point (°C):	-4 °C		
Auto-ignition temperature:	N.A.		
Decomposition temperature:	N.A.		
pH:	N.A.		
Kinematic viscosity:	N.A.		
Solubility in water:	N.A.		
Solubility in oil:	N.A.		
Partition coefficient n- octanol/water (log value):	N.A.		
Vapour pressure:	N.A.		

P29101EU - version 8 Page 6 / 14



Density and/or relative density:	< 1		
Relative vapour density:	N.A.		
Particle characteristics:			
Particle size:	N.A.		

9.2. Other information

No other relevant information Volatile Organic compounds - VOCs = 805 g/l

N.A. = not available

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapours may form an explosive mixture with air.

- 10.2. Chemical stability
 - Stable under normal conditions
- 10.3. Possibility of hazardous reactions None
- **10.4. Conditions to avoid** Stable under normal conditions.
- 10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological information of the product:

MEK - SATWIPES / PROSAT / SOCOSAT

Acute toxicity

Not classified

Based on available data, the classification criteria are not met

Skin corrosion/irritation

Not classified

Based on available data, the classification criteria are not met

Serious eye damage/irritation

The product is classified: Eye Irrit. 2 H319

Respiratory or skin sensitisation

- Not classified
- Based on available data, the classification criteria are not met
- Germ cell mutagenicity

Not classified



Based on available data, the classification criteria are not met Carcinogenicity Not classified Based on available data, the classification criteria are not met Reproductive toxicity Not classified Based on available data, the classification criteria are not met STOT-single exposure The product is classified: STOT SE 3 H336 STOT-repeated exposure Not classified Based on available data, the classification criteria are not met Aspiration hazard Not classified Based on available data, the classification criteria are not met Toxicological information of the main substances found in the product: butanone; ethyl methyl ketone - CAS: 78-93-3 Acute toxicity: Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg Test: LC50 - Route: Inhalation > 5000 ppm

11.2. Information on other hazards

Endocrine disrupting properties: No endocrine disruptor substances present in concentration >= 0.1%

Other toxicological information:

butanone; ethyl methyl ketone Skin corrosion / irritation (rabbit): Slight irritating effect Severe eye injury/irritation (rabbit): Highly irritating

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

MEK - SATWIPES / PROSAT / SOCOSAT

Not classified for environmental hazards

Based on available data, the classification criteria are not met

butanone; ethyl methyl ketone - CAS: 78-93-3

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 13 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish > 1000 mg/l - Duration h: 96 - Notes: Oncorhynchuss mykiss Endpoint: EC50 - Species: Algae > 100 mg/l - Duration h: 168 - Notes: Desmodesmus subspicatus

P29101EU - version 8 Page 8 / 14



12.2. Persistence and degradability

butanone; ethyl methyl ketone - CAS: 78-93-3

Biodegradability: Readily biodegradable - Duration: 28 days - %: 98 - Notes: aerobie

12.3. Bioaccumulative potential

butanone; ethyl methyl ketone - CAS: 78-93-3

Log Pow 0.3

Log Kow 0.3

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration >= 0.1%

12.7. Other adverse effects

No harmful effects expected.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

Codes of wastes (Décision 2001/573/EC, Directive 2006/12/EEC, Directive 94/31/EEC on hazardous waste):

15 02 02* absorbents, filter materials (including oil filters not otherwise specified), wiping cloths, protective clothing contaminated by dangerous substances

SECTION 14: Transport information	
14.1. UN number or ID number	
ADR-UN Number:	3175
IATA-UN Number:	3175
IMDG-UN Number:	3175
14.2. UN proper shipping name	
ADR-Shipping Name:	SOLIDS or mixtures of solids (such as preparations and wastes) CONTAINING FLAMMABLE LIQUID, N.O.S. having a flash-point up to 60 °C (butanone; ethyl methyl ketone)
IATA-Shipping Name:	SOLIDS or mixtures of solids (such as preparations and wastes) CONTAINING FLAMMABLE LIQUID, N.O.S. having a flash-point up to 60 °C (butanone; ethyl methyl ketone)
IMDG-Shipping Name:	SOLIDS or mixtures of solids (such as preparations and wastes) CONTAINING FLAMMABLE LIQUID, N.O.S. having a flash-point up to 60 °C (butanone; ethyl methyl ketone)
14.3. Transport hazard class(es)	
ADR-Class:	4.1
ADR - Hazard identification nu	mber: 40
IATA-Class:	4.1



IATA-Label:	4.1
IMDG-Class:	4.1
14.4. Packing group	
ADR-Packing Group:	H
IATA-Packing group:	H
IMDG-Packing group:	11
14.5. Environmental hazards	
ADR-Enviromental Pollutant:	No
IMDG-Marine pollutant:	No
IMDG-EmS:	F-A , S-I
14.6. Special precautions for user	
ADR-Subsidiary hazards:	-
ADR-S.P.:	216 274 601
ADR-Transport category (Tunn	el restriction code): 2 (E)
IATA-Passenger Aircraft:	445
IATA-Subsidiary hazards:	-
IATA-Cargo Aircraft:	448
IATA-S.P.:	A46
IATA-ERG:	3L
IMDG-Subsidiary hazards:	-
IMDG-Stowage and handling:	Category B
IMDG-Segregation:	-
Q.L.: 1K	
Q.E.: E2	
14.7. Maritime transport in bulk acc	ording to IMO instruments

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work) Dir. 2000/39/EC (Occupational exposure limit values) Regulation (EC) n. 1907/2006 (REACH) Regulation (EC) n. 1272/2008 (CLP) Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013 Regulation (EU) n. 286/2011 (ATP 2 CLP) Regulation (EU) n. 618/2012 (ATP 3 CLP) Regulation (EU) n. 487/2013 (ATP 4 CLP) Regulation (EU) n. 944/2013 (ATP 5 CLP) Regulation (EU) n. 605/2014 (ATP 6 CLP) Regulation (EU) n. 2015/1221 (ATP 7 CLP) Regulation (EU) n. 2016/918 (ATP 8 CLP) Regulation (EU) n. 2016/1179 (ATP 9 CLP) Regulation (EU) n. 2017/776 (ATP 10 CLP) Regulation (EU) n. 2018/669 (ATP 11 CLP) Regulation (EU) n. 2018/1480 (ATP 13 CLP)



Regulation (EU) n. 2019/521 (ATP 12 CLP) Regulation (EU) n. 2020/217 (ATP 14 CLP) Regulation (EU) n. 2020/1182 (ATP 15 CLP) Regulation (EU) n. 2021/643 (ATP 16 CLP) Regulation (EU) n. 2021/849 (ATP 17 CLP) Regulation (EU) n. 2022/692 (ATP 18 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: Restriction 3 Restriction 40 Restrictions related to the substances contained: Restriction 75

Listed or in compliance with the following international inventories:

Labelling of detergents (EC Regulations 648/2004 and 907/2006): N.A.

Labelling of biocides (Regulations 1896/2000, 1687/2002, 2032/2003, 1048/2005, 1849/2006, 1451/2007 and Directive 98/8/EC): N.A.

N.A.

Where applicable, refer to the following regulatory provisions : Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments. 1999/13/EC (VOC directive) Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III): Seveso III category according to Annex 1, part 1 Product belongs to category: P5c

15.2. Chemical safety assessment

No

SECTION 16: Other information N.A.: Not Applicable or Not Available

> P29101EU - version 8 Page 11 / 14



Full text of phrases referred to in Section 3:
H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
EUH066 Repeated exposure may cause skin dryness or cracking.

Hazard class and hazard category	Code	Description
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3

This safety data sheet has been completely updated in compliance to Regulation 2020/878. Paragraphs modified from the previous revision:

SECTION 1: Identification of the substance/mixture and of the company/undertaking SECTION 2: Hazards identification SECTION 3: Composition/information on ingredients SECTION 8: Exposure controls/personal protection SECTION 9: Physical and chemical properties SECTION 11: Toxicological information SECTION 12: Ecological information SECTION 15: Regulatory information

(EC) 1272/2008 [CLP] Yönetmeligine göre karisimlarin siniflandirmasini elde etmek için kullanılan siniflandirma ve prosedür:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Flam. Liq. 2, H225	On basis of test data
Eye Irrit. 2, H319	Calculation method
STOT SE 3, H336	Calculation method

This document was prepared by a competent person who has received appropriate training. Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities



SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold CCNL - Appendix 1 Insert further consulted bibliography

Important confidentiality : this document contains confidential information that is proprietary to SOCOMORE. Subject to legal provisions determining otherwise, the distribution, republication or re-transmission of this document, in full or in part, must be limited to clearly identified individuals, either because they use the product, or to provide HSE information. Any communication of this document outside of this framework without our written consent is strictly forbidden. SOCOMORE strongly advises every recipient of this safety data sheet to read it carefully and to consult experts in the field if necessary or appropriate, in order to understand the information it contains, notably the possible dangers associated with this product. The users must ensure the conformity and completeness of this information with regards to their specific use of the product. The information contained herein is based on our state of knowledge at the above-specified date. It

refers solely to the product indicated and constitutes no guarantee of particular quality. It is the responsibility of the purchaser/user to ensure that their activities conform with current legislation in force.

The information is considered correct, but it is not exhaustive and it shall be used only as a guide which is based on the current knowledge of the substance or mixture and it is applicable to the safety precautions appropriate for the product.

ADR:	European Agreement concerning the International Carriage of
	Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of
	Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport
	Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization"
	(ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.



PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods
	by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
STOT SE:	May cause drowsiness or dizziness
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day.
	(ACGIH Standard).
WGK:	German Water Hazard Class.