

**Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))  
PRIAM 32005 INCOL MT PA**

Regulation (EU) n. 2020/878

**Safety Data Sheet date: 3/7/2024, version 1****SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Trade name: PRIAM 32005 INCOL MT PA  
SDS code: 103130EU  
UFI: 8GDG-R6DD-YK9K-66PV

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Recommended use:

Industrial uses  
Paint/Coating

**1.3. Details of the supplier of the safety data sheet****Manufacturers:**

Socomore SASU - Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - France  
- Tel : +33 (0)2 97 43 76 83 - Fax : +33 (0)2 97 54 50 26

Socomore Ireland Ltd. - Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922 / Fax  
+353 21 4889923 / ireland@socomore.com

**Distributors:**

Socomore SASU - Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - France  
- Tel : +33 (0)2 97 43 76 83 - Fax : +33 (0)2 97 54 50 26

Socomore Ireland Ltd. - Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922 / Fax  
+353 21 4889923 / ireland@socomore.com

**Competent person responsible for the safety data sheet:**

techdirsocomore@socomore.com

**1.4. Emergency telephone number**

France : ORFILA (INRS) +33 (0)1 45 42 59 59  
International : CHEMTEL +1-813-248-0585.

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****EC regulation criteria 1272/2008 (CLP)**

- ⚠ Danger, Flam. Liq. 2, Highly flammable liquid and vapour.
- ⚠ Warning, Skin Irrit. 2, Causes skin irritation.
- ⚠ Warning, Eye Irrit. 2, Causes serious eye irritation.
- ⚠ Warning, Carc. 2, Suspected of causing cancer.
- ⚠ Warning, Repr. 2, Suspected of damaging the unborn child.
- ⚠ Warning, STOT SE 3, May cause drowsiness or dizziness.
- ⚠ Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure.

Adverse physicochemical, human health and environmental effects:

No other hazards

**2.2. Label elements**

Hazard pictograms:

**Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))**  
**PRIAM 32005 INCOL MT PA**



Danger

Hazard statements:

- H225 Highly flammable liquid and vapour.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H351 Suspected of causing cancer.
- H361d Suspected of damaging the unborn child.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements:

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P370+P378 In case of fire: Use dry sand, chemical powder or alcohol-resistant foam for extinction.
- P403+P235 Store in a well-ventilated place. Keep cool.

Special Provisions:

None

Contains

- toluene
- 4-methylpentan-2-one; isobutyl methyl ketone
- n-butyl acetate
- 2-methoxy-1-methylethyl acetate

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

**2.3. Other hazards**

No PBT, vPvB or endocrine disruptor substances present in concentration  $\geq 0.1\%$



**SECTION 3: Composition/information on ingredients**

**3.1. Substances**

N.A.

**3.2. Mixtures**

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification
$\geq 12.5\%$	toluene	Index 601-021-00-3	 2.6/2 Flam. Liq. 2 H225  3.7/2 Repr. 2 H361d
$< 15\%$		number:	

**Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))**  
**PRIAM 32005 INCOL MT PA**

		CAS: 108-88-3 EC: 203-625-9 REACH No.: 01-2119471310-51	<ul style="list-style-type: none"> <li>⚠ 3.10/1 Asp. Tox. 1 H304</li> <li>⚠ 3.9/2 STOT RE 2 H373</li> <li>⚠ 3.2/2 Skin Irrit. 2 H315</li> <li>⚠ 3.8/3 STOT SE 3 H336</li> <li>4.1/C3 Aquatic Chronic 3 H412</li> </ul>
>= 12.5% - < 15%	4-methylpentan-2-one; isobutyl methyl ketone	Index number: 606-004-00-4 CAS: 108-10-1 EC: 203-550-1	<ul style="list-style-type: none"> <li>⚠ 2.6/2 Flam. Liq. 2 H225</li> <li>⚠ 3.6/2 Carc. 2 H351</li> <li>⚠ 3.1/4/Inhal Acute Tox. 4 H332</li> <li>⚠ 3.8/3 STOT SE 3 H336</li> <li>⚠ 3.3/2 Eye Irrit. 2 H319</li> <li>EUH066</li> <li>Acute Toxicity Estimate: ATE - Oral 2080 mg/kg bw ATE - Inhalation (Vapours) 11 mg/l</li> </ul>
>= 12.5% - < 15%	n-butyl acetate	Index number: 607-025-00-1 CAS: 123-86-4 EC: 204-658-1 REACH No.: 01-2119485493-29	<ul style="list-style-type: none"> <li>⚠ 2.6/3 Flam. Liq. 3 H226</li> <li>⚠ 3.8/3 STOT SE 3 H336</li> <li>EUH066</li> </ul>
>= 1% - < 3%	2-methoxy-1-methylethyl acetate	Index number: 607-195-00-7 CAS: 108-65-6 EC: 203-603-9 REACH No.: 01-2119475791-29	<ul style="list-style-type: none"> <li>⚠ 2.6/3 Flam. Liq. 3 H226</li> <li>⚠ 3.8/3 STOT SE 3 H336</li> <li>EUH066</li> </ul>
>= 1% - < 3%	reaction mass of ethylbenzene and xylene	CAS: 1330-20-7 EC: 905-588-0 REACH No.: 01-2119488216-32	<ul style="list-style-type: none"> <li>⚠ 2.6/3 Flam. Liq. 3 H226</li> <li>⚠ 3.10/1 Asp. Tox. 1 H304</li> <li>⚠ 3.1/4/Dermal Acute Tox. 4 H312</li> <li>⚠ 3.1/4/Inhal Acute Tox. 4 H332</li> <li>⚠ 3.2/2 Skin Irrit. 2 H315</li> <li>⚠ 3.3/2 Eye Irrit. 2 H319</li> <li>⚠ 3.8/3 STOT SE 3 H336</li> <li>⚠ 3.9/2 STOT RE 2 H373</li> <li>4.1/C3 Aquatic Chronic 3 H412</li> <li>Acute Toxicity Estimate: ATE - Dermal 1100 mg/kg bw ATE - Inhalation (Vapours) 11 mg/l</li> </ul>
>= 0.3% -	ethylbenzene	Index number: 601-023-00-4	<ul style="list-style-type: none"> <li>⚠ 2.6/2 Flam. Liq. 2 H225</li> </ul>

**Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))**  
**PRIAM 32005 INCOL MT PA**

< 0.5%		CAS: 100-41-4 EC: 202-849-4 REACH No.: 01-2119489370-35	<p>⚠ 3.2/2 Skin Irrit. 2 H315          ⚠ 3.3/2 Eye Irrit. 2 H319          4.1/C3 Aquatic Chronic 3 H412          ⚠ 3.1/4/Inhal Acute Tox. 4 H332          ⚠ 3.9/2 STOT RE 2 H373 (hearing organs)          ⚠ 3.10/1 Asp. Tox. 1 H304          Acute Toxicity Estimate:          ATE - Inhalation (Vapours) 11 mg/l</p>
>= 0.001% - < 0.1%	Cumene	Index number: 601-024-00-X CAS: 98-82-8 EC: 202-704-5	<p>⚠ 2.6/3 Flam. Liq. 3 H226          ⚠ 3.6/1B Carc. 1B H350          ⚠ 3.10/1 Asp. Tox. 1 H304          ⚠ 3.8/3 STOT SE 3 H335          ⚠ 4.1/C2 Aquatic Chronic 2 H411</p>
< 0.0005%	1-methoxy-2-propanol; monopropylene glycol methyl ether	Index number: 603-064-00-3 CAS: 107-98-2 EC: 203-539-1 REACH No.: 01-2119457435-35	<p>⚠ 2.6/3 Flam. Liq. 3 H226          ⚠ 3.8/3 STOT SE 3 H336          Acute Toxicity Estimate:          ATE - Oral 3739 mg/kg bw          ATE - Dermal 2001 mg/kg bw          ATE - Inhalation (Vapours) 30,02 mg/l</p>

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting. Obtain a medical examination.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

**4.2. Most important symptoms and effects, both acute and delayed**

None

**4.3. Indication of any immediate medical attention and special treatment needed**

## Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

### PRIAM 32005 INCOL MT PA

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

No particular treatment.

---

#### SECTION 5: Firefighting measures

##### 5.1. Extinguishing media

Suitable extinguishing media:

Foam.

Carbon dioxide (CO<sub>2</sub>)

Dry powder

Extinguishing media which must not be used for safety reasons:

High power water jet

##### 5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

##### 5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

---

#### SECTION 6: Accidental release measures

##### 6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

##### 6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

##### 6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

##### 6.4. Reference to other sections

See also section 8 and 13

---

#### SECTION 7: Handling and storage

##### 7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Don't use empty container before they have been cleaned.

Before making transfer operations, ensure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contaminated clothing should be changed before entering eating areas.

## Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

### PRIAM 32005 INCOL MT PA

Do not eat or drink while working.

#### 7.2. Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Store at ambient temperatures. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

#### 7.3. Specific end use(s)

None in particular

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Occupational exposure limit values

toluene - CAS: 108-88-3

- OEL Type: National - TWA(8h): 190 mg/m<sup>3</sup> - Notes: Germany - DFG, H, Y
- OEL Type: National - TWA(8h): 76.8 mg/m<sup>3</sup>, 20 ppm - STEL(15min (Miw)): 384 mg/m<sup>3</sup>, 100 ppm - Behaviour: Binding - Notes: France VLEC - TMP N° 4bis, 84 ; peau
- OEL Type: EU - TWA(8h): 192 mg/m<sup>3</sup>, 50 ppm - STEL: 384 mg/m<sup>3</sup>, 100 ppm - Notes: Skin
- OEL Type: National - TWA: 191 mg/m<sup>3</sup>, 50 ppm - STEL: 384 mg/m<sup>3</sup>, 100 ppm - Notes: UK (WELs)
- OEL Type: ACGIH - TWA(8h): 20 ppm - Notes: OTO; A4; BEI - CNS, visual & hearing impair; female repro system eff; pregnancy loss
- OEL Type: MAK - TWA: 190 mg/m<sup>3</sup>, 50 ppm - STEL(15min (Miw)): 380 mg/m<sup>3</sup>, 100 ppm - Notes: Osterreich

4-methylpentan-2-one; isobutyl methyl ketone - CAS: 108-10-1

- OEL Type: EU - TWA(8h): 83 mg/m<sup>3</sup>, 20 ppm - STEL: 208 mg/m<sup>3</sup>, 50 ppm
- OEL Type: ACGIH - TWA(8h): 20 ppm - STEL: 75 ppm - Notes: A3, BEI - URT irr, dizziness, headache
- OEL Type: National - TWA(4h): 83 mg/m<sup>3</sup>, 20 ppm - STEL: 208 mg/m<sup>3</sup>, 50 ppm - Behaviour: Binding - Notes: France

n-butyl acetate - CAS: 123-86-4

- OEL Type: National - TWA: 241 mg/m<sup>3</sup>, 50 ppm - STEL: 723 mg/m<sup>3</sup>, 150 ppm - Behaviour: Binding - Notes: France, VLEPC
- OEL Type: National - TWA: 150 ppm - STEL: 200 ppm - Notes: United Kingdom
- OEL Type: National - TWA(8h): 300 mg/m<sup>3</sup>, 62 ppm - Notes: Germany
- OEL Type: ACGIH - TWA(8h): 50 ppm - STEL: 150 ppm - Notes: Eye and URT irr
- OEL Type: National - TWA(8h): 238 mg/m<sup>3</sup>, 50 ppm - STEL: 712 mg/m<sup>3</sup>, 150 ppm - Notes: BELGIQUE
- OEL Type: National - TWA(8h): 480 mg/m<sup>3</sup>, 99 ppm - Notes: PAYS-BAS
- OEL Type: National - TWA: 480 mg/m<sup>3</sup>, 100 ppm - STEL(Mow): 480 mg/m<sup>3</sup>, 100 ppm - Notes: Osterreich

## Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

### PRIAM 32005 INCOL MT PA

- OEL Type: EU - TWA(8h): 241 mg/m<sup>3</sup>, 50 ppm - STEL: 723 mg/m<sup>3</sup>, 150 ppm
- 2-methoxy-1-methylethyl acetate - CAS: 108-65-6
  - OEL Type: ACGIH - TWA(8h): 150 ppm - STEL: 100 ppm
  - OEL Type: National - TWA(8h): 275 mg/m<sup>3</sup>, 50 ppm - STEL: 550 mg/m<sup>3</sup>, 100 ppm - Behaviour: Binding - Notes: France VLEPC
  - OEL Type: National - TWA(8h): 270 mg/m<sup>3</sup>, 50 ppm - Notes: GERMANY
  - OEL Type: National - TWA(8h): 274 mg/m<sup>3</sup>, 50 ppm - STEL: 548 mg/m<sup>3</sup>, 100 ppm - Notes: UK (WELs)
  - OEL Type: National - TWA: 260 mg/m<sup>3</sup> - STEL: 520 mg/m<sup>3</sup> - Notes: POLAND
  - OEL Type: EU - TWA(8h): 275 mg/m<sup>3</sup>, 50 ppm - STEL: 550 mg/m<sup>3</sup>, 100 ppm - Notes: Skin
  - OEL Type: AIHA
- TWA: 50 ppm
  - OEL Type: National - TWA: 275 mg/m<sup>3</sup>, 50 ppm - STEL(5 min (Mow)): 550 mg/m<sup>3</sup>, 100 ppm - Notes: Österreich
  - OEL Type: National - TWA: 270 mg/m<sup>3</sup>, 50 ppm - Notes: Norway (Skin)
- reaction mass of ethylbenzene and xylene - CAS: 1330-20-7
  - OEL Type: National - TWA(8h): 221 mg/m<sup>3</sup>, 50 ppm - STEL: 442 mg/m<sup>3</sup>, 100 ppm - Notes: France VLEC - TMP N° 4Bis, 84
  - OEL Type: National - TWA(8h): 440 mg/m<sup>3</sup>, 100 ppm - Notes: Germany - DFG, H
  - OEL Type: National - TWA(8h): 220 mg/m<sup>3</sup>, 50 ppm - STEL: 441 mg/m<sup>3</sup>, 100 ppm - Notes: UK (WELs)
  - OEL Type: EU - TWA(8h): 221 mg/m<sup>3</sup>, 50 ppm - STEL: 442 mg/m<sup>3</sup>, 100 ppm - Notes: Skin
  - OEL Type: ACGIH - TWA(8h): 20 ppm - Notes: A4, BEI - URT and eye irr; hematologic eff; CNS impair
  - OEL Type: National - TWA: 435 mg/m<sup>3</sup>, 100 ppm - STEL: 870 mg/m<sup>3</sup>, 200 ppm - Notes: Swiss - SUVA
  - OEL Type: National - TWA: 221 mg/m<sup>3</sup>, 50 ppm - STEL(15min (Miw)): 442 mg/m<sup>3</sup>, 100 ppm - Notes: Österreich
  - OEL Type: National - TWA: 221 mg/m<sup>3</sup>, 50 ppm - Notes: TWA:Poland
- ethylbenzene - CAS: 100-41-4
  - OEL Type: National - TWA(8h): 88.4 mg/m<sup>3</sup>, 20 ppm - Notes: Germany - EU, H
  - OEL Type: National - TWA(8h): 88.4 mg/m<sup>3</sup>, 20 ppm - STEL: 442 mg/m<sup>3</sup>, 100 ppm - Notes: France VLEC - TMP N° 84
  - OEL Type: National - TWA(8h): 441 mg/m<sup>3</sup>, 100 ppm - STEL: 552 mg/m<sup>3</sup>, 125 ppm - Notes: UK (WELs)
  - OEL Type: EU - TWA(8h): 442 mg/m<sup>3</sup>, 100 ppm - STEL: 884 mg/m<sup>3</sup>, 200 ppm - Notes: Skin
  - OEL Type: ACGIH - TWA(8h): 20 ppm - Notes: OTO; A3, BEI - URT & eye irr; ototoxicity; kidney eff; CNS impair
  - OEL Type: National - STEL: 220 mg/m<sup>3</sup> - Notes: Swiss
  - OEL Type: MAK - TWA: 440 mg/m<sup>3</sup>, 100 ppm - STEL(5 min (Mow)): 880 mg/m<sup>3</sup>, 200 ppm - Notes: Osterreich
- Cumene - CAS: 98-82-8



## Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

### PRIAM 32005 INCOL MT PA

- OEL Type: EU - TWA(8h): 50 mg/m<sup>3</sup>, 10 ppm - STEL: 250 mg/m<sup>3</sup>, 50 ppm - Notes: Skin
  - OEL Type: ACGIH - TWA(8h): 5 ppm - Notes: A3 - URT adenoma, neurological eff
  - OEL Type: National - TWA(8h): 50 mg/m<sup>3</sup>, 10 ppm - STEL(15min (Miw)): 250 mg/m<sup>3</sup>, 50 ppm - Behaviour: Binding - Notes: France, VLEPC / peau
  - OEL Type: National - TWA: 50 mg/m<sup>3</sup> - STEL: 250 mg/m<sup>3</sup> - Notes: Poland (Skin / skóra)
- 1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2
- OEL Type: National - TWA(8h): 188 mg/m<sup>3</sup>, 50 ppm - STEL: 375 mg/m<sup>3</sup>, 100 ppm - Behaviour: Binding - Notes: France VLEC - INRS TMP N°84
  - OEL Type: National - TWA: 370 mg/m<sup>3</sup>, 100 ppm - Notes: Germany
  - OEL Type: National - TWA: 180 mg/m<sup>3</sup> - STEL: 360 mg/m<sup>3</sup> - Notes: Poland
  - OEL Type: EU - TWA(8h): 375 mg/m<sup>3</sup>, 100 ppm - STEL: 563 mg/m<sup>3</sup>, 150 ppm - Notes: Skin
  - OEL Type: ACGIH - TWA(8h): 50 ppm - STEL: 100 ppm - Notes: A4 - Eye and URT irr
  - OEL Type: National - TWA: 187 mg/m<sup>3</sup>, 50 ppm - STEL(15min (Miw)): 187 mg/m<sup>3</sup>, 50 ppm - Notes: Austria
  - OEL Type: National - TWA(8h): 375 mg/m<sup>3</sup>, 100 ppm - STEL(15min (Miw)): 560 mg/m<sup>3</sup>, 150 ppm - Notes: United Kingdom - Skin
  - OEL Type: National - TWA(8h): 188 mg/m<sup>3</sup>, 50 ppm - STEL: 375 mg/m<sup>3</sup>, 100 ppm - Notes: Canada (Gazette Officielle du Québec, January 4, 2023, Vol. 155, No.1)
  - OEL Type: National - TWA: 180 mg/m<sup>3</sup>, 50 ppm - Notes: Norway (skin)
  - OEL Type: DOW IHG - TWA: 1.5 ppm - STEL: 4.5 ppm

#### DNEL Exposure Limit Values

toluene - CAS: 108-88-3

Worker Professional: 384 mg/m<sup>3</sup> - Consumer: 226 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Professional: 192 mg/m<sup>3</sup> - Consumer: 56.5 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Professional: 180 mg/kg - Consumer: 226 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Consumer: 8.13 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

Worker Professional: 384 mg/m<sup>3</sup> - Consumer: 226 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, local effects

4-methylpentan-2-one; isobutyl methyl ketone - CAS: 108-10-1

Worker Industry: 208 mg/m<sup>3</sup> - Consumer: 155.2 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 208 mg/m<sup>3</sup> - Consumer: 155.2 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Industry: 11.8 mg/kg b.w./day - Consumer: 4.2 mg/kg b.w./day - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 83 mg/m<sup>3</sup> - Consumer: 14.7 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 4.2 mg/kg b.w./day - Exposure: Human Oral - Frequency: Long Term, systemic effects

Worker Industry: 83 mg/m<sup>3</sup> - Consumer: 14.7 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, local effects



## Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

### PRIAM 32005 INCOL MT PA

n-butyl acetate - CAS: 123-86-4

Worker Industry: 11 mg/kg - Consumer: 6 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 300 mg/m<sup>3</sup> - Consumer: 35.7 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 2 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

Worker Industry: 600 mg/m<sup>3</sup> - Consumer: 300 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 11 mg/kg - Consumer: 2 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects

Worker Industry: 600 mg/m<sup>3</sup> - Consumer: 300 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Industry: 300 mg/m<sup>3</sup> - Consumer: 35.7 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, local effects

Worker Industry: 11 mg/kg - Consumer: 6 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

Worker Industry: 796 mg/kg b.w./day - Consumer: 320 mg/kg b.w./day - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 275 mg/m<sup>3</sup> - Consumer: 33 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 36 mg/kg b.w./day - Exposure: Human Oral - Frequency: Long Term, systemic effects

Worker Industry: 550 mg/m<sup>3</sup> - Consumer: 33 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, local effects

reaction mass of ethylbenzene and xylene - CAS: 1330-20-7

Worker Industry: 77 mg/m<sup>3</sup> - Consumer: 14.8 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Industry: 289 mg/m<sup>3</sup> - Consumer: 174 mg/kg b.w./day - Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Industry: 289 mg/m<sup>3</sup> - Consumer: 174 mg/kg b.w./day - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 180 mg/kg b.w./day - Consumer: 108 mg/kg b.w./day - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Consumer: 1.6 mg/kg b.w./day - Exposure: Human Oral - Frequency: Long Term, systemic effects

ethylbenzene - CAS: 100-41-4

Worker Industry: 77 mg/m<sup>3</sup> - Consumer: 15 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

Worker Industry: 180 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 293 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, local effects

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

## Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

### PRIAM 32005 INCOL MT PA

Worker Industry: 369 mg/m<sup>3</sup> - Consumer: 43.9 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects  
 Worker Industry: 50.6 mg/kg b.w./day - Consumer: 18.1 mg/kg b.w./day - Exposure: Human Dermal - Frequency: Long Term, systemic effects  
 Consumer: 3.3 mg/kg b.w./day - Exposure: Human Oral - Frequency: Long Term, systemic effects  
 Worker Industry: 553.5 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term (acute)

#### PNEC Exposure Limit Values

toluene - CAS: 108-88-3

Target: Fresh Water - Value: 0.68 mg/l  
 Target: Freshwater sediments - Value: 16.39 mg/kg  
 Target: Soil (agricultural) - Value: 2.89 mg/kg  
 Target: Microorganisms in sewage treatments - Value: 13.61 mg/l

4-methylpentan-2-one; isobutyl methyl ketone - CAS: 108-10-1

Target: Fresh Water - Value: 0.6 mg/l  
 Target: Soil - Value: 1.3 mg/kg dw  
 Target: Freshwater sediments - Value: 8.27 mg/kg dw  
 Target: Sewage treatment plant - Value: 27.5 mg/l

n-butyl acetate - CAS: 123-86-4

Target: Fresh Water - Value: 0.18 mg/l  
 Target: Marine water - Value: 0.018 mg/l  
 Target: Freshwater sediments - Value: 0.981 mg/kg  
 Target: Water (intermittent discharge) - Value: 0.36 mg/l  
 Target: Marine water sediments - Value: 0.0981 mg/kg  
 Target: Soil - Value: 0.0903 mg/kg  
 Target: Microorganisms in sewage treatments - Value: 35.6 mg/l

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

Target: Fresh Water - Value: 0.635 mg/l  
 Target: Marine water - Value: 0.0635 mg/l  
 Target: Microorganisms in sewage treatments - Value: 100 mg/l  
 Target: Freshwater sediments - Value: 3.29 mg/kg dw  
 Target: Marine water sediments - Value: 0.329 mg/kg dw  
 Target: Soil - Value: 0.29 mg/kg  
 Target: PNEC intermittent - Value: 6.35 mg/l

reaction mass of ethylbenzene and xylene - CAS: 1330-20-7

Target: Fresh Water - Value: 0.327 mg/l  
 Target: Water (intermittent discharge) - Value: 0.327 mg/l  
 Target: Marine water - Value: 0.327 mg/l  
 Target: Sewage treatment plant - Value: 6.58 mg/l  
 Target: Freshwater sediments - Value: 12.46 mg/kg  
 Target: Marine water sediments - Value: 12.46 mg/kg  
 Target: Soil - Value: 2.31 mg/kg

ethylbenzene - CAS: 100-41-4

Target: Marine water - Value: 0.01 mg/l - Notes: factor assessment : 10

## Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

### PRIAM 32005 INCOL MT PA

Target: Marine water - Value: 0.1 mg/l - Notes:: factor assessment : 18  
 Target: PNEC predator - Value: 2.68 mg/kg - Notes:: ECHA  
 1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2  
 Target: Fresh Water - Value: 10 mg/l  
 Target: Freshwater sediments - Value: 41.6 mg/kg  
 Target: Marine water sediments - Value: 4.17 mg/kg  
 Target: Soil (agricultural) - Value: 2.47 mg/kg  
 Target: Microorganisms in sewage treatments - Value: 100 mg/l  
 Target: Marine water - Value: 1 mg/l  
 Target: Water (intermittent discharge) - Value: 100 mg/l

#### Biological Exposure Index

reaction mass of ethylbenzene and xylene - CAS: 1330-20-7  
 Remark: ACGIH BEL (2009)  
 Remark: FR IBE (1997)

#### 8.2. Exposure controls

See below, example of PPE to use.

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use adequate protective respiratory equipment.

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

Other conditions affecting workers exposure:

None

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes
Physical state:	Liquid	--	--
Colour:	Colourless	--	--
Odour:	de solvant/ solvent-like	--	--
Melting point/freezing point:	N.A.	--	--
Boiling point or initial boiling point and boiling range:	>36°C	--	--

**Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))**  
**PRIAM 32005 INCOL MT PA**

Flammability:	Flam. Liq. 2, H225	--	--
Lower and upper explosion limit:	N.A.	--	--
Flash point (°C):	~4°C	--	--
Auto-ignition temperature:	N.A.	--	--
Decomposition temperature:	Not Relevant	--	--
pH:	Not Relevant	--	--
Kinematic viscosity:	> 20,5 mm <sup>2</sup> / sec (40 °C)	--	--
Solubility in water:	immiscible	--	--
Solubility in oil:	N.A.	--	--
Partition coefficient n-octanol/water (log value):	N.A.	--	--
Vapour pressure:	N.A.	--	--
Density and/or relative density:	~1.05 g/cm <sup>3</sup> (23°C)	--	--
Relative vapour density:	<1.000 hPa (50°C)	--	--
Particle characteristics:			
Particle size:	N.A.	--	--

9.2. Other information

Properties	Value	Method:	Notes
Viscosity:	>20.6 mm <sup>2</sup> /s (40°C)	--	--

Volatile Organic compounds - VOCs = 44.53 %

Volatile Organic compounds - VOCs = 467.57 g/l

N.A. = not available

**Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))  
PRIAM 32005 INCOL MT PA****SECTION 10: Stability and reactivity****10.1. Reactivity**

Stable under normal conditions

**10.2. Chemical stability**

Stable under normal conditions

**10.3. Possibility of hazardous reactions**

None

**10.4. Conditions to avoid**

Stable under normal conditions.

**10.5. Incompatible materials**

Strong oxidizers.

**10.6. Hazardous decomposition products**

None.

---

**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Toxicological information of the product:

PRIAM 32005 INCOL MT PA

Acute toxicity

Not classified

Based on available data, the classification criteria are not met

ATEmix - Dermal 58100,4 mg/kg bw

ATEmix - Inhalation (Vapours) 75,5445 mg/l

Skin corrosion/irritation

The product is classified: Skin Irrit. 2 H315

Serious eye damage/irritation

The product is classified: Eye Irrit. 2 H319

Respiratory or skin sensitisation

Not classified

Based on available data, the classification criteria are not met

Germ cell mutagenicity

Not classified

Based on available data, the classification criteria are not met

Carcinogenicity

The product is classified: Carc. 2 H351

Reproductive toxicity

The product is classified: Repr. 2 H361d

STOT-single exposure

The product is classified: STOT SE 3 H336

STOT-repeated exposure

The product is classified: STOT RE 2 H373

Aspiration hazard

Not classified

Based on available data, the classification criteria are not met

Toxicological information of the main substances found in the product:

toluene - CAS: 108-88-3

Acute toxicity:

**Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))  
PRIAM 32005 INCOL MT PA**

Test: LD50 - Route: Oral - Species: Rat = 5580 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

Test: LC50 - Route: Inhalation Vapour - Species: Rat = 28.1 mg/l - Duration: 4h

4-methylpentan-2-one; isobutyl methyl ketone - CAS: 108-10-1

Acute toxicity

ATE - Oral 2080 mg/kg bw

ATE - Inhalation (Vapours) 11 mg/l

Test: ATE - Route: Inhalation Vapour = 11 mg/l - Source: Reg. (CE) No. 1272/2008

Test: ATE - Route: Oral = 2080 mg/kg

Test: LD50 - Route: Oral - Species: Rat = 2080 mg/kg - Source: OECD 401

Test: LD50 - Route: Skin - Species: Rat > 2000 mg/kg - Source: OECD 402

Test: LC50 - Route: Inhalation - Species: Rat > 8.2 mg/l - Duration: 4h - Source: OECD 403

Test: LC50 - Route: Inhalation - Species: Rat < 16.4 mg/l - Duration: 4h - Source: OECD 403

n-butyl acetate - CAS: 123-86-4

Acute toxicity:

Test: LD50 - Route: Skin - Species: Rabbit > 14000 mg/kg

Test: LD50 - Route: Oral - Species: Rat = 10736 mg/kg

Test: LC50 - Route: Inhalation Dust - Species: Rat = 23.4 mg/l - Duration: 4h

Test: LC50 - Route: Inhalation Mist - Species: Rat = 23.4 mg/l - Duration: 4h

Test: LC50 - Route: Inhalation (aerosol) - Species: Rabbit (male, female) = 0.74 mg/l - Duration: 4h - Source: OECD 403

Test: LC50 - Route: Inhalation Vapour - Species: Rat > 21.1 mg/l - Duration: 4h - Source: OECD 403

Test: LC0 - Route: Inhalation Vapour - Species: Rat > 38.32 mg/l - Duration: 6 hours

Reproductive toxicity:

Test: LOAEC - Route: Inhalation Vapour - Species: Rat = 1500 ppm - Source: OECD 414

Test: NOAEC - Route: Inhalation Vapour - Species: mouse (Male, female) = 2000 ppm - Duration: 90 Jours - Source: OECD 416

STOT-repeated exposure:

Test: NOAEC - Route: Inhalation - Species: Rat (Male, female) = 500 ppm - Duration: 13 weeks - Source: EPA OTS 798.2450

Test: NOAEL - Route: Oral - Species: Rat (Male, female) = 125 mg/kg bw/day - Duration: 13 weeks

Test: LOAEL

- Route: Oral - Species: mouse (Male, female) = 500 mg/kg bw/day - Duration: 13 days

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg - Source: OECD 401

Test: LD50 - Route: Skin - Species: Rat > 2000 mg/kg - Source: OECD 402

Test: LC50 - Route: Inhalation - Species: Rat > 10.8 mg/l

Test: LC50 - Route: Skin - Species: Rabbit > 5000 mg/kg - Source: OECD 402

Test: LC0 - Route: Inhalation Vapour - Species: Rabbit = 23.5 mg/l - Source: OECD 403

Test: ATE - Route: Oral > 5000 mg/kg

**Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))  
PRIAM 32005 INCOL MT PA**

Test: ATE - Route: Inhalation Vapour > 23.5 mg/l - Duration: 6 hours

Test: ATE - Route: Skin > 5000 mg/kg

reaction mass of ethylbenzene and xylene - CAS: 1330-20-7

Acute toxicity

ATE - Dermal 1100 mg/kg bw

ATE - Inhalation (Vapours) 11 mg/l

Test: LD50 - Route: Skin = 1100 mg/kg

Test: LC50 - Route: Inhalation Vapour = 11 mg/l

Carcinogenicity:

Test: NOAEL - Route: Oral - Species: Rat > 500 mg/kg bw/day

Reproductive toxicity:

Test: NOAEC - Route: Inhalation - Species: Rat = 500 ppm - Notes: fertilité/fertility

Test: NOAEC - Route: Inhalation - Species: Rat = 100 ppm - Notes:  
développement/development

Aspiration hazard:

= 0.812 cP - Notes: @20°C

ethylbenzene - CAS: 100-41-4

Acute toxicity

ATE - Inhalation (Vapours) 11 mg/l

Test: LD50 - Route: Skin - Species: Rabbit = 4100 mg/kg

Test: LD50 - Route: Oral - Species: Rat = 3500 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 20 mg/l - Duration: 4h

Test: LCL0 - Route: Inhalation - Species: Rat = 4000 ppm - Duration: 4h

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

Acute toxicity

ATE - Oral 3739 mg/kg bw

ATE - Dermal 2001 mg/kg bw

ATE - Inhalation (Vapours) 30,02 mg/l

Test: LD50 - Route: Oral - Species: Rat (male) = 3739 mg/kg - Source: OECD 401

Test: LD50 - Route: Oral - Species: Rat (female) = 4277 mg/kg - Source: OECD 401

Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 5 mg/l - Duration: 4h

Test: LC50 - Route: Inhalation Vapour - Species: Rat (Male, female) = 30.02 mg/l -

Duration: 4h - Source: OECD 403

Test: ATE - Route: Oral = 3739 mg/kg

Test: ATE - Route: Inhalation Vapour = 30.02 mg/l - Duration: 4h

**11.2. Information on other hazards**

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration  $\geq 0.1\%$

Other toxicological information:

toluene

Skin contact:

Irritating effect



## Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

### PRIAM 32005 INCOL MT PA

Eye contact:

Irritating effect

Inhalation of high concentration of vapours may cause irritation of the respiratory system.

Inhalation of high concentration vapours causes a narcotic reaction on the central nervous system, and severe lung damage.

Ingestion may cause irritation of the digestive tract, nausea, vomiting and diarrhea, abdominal pain.

Risk of central nervous system depression.

-

reaction mass of ethylbenzene and xylene

Skin contact:

Irritating effect

Ingestion:

Ingestion may cause irritation of the digestive tract, nausea, vomiting and diarrhea, abdominal pain.

Harmful by inhalation.

## SECTION 12: Ecological information

### 12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

PRIAM 32005 INCOL MT PA

Not classified for environmental hazards

Based on available data, the classification criteria are not met

toluene - CAS: 108-88-3

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae = 134 mg/l - Duration h: 3 - Notes: Chlorella vulgaris

Endpoint: EC50 - Species: Daphnia = 3.78 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish = 5.5 mg/l - Duration h: 96 - Notes: Oncorhynchus kisutch

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 0.74 mg/l - Duration h: 168 - Notes: Ceriodaphnia dubia

Endpoint: NOEC - Species: Algae = 10 mg/l - Duration h: 72 - Notes: Skeletonema costatum

Endpoint: EC50 - Species: Daphnia = 3.23 mg/l - Duration h: 168 - Notes: Ceriodaphnia dubia

Endpoint: LOEC

- Species: Daphnia = 2.76 mg/kg/d - Duration h: 168 - Notes: Ceriodaphnia dubia

Endpoint: NOEC - Species: Fish = 1.39 mg/l - Duration h: 960 - Notes: Oncorhynchus kisutch

Endpoint: LOEC

- Species: Fish = 2.77 mg/l - Duration h: 960 - Notes: Oncorhynchus kisutch

c) Bacteria toxicity:

Endpoint: NOEC - Species: bacteria = 29 mg/l - Duration h: 16 - Notes: pseudomonas putida

4-methylpentan-2-one; isobutyl methyl ketone - CAS: 108-10-1

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 179 mg/l - Duration h: 96 - Notes: Danio rerio; OECD 203

Endpoint: EC50 - Species: Daphnia > 200 mg/l - Duration h: 48 - Notes: Daphnia magna; OECD 202

## Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

### PRIAM 32005 INCOL MT PA

Endpoint: NOEC - Species: Daphnia = 30 mg/l - Duration h: 504 - Notes: Daphnia magna; OECD 211

Endpoint: EC50 - Species: bacteria = 275 mg/l - Duration h: 16 - Notes: Pseudomonas putida; DIN 38412 T.8

n-butyl acetate - CAS: 123-86-4

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae = 647.7 mg/l - Duration h: 72 - Notes: Desmodesmus subspicatus

Endpoint: NOEC - Species: Algae = 200 mg/l - Notes: Desmodesmus subspicatus

Endpoint: EC50 - Species: Aquatic plants = 397 mg/l - Duration h: 72 - Notes: DIN 38412 Part. 9, Pseudokirchneriella subcapitata

Endpoint: LC50 - Species: Fish = 18 mg/l - Duration h: 96 - Notes: OECD 203, Pimephales promelas

Endpoint: EC50 - Species: bacteria = 356 mg/l - Duration h: 40 - Notes: Tetrahymena pyriformis

Endpoint: EC50 - Species: Daphnia = 44 mg/l - Duration h: 48 - Notes: OECD 202

Endpoint: ErC50 - Species: Aquatic plants = 397 mg/l - Duration h: 72 - Notes: OECD 201, Pseudokirchneriella subcapitata

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 23 mg/l - Duration h: 504 - Notes: OCDE 211

Endpoint: NOEC - Species: Aquatic plants = 196 mg/l - Duration h: 72 - Notes: OECD 201, Pseudokirchneriella subcapitata

Endpoint: IC50 - Species: bacteria = 356 mg/l - Duration h: 40 - Notes: TETRATOX assay, Tetrahymena pyriformis

d) Terrestrial toxicity:

Endpoint: EC50 > 1000 mg/kg - Duration h: 336 - Notes: Lactuca sativa

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Aquatic plants > 1000 mg/l - Duration h: 72 - Notes: Selenastrum capricornutum, OECD 201

Endpoint: LC50 - Species: Fish = 134 mg/l - Duration h: 96 - Notes: Oncorhynchus mykiss, OECD 203

Endpoint: EC50 - Species: Invertebrates > 500 mg/l - Duration h: 48 - Notes: Daphnia magna

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Fish = 47.5 mg/l - Duration h: 336 - Notes: Oryzias latipes, OECD 204

Endpoint: NOEC - Species: Invertebrates > 100 mg/l - Duration h: 504 - Notes: Daphnia magna, OECD 202

reaction mass of ethylbenzene and xylene - CAS: 1330-20-7

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 2.6 mg/l - Duration h: 96 - Notes: Oncorhynchus mykiss

Endpoint: IC50 - Species: Aquatic invertebrates = 1 mg/kg/d - Duration h: 24 - Notes: Daphnia magna

Endpoint: EC50 - Species: Aquatic plants = 2.2 mg/l - Duration h: 73 - Notes: Pseudokirchneriella subcapitata

## Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

### PRIAM 32005 INCOL MT PA

Endpoint: NOEC - Species: activated sludge = 157 mg/l - Duration h: 3

Endpoint: NOEC - Species: Fish > 1.3 mg/l - Duration h: 1344 - Notes: Oncorhynchus mykiss

Endpoint: NOAEL - Species: Aquatic invertebrates = 1.17 mg/l - Duration h: 168 - Notes:  
Ceriodaphnia dubia

ethylbenzene - CAS: 100-41-4

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia > 1.37 mg/l - Duration h: 48

Endpoint: EC50 - Species: Daphnia < 4.4 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish = 4.2 mg/l - Duration h: 96 - Notes: Oncorhynchus mykiss

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Fish > 1 mg/l

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 1000 mg/l - Duration h: 96 - Notes: Leuciscus idus, LC/EC/IC50

Endpoint: LC50 - Species: Daphnia > 1000 mg/l - Duration h: 48 - Notes: LC/EC/IC50

Endpoint: LC50 - Species: Algae > 1000 mg/l - Notes: LC/EC/IC50

Endpoint: LC50 - Species: Fish < 4600 mg/l - Duration h: 96 - Notes: Leuciscus idus

#### 12.2. Persistence and degradability

toluene - CAS: 108-88-3

Biodegradability: Readily biodegradable - Duration: 14 days - %: 100

4-methylpentan-2-one; isobutyl methyl ketone - CAS: 108-10-1

Biodegradability: Readily biodegradable - Test: OECD 301F - %: 83%

n-butyl acetate - CAS: 123-86-4

Biodegradability: Biodegradability rate - Test: OECD 301D - Duration: 5 days - %: 83% - Notes:  
CEE 92/69, C.4-E

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

Biodegradability: Biological oxygen demand (BOD) - Test: OECD 301F - Duration: 28 days - %:  
83% - Notes: ISO 9408; 92/69/CEE, C.4-D

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

Biodegradability: Readily biodegradable

#### 12.3. Bioaccumulative potential

toluene - CAS: 108-88-3

BCF 90

Log Pow 2.65

n-butyl acetate - CAS: 123-86-4

BCF 15.3

Log Kow 2.3 - Notes: 25 °C

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

BCF < 100

Log Pow < 3

ethylbenzene - CAS: 100-41-4

Log Kow 3.15

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

Log Pow 0.37

#### 12.4. Mobility in soil

n-butyl acetate - CAS: 123-86-4

## Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

### PRIAM 32005 INCOL MT PA

Log Koc 1.268

Volatility (H: Henry's Law Constant) 28.5 Pa.m<sup>3</sup>/mol - Notes: 25 °C

reaction mass of ethylbenzene and xylene - CAS: 1330-20-7

Log Koc 2.73 - Notes: @20-25°C

Volatility (H: Henry's Law Constant) 623-665 Pa m<sup>3</sup>/mol - Notes: @25°C

Surface tension 29.76 mN/m - Notes: @25°C

#### 12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

#### 12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration >= 0.1%

#### 12.7. Other adverse effects

No harmful effects expected.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

Codes of wastes (Décision 2001/573/EC, Directive 2006/12/EEC, Directive 94/31/EEC on hazardous waste):

08 01 11\* wastes of paint and varnish containing organic solvents or other dangerous substances

### SECTION 14: Transport information



#### 14.1. UN number or ID number

ADR-UN Number: 1263

IATA-UN Number: 1263

IMDG-UN Number: 1263

#### 14.2. UN proper shipping name

ADR-Shipping Name: PAINT

IATA-Shipping Name: PAINT

IMDG-Shipping Name: PAINT

#### 14.3. Transport hazard class(es)

ADR-Class: 3

ADR - Hazard identification number: 33

IATA-Class: 3

IATA-Label: 3

IMDG-Class: 3

#### 14.4. Packing group

ADR-Packing Group: II

IATA-Packing group: II

IMDG-Packing group: II

#### 14.5. Environmental hazards

ADR-Environmental Pollutant: No

IMDG-Marine pollutant: No

## **Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))**

### **PRIAM 32005 INCOL MT PA**

IMDG-EmS: F-E , S-E

#### **14.6. Special precautions for user**

ADR-Subsidiary hazards: -  
 ADR-S.P.: 163 367 640D 650  
 ADR-Transport category (Tunnel restriction code): 2 (D/E)  
 IATA-Passenger Aircraft: 353  
 IATA-Subsidiary hazards: -  
 IATA-Cargo Aircraft: 364  
 IATA-S.P.: A3 A72 A192  
 IATA-ERG: 3L  
 IMDG-Subsidiary hazards: -  
 IMDG-Stowage and handling: Category B  
 IMDG-Segregation: -  
 Q.L.: 5L  
 Q.E.: E2

#### **14.7. Maritime transport in bulk according to IMO instruments**

N.A.

---

## **SECTION 15: Regulatory information**

### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Dir. 98/24/EC (Risks related to chemical agents at work)  
 Dir. 2000/39/EC (Occupational exposure limit values)  
 Regulation (EC) n. 1907/2006 (REACH)  
 Regulation (EC) n. 1272/2008 (CLP)  
 Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013  
 Regulation (EU) n. 286/2011 (ATP 2 CLP)  
 Regulation (EU) n. 618/2012 (ATP 3 CLP)  
 Regulation (EU) n. 487/2013 (ATP 4 CLP)  
 Regulation (EU) n. 944/2013 (ATP 5 CLP)  
 Regulation (EU) n. 605/2014 (ATP 6 CLP)  
 Regulation (EU) n. 2015/1221 (ATP 7 CLP)  
 Regulation (EU) n. 2016/918 (ATP 8 CLP)  
 Regulation (EU) n. 2016/1179 (ATP 9 CLP)  
 Regulation (EU) n. 2017/776 (ATP 10 CLP)  
 Regulation (EU) n. 2018/669 (ATP 11 CLP)  
 Regulation (EU) n. 2018/1480 (ATP 13 CLP)  
 Regulation (EU) n. 2019/521 (ATP 12 CLP)  
 Regulation (EU) n. 2020/217 (ATP 14 CLP)  
 Regulation (EU) n. 2020/1182 (ATP 15 CLP)  
 Regulation (EU) n. 2021/643 (ATP 16 CLP)  
 Regulation (EU) n. 2021/849 (ATP 17 CLP)  
 Regulation (EU) n. 2022/692 (ATP 18 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

**Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))  
PRIAM 32005 INCOL MT PA**

Restrictions related to the product:

Restriction 3  
Restriction 40

Restrictions related to the substances contained:

Restriction 30  
Restriction 48  
Restriction 70  
Restriction 75

Listed or in compliance with the following international inventories:

Labelling of detergents (EC Regulations 648/2004 and 907/2006):

N.A.

Labelling of biocides (Regulations 1896/2000, 1687/2002, 2032/2003, 1048/2005, 1849/2006, 1451/2007 and Directive 98/8/EC):

N.A.

N.A.

Where applicable, refer to the following regulatory provisions :

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments.

1999/13/EC (VOC directive)

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

Product belongs to category: P5c

**15.2. Chemical safety assessment**

No

---

**SECTION 16: Other information**

N.A.: Not Applicable or Not Available

Full text of phrases referred to in Section 3:

H225 Highly flammable liquid and vapour.

H361d Suspected of damaging the unborn child.

H304 May be fatal if swallowed and enters airways.

H373 May cause damage to organs through prolonged or repeated exposure.

## Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

### PRIAM 32005 INCOL MT PA

H315 Causes skin irritation.  
 H336 May cause drowsiness or dizziness.  
 H412 Harmful to aquatic life with long lasting effects.  
 H351 Suspected of causing cancer.  
 H332 Harmful if inhaled.  
 H319 Causes serious eye irritation.  
 EUH066 Repeated exposure may cause skin dryness or cracking.  
 H226 Flammable liquid and vapour.  
 H312 Harmful in contact with skin.  
 H335 May cause respiratory irritation.  
 H373 (hearing organs) May cause damage to organs (hearing organs) through prolonged or repeated exposure.  
 H350 May cause cancer.  
 H411 Toxic to aquatic life with long lasting effects.

Hazard class and hazard category	Code	Description
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
Acute Tox. 4	3.1/4/Dermal	Acute toxicity (dermal), Category 4
Acute Tox. 4	3.1/4/Inhal	Acute toxicity (inhalation), Category 4
Asp. Tox. 1	3.10/1	Aspiration hazard, Category 1
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
Carc. 1B	3.6/1B	Carcinogenicity, Category 1B
Carc. 2	3.6/2	Carcinogenicity, Category 2
Repr. 2	3.7/2	Reproductive toxicity, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3
STOT RE 2	3.9/2	Specific target organ toxicity - repeated exposure, Category 2
Aquatic Chronic 2	4.1/C2	Chronic (long term) aquatic hazard, category 2
Aquatic Chronic 3	4.1/C3	Chronic (long term) aquatic hazard, category 3



**Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))  
PRIAM 32005 INCOL MT PA**

This safety data sheet has been completely updated in compliance to Regulation 2020/878. (EC) 1272/2008 [CLP] Yönetmeliğine göre karışımların sınıflandırmasını elde etmek için kullanılan sınıflandırma ve prosedür:

<b>Classification according to Regulation (EC) Nr. 1272/2008</b>	<b>Classification procedure</b>
Flam. Liq. 2, H225	On basis of test data
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
Carc. 2, H351	Calculation method
Repr. 2, H361d	Calculation method
STOT SE 3, H336	Calculation method
STOT RE 2, H373	Calculation method

Due to the integration of the Mader Aero products range into the Socomore Group, all Safety Data Sheets have been re-evaluated on the basis of consolidated information. This may have led to significant changes in our Safety Data Sheets. If you have any questions regarding these changes, you can contact us at the address indicated in section 1.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

- ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities
  - SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold
  - CCNL - Appendix 1
- Insert further consulted bibliography

Important confidentiality : this document contains confidential information that is proprietary to SOCOMORE. Subject to legal provisions determining otherwise, the distribution, republication or re-transmission of this document, in full or in part, must be limited to clearly identified individuals, either because they use the product, or to provide HSE information. Any communication of this document outside of this framework without our written consent is strictly forbidden.

SOCOMORE strongly advises every recipient of this safety data sheet to read it carefully and to consult experts in the field if necessary or appropriate, in order to understand the information it contains, notably the possible dangers associated with this product. The users must ensure the conformity and completeness of this information with regards to their specific use of the product.

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the responsibility of the purchaser/user to ensure that their activities conform with current legislation in force.

**Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))  
PRIAM 32005 INCOL MT PA**

The information is considered correct, but it is not exhaustive and it shall be used only as a guide which is based on the current knowledge of the substance or mixture and it is applicable to the safety precautions appropriate for the product.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
STOT SE:	May cause drowsiness or dizziness
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
WGK:	German Water Hazard Class.