

**Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))
SOCOCLEAN A2501 UV SATWIPES PROSAT SOCOSAT**

Regulation (EU) n. 2020/878

Master item code: **P42502**Safety Data Sheet date: **22/11/2024, version 10****SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Trade name: SOCOCLEAN A2501 UV SATWIPES PROSAT SOCOSAT
SDS code: P47126EU
References: SOCOCLEAN A2501 UV E 15x14
UFI: QDSX-JUDU-JC46-170W

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Cleaner

Industrial uses

Uses advised against:

No uses advised against are identified.

1.3. Details of the supplier of the safety data sheet**Manufacturers:**

Socomore SASU - Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - France
-Tel. +33 (0)2 97 43 76 90

Manufacturing - Parc Gohelis - 56250 ELVEN France - Tel +33 (0)2 97 43 76 83 - Fax +33 (0)2 97 54 50 26

Socomore Ireland Ltd. - Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922 / Fax +353 21 4889923 / ireland@socomore.com

Distributors:

Socomore SASU - Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - France
-Tel. +33 (0)2 97 43 76 90

Manufacturing - Parc Gohelis - 56250 ELVEN France - Tel +33 (0)2 97 43 76 83 - Fax +33 (0)2 97 54 50 26

Socomore Ireland Ltd. - Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922 / Fax +353 21 4889923 / ireland@socomore.com

Competent person responsible for the safety data sheet:

msdsinformation-eu@socomore.com

1.4. Emergency telephone number

France : ORFILA (INRS) +33 (0)1 45 42 59 59

International : CHEMTEL +1-813-248-0585.

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****EC regulation criteria 1272/2008 (CLP)**

⚠ Warning, Flam. Liq. 3, Flammable liquid and vapour.

⚠ Warning, Eye Irrit. 2, Causes serious eye irritation.

Adverse physicochemical, human health and environmental effects:

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOCLEAN A2501 UV SATWIPE PROSAT SOCOSAT

No other hazards

2.2. Label elements

Hazard pictograms:



Warning

Hazard statements:

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 Wear protective gloves and eye/face protection.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire, use a CO2 fire extinguisher to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration $\geq 0.1\%$





SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.


3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification
$\geq 15\%$ - $< 20\%$	propan-2-ol	Index number: CAS: EC: REACH No.: 603-117-00-0 67-63-0 200-661-7 01-2119457558-25	 2.6/2 Flam. Liq. 2 H225  3.3/2 Eye Irrit. 2 H319  3.8/3 STOT SE 3 H336
$\geq 3\%$ - $< 5\%$	3-butoxypropan-2-ol; propylene glycol	Index number: 603-052-00-8	 3.3/2 Eye Irrit. 2 H319

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOCLEAN A2501 UV SATWIPES PROSAT SOCOSAT

	monobutyl ether	CAS: 5131-66-8 EC: 225-878-4 REACH No.: 01-2119475527-28	 3.2/2 Skin Irrit. 2 H315
--	-----------------	--	---

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting. Obtain a medical examination.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

No particular treatment.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

In case of fire, use a CO2 fire extinguisher to extinguish.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

**Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))
SOCOCLEAN A2501 UV SATWIPE PROSAT SOCOSAT****SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, ensure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

7.2. Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Store at ambient temperatures. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

7.3. Specific end use(s)

None in particular

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

Occupational exposure limit values

propan-2-ol - CAS: 67-63-0

- OEL Type: National - STEL: 980 mg/m³, 400 ppm - Notes: France

- OEL Type: National - TWA: 500 mg/m³, 200 ppm - Notes: DFG, Y - Germany

- OEL Type: National - TWA: 999 mg/m³, 400 ppm - STEL: 1250 mg/m³, 500 ppm -

Notes: United Kingdom

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOCLEAN A2501 UV SATWIPES PROSAT SOCOSAT

- OEL Type: ACGIH - TWA(8h): 200 ppm - STEL: 400 ppm - Notes: A4, BEI - Eye and URT irr, CNS impair
- OEL Type: National - TWA: 999 mg/m³, 400 ppm - STEL: 1250 mg/m³, 500 ppm
- OEL Type: OSHA PEL - TWA: 980 mg/m³, 400 ppm
- OEL Type: NIOSH REL - TWA: 980 mg/m³, 400 ppm - STEL: 1225 mg/m³, 500 ppm
- OEL Type: National - TWA: 500 mg/m³, 200 ppm - STEL(30min (Miw)): 1960 mg/m³, 800 ppm - Notes: Österreich
- OEL Type: National - TWA: 900 mg/m³ - STEL: 1200 mg/m³ - Notes: Poland (Dz.U. 2018 pos. 1286)

DNEL Exposure Limit Values

propan-2-ol - CAS: 67-63-0

Worker Industry: 888 mg/kg - Consumer: 319 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 500 mg/kg - Consumer: 89 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 26 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

3-butoxypropan-2-ol; propylene glycol monobutyl ether - CAS: 5131-66-8

Worker Industry: 44 mg/kg b.w./day - Consumer: 16 mg/kg b.w./day - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 270.5 mg/m³ - Consumer: 33.8 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 8.75 mg/kg b.w./day - Exposure: Human Oral - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

propan-2-ol - CAS: 67-63-0

Target: Fresh Water - Value: 140.9 mg/l

Target: Marine water - Value: 140.9 mg/l

Target: Freshwater sediments - Value: 552 mg/kg

Target: Marine water sediments - Value: 552 mg/kg

Target: Soil (agricultural) - Value: 28 mg/kg

Target: Microorganisms in sewage treatments - Value: 2251 mg/l

Target: Water (intermittent discharge) - Value: 140.9 mg/l

Target: Oral (secondary poisoning) (foodstuff) - Value: 160 mg/kg

3-butoxypropan-2-ol; propylene glycol monobutyl ether - CAS: 5131-66-8

Target: Fresh Water - Value: 0.525 mg/l

Target: Marine water - Value: 0.0525 mg/l

Target: Microorganisms in sewage treatments - Value: 10 mg/l

Target: Freshwater sediments - Value: 2.36 mg/kg dw

Target: Marine water sediments - Value: 0.236 mg/kg dw

Target: Soil (agricultural) - Value: 0.16 mg/kg dw

Biological Exposure Index

N.A.

8.2. Exposure controls

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOCLEAN A2501 UV SATWIPES PROSAT SOCOSAT

See below, example of PPE to use.

Eye protection:

Safety goggles (EN 166)

Face protection shield. (EN 166)

Use closed fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable gloves type: NF EN374

NBR (nitrile rubber).

NR (natural rubber, natural latex).

PVC (polyvinyl chloride).

Butyl rubber (isobutylene-isoprene copolymer)

Respiratory protection:

Use adequate protective respiratory equipment.

Use respiratory protection where ventilation is insufficient or exposure is prolonged. Masks such as "A1" brown-color filter (NF EN 14387) are recommended. Always follow all local and federal regulations.

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

Other conditions affecting workers exposure:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes
Physical state:	Liquid coated on wipes	--	--
Colour:	Colourless	--	--
Odour:	N.A.	--	--
Melting point/freezing point:	Not Relevant	--	--
Boiling point or initial boiling point and boiling range:	N.A.	--	--
Flammability:	Flam. Liq. 3, H226	--	--
Lower and upper explosion limit:	N.A.	--	--
Flash point (°C):	26 °C	EN ISO 13736	--

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))
SOCOCLEAN A2501 UV SATWIPES PROSAT SOCOSAT

Auto-ignition temperature:	N.A.	--	--
Decomposition temperature:	N.A.	--	--
pH:	N.A.	--	--
Kinematic viscosity:	N.A.	--	--
Solubility in water:	N.A.	--	--
Solubility in oil:	N.A.	--	--
Partition coefficient n-octanol/water (log value):	N.A.	--	--
Vapour pressure:	N.A.	--	--
Density and/or relative density:	0.955	--	--
Relative vapour density:	N.A.	--	--
Particle characteristics:			
Particle size:	N.A.	--	--

9.2. Other information

No other relevant information

Volatile Organic compounds - VOCs = 30 %

Volatile Organic compounds - VOCs = 288 g/l

N.A. = not available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

None.

**Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))
SOCOCLEAN A2501 UV SATWIPE PROSAT SOCOSAT****SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Toxicological information of the product:

SOCOCLEAN A2501 UV SATWIPE PROSAT SOCOSAT

Acute toxicity

Not classified

Based on available data, the classification criteria are not met

Skin corrosion/irritation

Not classified

Based on available data, the classification criteria are not met

Serious eye damage/irritation

The product is classified: Eye Irrit. 2 H319

Respiratory or skin sensitisation

Not classified

Based on available data, the classification criteria are not met

Germ cell mutagenicity

Not classified

Based on available data, the classification criteria are not met

Carcinogenicity

Not classified

Based on available data, the classification criteria are not met

Reproductive toxicity

Not classified

Based on available data, the classification criteria are not met

STOT-single exposure

Not classified

Based on available data, the classification criteria are not met

STOT-repeated exposure

Not classified

Based on available data, the classification criteria are not met

Aspiration hazard

Not classified

Based on available data, the classification criteria are not met

Toxicological information of the main substances found in the product:

propan-2-ol - CAS: 67-63-0

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 4570 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 20 mg/l - Duration: 8h

Test: LC50 - Route: Inhalation Vapour - Species: Rat > 25000 mg/m³ - Duration: 6 hours

Test: LD50 - Route: Skin - Species: Rabbit = 12.800 mg/kg

Reproductive toxicity:

Test: NOAEL - Route: Oral - Species: Rat = 500 mg/kg

STOT-repeated exposure:

Test: NOAEL - Route: Inhalation - Species: Rat = 1.3 mg/l

Test: NOAEL - Route: Inhalation Vapour - Species: Rat (Male, female) = 12.5 mg/l

**Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))
SOCOCLEAN A2501 UV SATWIPES PROSAT SOCOSAT**

3-butoxypropan-2-ol; propylene glycol monobutyl ether - CAS: 5131-66-8

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 2.700 mg/kg

Test: LD50 - Route: Skin - Species: Rat > 2.000 mg/kg

Test: LC50 - Route: Inhalation Vapour - Species: Rat > 3.5 mg/l

11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration \geq 0.1%

Other toxicological information:

propan-2-ol

Severe eye damage/irritation:

Irritating to eyes

Foetal development:

Toxic effects on foetal development at doses that produce effects in mothers.

No teratogenic effects, NOAEL: 400 mg/kg Maternal No Effect Concentration: 400 mg/kg (rat)

Absence of toxic effects on foetal development. NOAEL: > 480 mg/kg. Maternal No-effect

Concentration: 240 mg/kg (rabbit)

Inhalation:

Irritating to eyes and respiratory tract (vapour, 1.0 mg/l)

-

3-butoxypropan-2-ol; propylene glycol monobutyl ether

Moderate eye irritation, mild corneal lesions

Brief contact may cause moderate skin irritation with local redness.

SECTION 12: Ecological information**12.1. Toxicity**

Adopt good working practices, so that the product is not released into the environment.

SOCOCLEAN A2501 UV SATWIPES PROSAT SOCOSAT

Not classified for environmental hazards

Based on available data, the classification criteria are not met

propan-2-ol - CAS: 67-63-0

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 100 mg/l - Duration h: 48 - Notes: Leuciscus melanotus

Endpoint: LC50 - Species: Fish = 9640 mg/l - Duration h: 96 - Notes: Pimephales promelas

Endpoint: LC50 - Species: Daphnia > 10.000 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae > 100 mg/l - Duration h: 72 - Notes: Scenedesmus subspicatus

Endpoint: EC50 - Species: Daphnia > 100 mg/l - Duration h: 48

Endpoint: NOAEC - Species: Algae = 1800 mg/l - Duration h: 84 - Notes: Algues vertes / Green algae

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 100 mg/l - Duration h: 72 - Notes: Pseudokirchneriella subcapitata

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOCLEAN A2501 UV SATWIPES PROSAT SOCOSAT

c) Bacteria toxicity:

Species: bacteria = 1.050 mg/l

3-butoxypropan-2-ol; propylene glycol monobutyl ether - CAS: 5131-66-8

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish 560-1000 mg/l - Duration h: 96 - Notes: guppy (*Poecilia reticulata*)

Endpoint: EC50 - Species: Algae > 560 mg/l - Duration h: 96 - Notes: *Pseudokirchneriella subcapitata*

Endpoint: EC50 - Species: Daphnia > 1.000 mg/l - Duration h: 3

Endpoint: NOEC - Species: Fish = 180 mg/l - Duration h: 96 - Notes: guppy

Endpoint: NOEC - Species: Daphnia = 560 mg/l - Duration h: 48 - Notes: *Selenastrum*

Endpoint: NOEC - Species: Algae = 560 mg/l - Duration h: 96

c) Bacteria toxicity:

Endpoint: EC50 - Species: bacteria > 1.000 mg/l - Duration h: 3

12.2. Persistence and degradability

propan-2-ol - CAS: 67-63-0

Biodegradability: Readily biodegradable - Duration: 5 days - %: 53 - Notes: Aerobie, activated sludge

Biodegradability: Oxidizes rapidly by photochemical reactions in air.

Biodegradability: Photodegradation (in air) - overall half-life time - Test: Degradation by OH radicals: Direct photolysis - Duration: 33 hours

3-butoxypropan-2-ol; propylene glycol monobutyl ether - CAS: 5131-66-8

Biodegradability: Readily biodegradable

12.3. Bioaccumulative potential

propan-2-ol - CAS: 67-63-0

Estimated not significantly bioaccumulative.

Log Pow <=4

Log Kow 0.05 - Notes: 25°C

3-butoxypropan-2-ol; propylene glycol monobutyl ether - CAS: 5131-66-8

Potentially bioaccumulative.

Low bioconcentration potential

12.4. Mobility in soil

3-butoxypropan-2-ol; propylene glycol monobutyl ether - CAS: 5131-66-8

Mobile

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration >= 0.1%

12.7. Other adverse effects

No harmful effects expected.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

Codes of wastes (Décision 2001/573/EC, Directive 2006/12/EEC, Directive 94/31/EEC on hazardous waste):

15 02 02* absorbents, filter materials (including oil filters not otherwise specified), wiping cloths,

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))
SOCOCLEAN A2501 UV SATWIPE PROSAT SOCOSAT

protective clothing contaminated by dangerous substances

SECTION 14: Transport information



14.1. UN number or ID number

ADR-UN Number: 3175
 IATA-UN Number: 3175
 IMDG-UN Number: 3175

14.2. UN proper shipping name

ADR-Shipping Name: SOLIDS or mixtures of solids (such as preparations and wastes) CONTAINING FLAMMABLE LIQUID, N.O.S. having a flash-point up to 60 °C (propan-2-ol; isopropyl alcohol; isopropanol)
 IATA-Shipping Name: SOLIDS or mixtures of solids (such as preparations and wastes) CONTAINING FLAMMABLE LIQUID, N.O.S. having a flash-point up to 60 °C (propan-2-ol; isopropyl alcohol; isopropanol)
 IMDG-Shipping Name: SOLIDS or mixtures of solids (such as preparations and wastes) CONTAINING FLAMMABLE LIQUID, N.O.S. having a flash-point up to 60 °C (propan-2-ol; isopropyl alcohol; isopropanol)

14.3. Transport hazard class(es)

ADR-Class: 4.1
 ADR - Hazard identification number: 40
 IATA-Class: 4.1
 IATA-Label: 4.1
 IMDG-Class: 4.1

14.4. Packing group

ADR-Packing Group: II
 IATA-Packing group: II
 IMDG-Packing group: II

14.5. Environmental hazards

ADR-Environmental Pollutant: No
 IMDG-Marine pollutant: No
 IMDG-EmS: F-A , S-I

14.6. Special precautions for user

ADR-Subsidiary hazards: -
 ADR-S.P.: 216 274 601
 ADR-Transport category (Tunnel restriction code): 2 (E)
 IATA-Passenger Aircraft: 445
 IATA-Subsidiary hazards: -
 IATA-Cargo Aircraft: 448
 IATA-S.P.: A46
 IATA-ERG: 3L
 IMDG-Subsidiary hazards: -
 IMDG-Stowage and handling: Category B
 IMDG-Segregation: -

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOCLEAN A2501 UV SATWIPES PROSAT SOCOSAT

Q.L.: 1K

Q.E.: E2

14.7. Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Regulation (EU) n. 2021/849 (ATP 17 CLP)

Regulation (EU) n. 2022/692 (ATP 18 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restriction 40

Restrictions related to the substances contained:

Restriction 75

Listed or in compliance with the following international inventories:

N.A.

Labelling of detergents (EC Regulations 648/2004 and 907/2006):

N.A.

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOCOCLEAN A2501 UV SATWIPES PROSAT SOCOSAT

Labelling of biocides (Regulations 1896/2000, 1687/2002, 2032/2003, 1048/2005, 1849/2006, 1451/2007 and Directive 98/8/EC):

N.A.

N.A.

Where applicable, refer to the following regulatory provisions :

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments.

1999/13/EC (VOC directive)

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

Product belongs to category: P5c

15.2. Chemical safety assessment

No

SECTION 16: Other information

N.A.: Not Applicable or Not Available

Full text of phrases referred to in Section 3:

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H315 Causes skin irritation.

Hazard class and hazard category	Code	Description
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3

**Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))
SOCOCLEAN A2501 UV SATWIPES PROSAT SOCOSAT**

This safety data sheet has been completely updated in compliance to Regulation 2020/878.
Paragraphs modified from the previous revision:

SECTION 1: Identification of the substance/mixture and of the company/undertaking
SECTION 2: Hazards identification
SECTION 3: Composition/information on ingredients
SECTION 8: Exposure controls/personal protection
SECTION 9: Physical and chemical properties
SECTION 11: Toxicological information
SECTION 12: Ecological information
SECTION 15: Regulatory information
SECTION 16: Other information

(EC) 1272/2008 [CLP] Yönetmeliğine göre karışımların sınıflandırmasını elde etmek için kullanılan sınıflandırma ve prosedür:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Flam. Liq. 3, H226	On basis of test data
Eye Irrit. 2, H319	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,
Commission of the European Communities
SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van
Nostrand Reinold
CCNL - Appendix 1
Insert further consulted bibliography

Important confidentiality : this document contains confidential information that is proprietary to SOCOMORE. Subject to legal provisions determining otherwise, the distribution, republication or re-transmission of this document, in full or in part, must be limited to clearly identified individuals, either because they use the product, or to provide HSE information. Any communication of this document outside of this framework without our written consent is strictly forbidden.

SOCOMORE strongly advises every recipient of this safety data sheet to read it carefully and to consult experts in the field if necessary or appropriate, in order to understand the information it contains, notably the possible dangers associated with this product. The users must ensure the conformity and completeness of this information with regards to their specific use of the product.

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the responsibility of the purchaser/user to ensure that their activities conform with current legislation in force.

**Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))
SOCOCLEAN A2501 UV SATWIPES PROSAT SOCOSAT**

The information is considered correct, but it is not exhaustive and it shall be used only as a guide which is based on the current knowledge of the substance or mixture and it is applicable to the safety precautions appropriate for the product.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
STOT SE:	May cause drowsiness or dizziness
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
WGK:	German Water Hazard Class.